SikaWall®-168 Plaster



Version	Revision Date:	SDS Number:	Date of last issue: 01.12.2018
2.0	27.08.2020	100000024090	Date of first issue: 01.12.2018
2.0	21.00.2020	100000024090	Date of first issue. 01.12.2010

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier		
Product name	:	SikaWall [®] -168 Plaster
Product code	:	10000024090
Recommended use of the c	hem	ical and restrictions on use
Product use	:	Mortar
Manufacturer or supplier's o	deta	ils
Company	:	Sika Kimia Sdn. Bhd. Lot 689 Nilai Industrial Estate
		71800 Nilai
Telephone	:	+60 6799 1762
Telefax	:	+60 6799 1980
E-mail address	:	EHS@my.sika.com
Emergency telephone num- ber	:	-

SECTION 2: Hazards identification

Classification of the hazardous chemical						
Skin corrosion/irritation	:	Category 2				
Serious eye damage/eye irri- tation	:	Category 1				
Skin sensitisation	:	Category 1				
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)				
Label elements						
Hazard pictograms	:					
Signal word	:	Danger				
Hazard statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.				
Precautionary statements	:	Prevention:				

SikaWall®-168 Plaster



Version 2.0	Revision Date: 27.08.2020	SDS Number: 100000024090	Date of last issue: 01.12.2018 Date of first issue: 01.12.2018
		P264 Wash skin thoroughly	/ fume/ gas/ mist/ vapours/ spray. y after handling. es/ eye protection/ face protection.
		Response:	
		and keep at rest in a position POISON CENTER or doctor P305 + P351 + P338 + P3 water for several minutes. and easy to do. Continue r CENTER or doctor/ physic	HALED: Remove victim to fresh air on comfortable for breathing. Call a or/ physician if you feel unwell. 10 IF IN EYES: Rinse cautiously with Remove contact lenses, if present insing. Immediately call a POISON ian. on or rash occurs: Get medical ad-
Other	hazards which do not	result in classification	

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 60 -<= 100
Cement, portland, chemicals	65997-15-1	>= 20 -< 30

SECTION 4: First aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
		2 / 10

SikaWall®-168 Plaster



/ersion 2.0	Revision Date: 27.08.2020	SDS Number: 100000024090	Date of last issue: 01.12.2018 Date of first issue: 01.12.2018
	important symptoms ffects, both acute and ed	 irritant effects sensitising effects Cough Respiratory disorder Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more and symptoms. Causes skin irritation. May cause an allergic ski Causes serious eye dama May cause respiratory irrit 	age.
Notes	to physician	: Treat symptomatically.	
Extin	5: Firefighting measure guishing media ble extinguishing media		res that are appropriate to local cir-
Suitai		cumstances and the surro	
-		ising from the chemical	
Hazaı ucts	rdous combustion prod-	: No hazardous combustio	n products are known
Speci	ial protective equipmen	t and precautions for fire-fig	ghters
	al protective equipment efighters	: In the event of fire, wear s	self-contained breathing apparatus.
Speci ods	fic extinguishing meth-	: Standard procedure for c	hemical fires.
SECTION	6: Accidental release n	neasures	
Perso	nal precautions protec-	· Use personal protective e	auinment

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
Environmental precautions :	Do not flush into surface water or sanitary sewer system.
Methods and materials for : containment and cleaning up	Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

SikaWall®-168 Plaster



2.0 27.08.202	0 1000002409	Date of first issue: 01.12.2018

SECTION 7: Handling and storage

Handling

Precautions for safe handlin Advice on protection against fire and explosion	-	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
Advice on safe handling	:	Do not breathe vapours/dust. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
Storage		
Conditions for safe storage	, in	cluding any incompatibilities

Conditions for safe storage	:	Keep in a well-ventilated place.
		Observe label precautions. Store in accordance with local regulations.
Further information on stor- age stability	:	Keep in a dry place. No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA (Res- pirable frac- tion)	0.1 mg/m3	MY PEL
		PEL (Respir- able dust)	0.1 mg/m3	MY PEL
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Res-	0.025 mg/m3	ACGIH



SikaWall®-168 Plaster

Version 2.0	Revision Date: 27.08.2020	SDS Nu 1000000		Date of last issue: 01.12.2018 Date of first issue: 01.12.2018		
			pirable par- ticulate mat- ter)	(Silica)		
			TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH	
			TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH	
Ceme	nt, portland, chemicals	65997-15-1	TŴA	10 mg/m3	MY PEL	
			PEL (Respir- able dust)	5 mg/m3	MY PEL	
			PEL (Total dust)	10 mg/m3	MY PEL	
			TWA (Res- pirable par- ticulate mat- ter)	1 mg/m3	ACGIH	
Indivi	dual protection measur	es. such as per	sonal protective	e equipment		
	ace protection	: Safety eyewe	ar complying wit	h an approved sta ent indicates this is		
Skin p	protection		mount of danger	ation to its type, to ous substances, ar		
Respi	ratory protection	ventilation is that exposure The filter clas imum expecte (gas/vapour/a dling the proc	provided or expo es are within reco s for the respirat ed contaminant of aerosol/particulat	es) that may arise entration is exceed	demonstrates re guidelines. e for the max- when han-	
Hygie	ne measures	practice. When using o When using o	do not eat or drin do not smoke.	od industrial hygie k. nd at the end of wo		

SECTION 9: Physical and chemical properties

Appearance	:	powder
Colour	:	grey
Odour	:	characteristic

SikaWall®-168 Plaster



/ersion 2.0	Revision Date: 27.08.2020		SDS Number: 100000024090	Date of last issue: 01.12.2018 Date of first issue: 01.12.2018
Odour	Threshold	:	No data available	
pН		:	Not applicable	
	g point/range / Freezing	:	No data available	
point Boiling	point/boiling range	:	No data available	
Flash	point	:	No data available	
Evapo	ration rate	:	No data available	
Flamm	nability (solid, gas)	:	No data available	
	explosion limit / Upper ability limit	:	No data available	
	explosion limit / Lower ability limit	:	No data available	
Vapou	r pressure	:	No data available	
Relativ	ve vapour density	:	No data available	
Densit	у	:	ca. 1.8 g/cm3 (20 °C (68 °F))	
	lity(ies) ter solubility	:	No data available	
Sol	ubility in other solvents	:	No data available	
	on coefficient: n- I/water	:	No data available	
	gnition temperature	:	No data available	
Decom	position temperature	:	No data available	
Viscos Vis	ity cosity, dynamic	:	No data available	
Vis	cosity, kinematic	:	No data available	
Explos	ive properties	:	No data available	
Oxidizi	ing properties	:	No data available	

SECTION 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.

SikaWall®-168 Plaster



Version 2.0	Revision Date: 27.08.2020	SDS Number: 100000024090	Date of last issue: 01.12.2018 Date of first issue: 01.12.2018
Possik tions	pility of hazardous reac-	: No hazards to be specially	mentioned.
Condi	tions to avoid	: No data available	
Incom	patible materials	: No data available	
No de	composition if stored and	applied as directed.	
SECTION	11: Toxicological inforn	nation	
Inform expos	ation on likely routes of ure	: None known.	
	toxicity assified based on availab	le information.	
	corrosion/irritation es skin irritation.		
	u s eye damage/eye irrit a es serious eye damage.	ation	
Respi	ratory or skin sensitisa	tion	
	sensitisation ause an allergic skin read	tion.	
-	ratory sensitisation assified based on availab	le information.	
	cell mutagenicity assified based on availab	le information.	
	n ogenicity assified based on availab	le information.	
-	ductive toxicity assified based on availab	le information.	
	- single exposure ause respiratory irritation		
	- repeated exposure assified based on availab	le information.	
	ation toxicity assified based on availab	le information	

Ecotoxicity No data available

SikaWall[®]-168 Plaster



/ersion 0	Revision Date: 27.08.2020		SDS Number: 100000024090	Date of last issue: 01.12.2018 Date of first issue: 01.12.2018
	stence and degradabi ta available	lity		
	cumulative potential ta available			
	ity in soil ta available			
Other	adverse effects			
<u>Produ</u> Additio matior	onal ecological infor-	: Ther	e is no data available	for this product.
SECTION	13: Disposal informat	ion		
Dispo	sal methods			
-	from residues	cal o	r used container.	, waterways or ditches with chemi- management company.
Conta	minated packaging	Disp	ty remaining contents. ose of as unused proc ot re-use empty conta	duct.

SECTION 14: Transport information

International Regulations

UNRTDG Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

SikaWall[®]-168 Plaster



Version	Revision Date:	SDS Number:	Date of last issue: 01.12.2018
2.0	27.08.2020	10000024090	Date of first issue: 01.12.2018

Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Date format	:	dd.mm.yyyy		
Full text of other abbreviations				
ACGIH MY PEL	:	USA. ACGIH Threshold Limit Values (TLV) Malaysia. Occupational Safety and Health (Use and Stand- ards of Exposure of Chemicals Hazardous to Health) Regula- tions 2000.		
MY PEL	:	Malaysia. Factories and Machinery (Mineral Dust) Regulations - Permissible Exposure Limit		
ACGIH / TWA MY PEL / TWA MY PEL / PEL ADR	:	8-hour, time-weighted average Eight-hour time-weighted average airborne concentration Permissible exposure limit (PEL) European Agreement concerning the International Carriage of Dangerous Goods by Road		
CAS DNEL EC50	:	Chemical Abstracts Service Derived no-effect level Half maximal effective concentration		
GHS IATA IMDG	:	Globally Harmonized System International Air Transport Association		
LD50	:	International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)		
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)		
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978		
OEL PBT	:	Occupational Exposure Limit Persistent, bioaccumulative and toxic		
PNEC REACH	:	Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency		
SVHC vPvB	:	Substances of Very High Concern Very persistent and very bioaccumulative		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.


Changes as compared to previous version !

MY / EN

SikaWall®-168 Plaster

Version Revision Date: 2.0 27.08.2020

SDS Number: 100000024090



R