

PRODUCT DATA SHEET

SikaWall®-168 Plaster

HIGH PERFORMANCE, CEMENTITIOUS RENDER

DESCRIPTION

SikaWall®-168 Plaster is a durable, high quality cementitious prepacked mortar specially formulated for plastering work on concrete surfaces, brickwalls and blockwalls. It provides superior bond strength to the substrates and can be used for both internal and external applications.

USES

SikaWall®-168 Plaster is designed for plastering on concrete surfaces, brickwalls, blockwalls and lightweight autoclaved aerated blocks. It is recommended for use as a joint mortar for brickworks, blockworks and bedding to receiving wall tiles. It is suitable for internal and external applications.

CHARACTERISTICS / ADVANTAGES

- Excellent bond strength.
- Minimizes shrinkage cracking.
- Consistent quality.
- Convenient in handling, mixing and application.
- Weather resistant and durable

PRODUCT INFORMATION

Packaging	<ul style="list-style-type: none"> ▪ 25 kg bag ▪ 40 kg bag
Appearance / Colour	Grey powder
Shelf Life	6 months from the date of production
Storage Conditions	Store properly in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Protect from direct sunlight.
Maximum Grain Size	≤ 1.2 mm

TECHNICAL INFORMATION

Tensile Adhesion Strength	≥ 0.7 N/mm ² (at 14 days)	(EN 1015-12)
----------------------------------	--------------------------------------	--------------

APPLICATION INFORMATION

Mixing Ratio	Packaging	Water consumption per bag
	25 kg	4.1–4.6 L
40 kg	6.6–7.4 L	

Fresh Mortar Density	1.8–1.9 kg/l
Consumption	1.5–1.6 kg/m ² per mm * This may only serve as a guideline. It is highly recommended to run a trial on site to determine the actual coverage.
Layer Thickness	5–15 mm per layer (30 mm max.)
Pot Life	30–45 minutes

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Surface should be structurally sound, clean, free from oil, grease, dust deposits and other contaminants that may affect adhesion. Dry and porous substrates should be dampened before application of SikaWall®-168 Plaster.

MIXING

Add clean water to SikaWall®-168 Plaster and mix thoroughly using a hand-held or mechanical mixer for 3–5 minutes until a homogenous lump-free paste is achieved. Allow mixture to stand for a few minutes for additives to dissolve and mix is ready for use.

APPLICATION

Apply SikaWall®-168 Plaster onto moist, clean substrate using a wooden/steel float or steel trowel while the mix is still workable. It can be applied at a recommended thickness of 5–15 mm per layer of application and up to a total build-up thickness of 30 mm. Ensure that each layer is dry before applying the subsequent layer.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate, 71800 Nilai
Negeri Sembilan D.K., Malaysia
Phone: +606-7991762
Fax: +606-7991980
e-mail: info@my.sika.com
Website: www.sika.com.my



Product Data Sheet

SikaWall®-168 Plaster
February 2020, Version 02.01
021820101000000052

SikaWall-168Plaster-en-MY-(02-2020)-2-1.pdf