SikaWall®-190 Coarse Grey



Version Rev	vision Date:	SDS Number:	Date of last issue: 20.04.2020
5.0 26.0	08.2020	00000606596	Date of first issue: 12.03.2015

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier Product name		
Floduct name	•	SikaWall [®] -190 Coarse Grey
Product code	:	00000606596
Manufacturer or supplier's o	deta	ils
Company	:	Sika Kimia Sdn. Bhd. Lot 689 Nilai Industrial Estate 71800 Nilai
Telephone	:	+60 6799 1762
Telefax	:	+60 6799 1980
E-mail address	:	EHS@my.sika.com
Emergency telephone num- ber	:	-

SECTION 2: Hazards identification

Classification of the hazardous chemical						
Skin corrosion/irritation	:	Category 2				
Serious eye damage/eye irri- tation	:	Category 1				
Skin sensitisation	:	Category 1				
Label elements						
Hazard pictograms	:					
Signal word	:	Danger				
Hazard statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage.				
Precautionary statements	:	Prevention:				
		P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ eye protection/ face protection.				
		Response:				
		P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON				

SikaWall[®]-190 Coarse Grey



Version 5.0	Revision Date: 26.08.2020	SDS Number: 000000606596	Date of last issue: 20.04.2020 Date of first issue: 12.03.2015
		vice/ attention.	ian. on or rash occurs: Get medical ad- ed clothing and wash before reuse.
Other	hazards which do not	result in classification	

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 60 -<= 100
Cement, portland, chemicals	65997-15-1	>= 10 -< 20
Limestone	1317-65-3	>= 5 -< 10

SECTION 4: First aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	:	irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms.

SikaWall®-190 Coarse Grey



Version 5.0			SDS Number: 000000606596	Date of last issue: 20.04.2020 Date of first issue: 12.03.2015	
			Causes skin irritation. May cause an allergic skin reacti Causes serious eye damage.	on.	
Not	es to physician	:	Treat symptomatically.		
SECTIO	N 5: Firefighting measure	es			
Ext	inguishing media				
Sui	table extinguishing media	:	Use extinguishing measures that cumstances and the surrounding		
Phy	sicochemical hazards ar	isiı	ng from the chemical		
Haz ucts		:	No hazardous combustion produ	cts are known	
Spe	ecial protective equipmer	nt a	nd precautions for fire-fighters		
	ecial protective equipment firefighters	:	In the event of fire, wear self-con	tained breathing apparatus.	
Spe ods		:	Standard procedure for chemical	fires.	

SECTION 6: Accidental release measures

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
Methods and materials for containment and cleaning up	:	Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handlin	ng	
Advice on protection against fire and explosion	:	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
Advice on safe handling	:	Do not breathe vapours/dust. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing.

SikaWall®-190 Coarse Grey



Version 5.0	Revision Date: 26.08.2020		SDS Number: 000000606596	Date of last issue: 20.04.2020 Date of first issue: 12.03.2015
		Pers ma, not use Smo plica Follo	allergies, chronic or rec be employed in any pro- d. oking, eating and drinkin ation area.	section 8. in sensitisation problems or asth- urrent respiratory disease should cess in which this mixture is being g should be prohibited in the ap- easures when handling chemical
Stora	ge			
Cond	itions for safe storage,	includi	ng any incompatibilitie	95
Cond	itions for safe storage	plac		d in a dry and well-ventilated cal regulations.
	er information on stor- tability		p in a dry place. decomposition if stored a	and applied as directed.

SECTION 8: Exposure controls and personal protection

•				
Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
		exposure)	concentration	
Quartz (SiO2)	14808-60-7	TWA (Res-	0.1 mg/m3	MY PEL
		pirable frac-		
		tion)		
		PEL (Respir-	0.1 mg/m3	MY PEL
		able dust)	, , , , , , , , , , , , , , , , , , ,	
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-	Ŭ	
		ticulate mat-		
		ter)		
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-	(Silica)	
		ticulate mat-	()	
		ter)		
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-	(Silica)	
		ticulate mat-	· · /	
		ter)		
Cement, portland, chemicals	65997-15-1	TŴA	10 mg/m3	MY PEL
÷		PEL (Respir-	5 mg/m3	MY PEL
		able dust)	, č	
		PEL (Total	10 mg/m3	MY PEL

Control parameters



SikaWall®-190 Coarse Grey

Version 5.0	on Revision Date: SDS Number: 26.08.2020 00000606596			Date of last issue: 20.04.2020 Date of first issue: 12.03.2015		
			dust)			
			TWA (Res- pirable par- ticulate mat- ter)	1 mg/m3	ACGIH	
Limes	tone	1317-65-3	TWA (partic- ulate)	10 mg/m3 (Calcium car- bonate)	MY PEL	
			Further information: The value is for particulate matter containing no asbestos and <1% crystalline silica			
			PEL (Respir- able dust)	5 mg/m3	MY PEL	
			PEL (Total dust)	10 mg/m3	MY PEL	
	dual protection meas					
Eye/fa	ace protection			th an approved sta ent indicates this is		
Skin p	protection		mount of danger	ation to its type, to ous substances, ar		
Respi	ratory protection	ventilation is that exposurd The filter clas imum expect (gas/vapour/ dling the prod	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.			
Hygie	ne measures	practice. When using When using	5 ,5 ,			

SECTION 9: Physical and chemical properties

Appearance	:	powder
Colour	:	light grey
Odour	:	odourless
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing point	:	No data available
		5/9

SikaWall®-190 Coarse Grey



Versi 5.0	on Revision Date: 26.08.2020		SDS Number: 000000606596	Date of last issue: 20.04.2020 Date of first issue: 12.03.2015
	Boiling point/boiling range	:	No data available	
	Flash point		Not applicable	
	Evaporation rate	:	No data available	
	Flammability (solid, gas)	:	No data available	
	Upper explosion limit / Upper flammability limit	:	No data available	
	Lower explosion limit / Lower flammability limit	:	No data available	
	Vapour pressure	:	No data available	
	Relative vapour density	:	No data available	
	Density	:	No data available	
	Bulk density Solubility(ies)	:	1,000 kg/m3	
	Water solubility	:	soluble	
	Solubility in other solvents	:	No data available	
	Partition coefficient: n- octanol/water	:	No data available	
	Auto-ignition temperature	:	No data available	
	Decomposition temperature		No data available	
	Viscosity Viscosity, dynamic	:	No data available	
	Viscosity, kinematic	:	Not applicable	
	Explosive properties	:	No data available	
	Oxidizing properties	:	No data available	

SECTION 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	No hazards to be specially mentioned.
Conditions to avoid	÷	No data available

SikaWall®-190 Coarse Grey



Version 5.0	Revision Date: 26.08.2020	SDS Number: 000000606596	Date of last issue: 20.04.2020 Date of first issue: 12.03.2015
Incom	patible materials	: No data available	
No de	composition if stored and	applied as directed.	
	•		
SECTION	11: Toxicological inform	ation	
Inform expos	nation on likely routes of ure	None known.	
	e toxicity assified based on availabl	e information.	
	corrosion/irritation		
	es skin irritation.		
	us eye damage/eye irrita es serious eye damage.	ation	
	iratory or skin sensitisat	ion	
	sensitisation ause an allergic skin reac	tion.	
Respi	i ratory sensitisation assified based on availabl		
	cell mutagenicity assified based on availabl	e information.	
	nogenicity assified based on availabl	e information.	
-	oductive toxicity assified based on availabl	e information.	
STOT	- single exposure		
	assified based on availabl	e information.	
	 repeated exposure assified based on available 	e information	
	ation toxicity		
	assified based on availabl	e information.	
SECTION	12: Ecological informati	on	
Ecoto No da	oxicity ta available		
	stence and degradability	1	
	ta available	,	
Bioac	cumulative potential		

No data available

SikaWall[®]-190 Coarse Grey



Versio 5.0	n Revision Date: 26.08.2020		SDS Number: 000000606596	Date of last issue: 20.04.2020 Date of first issue: 12.03.2015	
	Mobility in soil No data available				
C	Other adverse effects				
A	Product: Additional ecological infor- mation	:	There is no data available for	this product.	
SECT	[ION 13: Disposal information	tion			
	Disposal methods				
V	Waste from residues		Do not contaminate ponds, w cal or used container. Send to a licensed waste mar	aterways or ditches with chemi- nagement company.	
(Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.				

SECTION 14: Transport information

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

SikaWall[®]-190 Coarse Grey



Version 5.0	Revision Date: 26.08.2020		SDS Number: 000000606596	Date of last issue: 20.04.2020 Date of first issue: 12.03.2015		
Date format		:	dd.mm.yyyy			
Fu	Ill text of other abbreviatio	ons				
AC	CGIH		USA. ACGIH Threshold Limit Valu	ies (TLV)		
	YPEL	÷	Malaysia. Occupational Safety and Health (Use and Stand-			
		•	ards of Exposure of Chemicals Ha tions 2000.			
M	Y PEL	•	Malaysia. Factories and Machiner - Permissible Exposure Limit	y (Mineral Dust) Regulations		
AC	CGIH / TWA	•	8-hour, time-weighted average			
	Y PEL / TWA	÷	Eight-hour time-weighted average airborne concentration			
	Y PEL / PEL	:	Permissible exposure limit (PEL)			
A	DR	:	European Agreement concerning	the International Carriage of		
			Dangerous Goods by Road	-		
CA	AS	:	Chemical Abstracts Service			
	NEL	:	Derived no-effect level			
	C50	: Half maximal effective concentration		on		
	HS	:	: Globally Harmonized System			
	ТА	: International Air Transport Association				
	IDG	: International Maritime Code for Dangerous Goods				
	050	:	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)			
LC	C50	:	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)			
M	ARPOL	:	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978			
O	EL	: Occupational Exposure Limit				
PE	ЗТ	:	Persistent, bioaccumulative and to	oxic		
Pl	NEC	:	Predicted no effect concentration			
RI	EACH	:	Regulation (EC) No 1907/2006 of and of the Council of 18 December istration, Evaluation, Authorisation cals (REACH), establishing a Euro	er 2006 concerning the Reg- n and Restriction of Chemi-		
S١	/HC	:	Substances of Very High Concern			
vF	PvB	: Very persistent and very bioaccumulative				

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

MY / EN