
Sikalastic®-632 R



SECTION 1: Identification of the hazardous chemical and of the supplier

Product name : Sikalastic®-632 R

Product code : 100000017461

Type of product : liquid

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

 Telephone
 : +60 6799 1762

 Telefax
 : +60 6799 1980

 E-mail address
 : EHS@my.sika.com

Emergency telephone

number

Contact point

SECTION 2: Hazards identification

Classification of the hazardous chemical

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Hazardous to the aquatic

environment - chronic hazard

: Category 3

Label elements

Hazard pictograms





Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P264 Wash skin thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam for extinction.

Sikalastic®-632 R



Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
xylene	1330-20-7	>= 5 - < 10
N,N-dibenzyliden polyoxypropylene diamine (polymer)	136855-71-5	>= 5 - < 10
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	>= 3 - < 5

SECTION 4: First aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

: irritant effects Dermatitis

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.
Causes skin irritation.

Notes to physician : Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Sikalastic®-632 R

SDS Number: 100000017461 Version 1.0 Revision Date: 19.03.2019

Dry chemical

Unsuitable extinguishing

media

Water

Physicochemical hazards arising from the chemical

Hazardous combustion

products

: No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against

fire and explosion

: Use explosion-proof equipment. Keep away from

heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).


Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

Sikalastic®-632 R



(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7	TWA	100 ppm 434 mg/m3	MY PEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH

Individual protection measures, such as personal protective equipment

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Sikalastic®-632 R

Version 1.0 SDS Number: 100000017461 Revision Date: 19.03.2019

Sika ®

SECTION 9: Physical and chemical properties

Appearance : liquid

Colour : various

Odour : mild

Odour Threshold : No data available

pH : No data available

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : No data available

Flash point : ca. 43 °C (109 °F)

Method: closed cup

Evaporation rate : No data available

Flammability : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0.1 hPa (0.1 mmHg)

Relative vapour density : No data available

Density : ca. 1.4 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 4,300 mPa.s (25 °C)

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Explosive properties : No data available

Molecular weight : No data available

Sikalastic®-632 R

Version 1.0 SDS Number: 100000017461 Revision Date: 19.03.2019

SECTION 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of : None known.

exposure

Acute toxicity

Not classified based on available information.

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,700 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Sikalastic®-632 R

Version 1.0 SDS Number: 100000017461 Revision Date: 19.03.2019

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

Components:

xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.3 mg/l

Exposure time: 96 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological

information

: Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal information

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3

Sikalastic®-632 R

Version 1.0 SDS Number: 100000017461 Revision Date: 19.03.2019

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III

Labels : Flammable Liquids

366

Packing instruction (cargo

aircraft)

Packing instruction : 355

(passenger aircraft)

IMDG-Code

UN number : UN 1263 Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!