

# PENTENS CUREHARD MY

Hardening Compound/Curing

## Product Data Sheet

### Description

PENTENS CUREHARD MY is a liquid applied, styrene acrylic clear resin. It is designed to give superior resistance to water retention for newly freshly placed concrete. PENTENS CUREHARD MY impregnate and penetrate within the concrete surface which provides good wear resistant.

### Uses

On freshly-placed concrete:

- Floor hardener
- Curing compound

On hardened concrete:

- Floor hardener

### Advantages

- Seals moisture in freshly placed concrete for curing and provides a hard and dust-free surface.
- The dry coating resists oil, grease, stain and short exposure to gasoline.
- On hardened concrete, it impregnates into the concrete making it easy to clean and maintain the floor.
- Easy to apply and dries quickly.

### Technical & Physical Data

Form	Clear liquid
Specific Gravity (25°C)	0.88
Consumption	On freshly-placed concrete ~ 5 m <sup>2</sup> /litre On dry, hardened concrete ~ 10 m <sup>2</sup> /litre/coat (2 coats required)
Shelf Life and Storage	1 year from the date of production when stored in original unopened packaging in a cool, dry place
Packaging	20 kg/pail 200 kg/drum

### Important Note

The material must be stored indoor to avoid being exposed to direct sunlight, wind or rain. Keep the material away from fire or smoke.

## Instruction for Use

### As a curing agent

Apply PENTENS CUREHARD MY with a low pressure spray gun immediately after concrete finishing.

### As a hardener

After 28 days of the casting of the concrete (depending on the curing conditions), apply 1 – 2 coats of PENTENS CUREHARD MY on the dry surface with a roller, spray or brush.

### Safety

Impervious gloves and barrier cream should be used when handling these products. Eye protection should be worn. In case of contact with eyes, rinse thoroughly with plenty of water and seek medical advice if symptoms persist. If contact with skin occurs, it must be removed before curing takes place. Wash off with an industrial skin cleanser followed by plenty of soap and water. Do not use solvent. Ensure adequate ventilation when using these products.

PINTAS TRADING SDN BHD

**PENTENS**



### UFON NANO-CHEMICAL LTD.

8F, No.2, Lane 348, Sec 2, Chung-Shang Road,  
Chung Ho City, Taipei Hsien, Taiwan, R.O.C.  
Tel: +886 2 2240 0220 Fax: +886 2 2242 6536  
URL: [www.pentens.com](http://www.pentens.com)  
E-mail: [pentens@ms35.hinet.net](mailto:pentens@ms35.hinet.net)

### DONG JI (M) SDN. BHD.

No.8, Jalan TPP 5/7, Taman Perindustrian Puchong,  
47100 Puchong Selangor, Malaysia.  
Tel: +603 8060 4396 Fax: +603 8060 4394  
URL: [www.pentens.com.my](http://www.pentens.com.my)  
E-mail: [dji@pentens.com.my](mailto:dji@pentens.com.my)