

SAFETY DATA SHEET

RENDEROC TG

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RENDEROC TG
 Product number 2243004AE1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cementitious overlay

1.3. Details of the supplier of the safety data sheet

Supplier Al Gurg Fosroc LLC
 PO Box 657
 Dubai
 United Arab Emirates
 + 971 4 2858606

1.4. Emergency telephone number

Emergency telephone +97142039699 (08:00 to 16:30) // +971506258232 (16:30 to 08:00)GMT+4

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified
 Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335
 Environmental hazards Not Classified

Human health Dust or splashes from the mixture may cause permanent eye damage. Dust may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Dust has an irritating effect on moist skin. Prolonged contact with moist or wet product may cause burns. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

Environmental The product will harden into a solid mass in contact with water and moisture. The resultant material is not biodegradable.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H315 Causes skin irritation.
 H335 May cause respiratory irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.

RENDEROC TG

Precautionary statements

P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container in accordance with national regulations.

Contains ORDINARY PORTLAND CEMENT

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ORDINARY PORTLAND CEMENT	30-60%
---------------------------------	---------------

CAS number: 65997-15-1	EC number: 266-043-4
------------------------	----------------------

Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Irrit. 2 - H315	Xi; R37/38, R41. R43
Eye Irrit. 2 - H319	
STOT SE 3 - H335	

CALCIUM CARBONATE	30-60%
--------------------------	---------------

CAS number: 1317-65-3

Classification	Classification (67/548/EEC or 1999/45/EC)
Not Classified	-

CSA EXPANSIVE AGENT	1-5%
----------------------------	-------------

CAS number: 1305-78-8

Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Irrit. 2 - H315	Xi;R36/37/38.
Eye Irrit. 2 - H319	
STOT SE 3 - H335	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information No personal protective equipment is needed for first aid responders. First aid workers should avoid contact with wet cement or wet cement containing preparations.

Inhalation Move affected person to fresh air at once. Dust in throat and nasal passages should clear spontaneously. Get medical attention if irritation persists or later develops, or if discomfort, coughing or other symptoms persist.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin contact Wash immediately with copious quantities of water. Remove contaminated clothing immediately. Obtain medical advice if skin orders develop.

RENDEROC TG

Eye contact Do not rub eye. Remove any contact lenses and open eyelids wide apart. Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for 30 minutes. Get medical attention. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

Ingestion Ingestion of large doses may result in irritation to the gastrointestinal tract.

Skin contact May have an irritating effect on moist skin after prolonged contact, or may cause dermatitis after repeated contact.
Prolonged skin contact with wet preparation may cause serious burns without pain being felt, including through clothing.

Eye contact Eye contact may cause serious and potentially irreversible injuries.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Water used for fire extinguishing, which has been in contact with the product, may be corrosive. No unusual fire or explosion hazards noted.

Hazardous combustion products No known hazardous decomposition products.

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

Special protective equipment for firefighters Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of dust. Use work methods which minimize dust production. Avoid contact with eyes and prolonged skin contact. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Collect and dispose of spillage as indicated in Section 13. Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

RENDEROC TG

Methods for cleaning up

Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Dry material: Collect powder using special dust vacuum cleaner with particle filter. Alternatively, damp powder with fine spray (to avoid dust formation) and remove slurry. Place into container and allow to solidify before disposal as described in section 13. Wet material: Clean up wet material and place in a container. Allow to dry and solidify before disposal as described in section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Avoid contact with skin and eyes. Avoid generation and spreading of dust. Avoid inhalation of dust. Mechanical ventilation or local exhaust ventilation may be required. Change contaminated clothing. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry and cool place. Unsuitable container materials: Aluminium. The product contains less than 2 mg chromate/kg dry cement, and this limit will not be exceeded for 12 months from the packing date stated on the packaging. Seal opened containers and use up as soon as possible. To be stored out of reach of children in its original packaging in a dry place.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ORDINARY PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

CALCIUM CARBONATE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

WEL = Workplace Exposure Limit

ORDINARY PORTLAND CEMENT (CAS: 65997-15-1)

DNEL

Workers - Inhalation; Short term : 3 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.

RENDEROC TG

Personal protection	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. This product may present a chromate (VI) allergy risk. It contains a chromate reducing agent, but users should wear appropriate personal protective equipment.
Eye/face protection	The following protection should be worn: Chemical splash goggles. (conform EN 166)
Hand protection	Use impervious, abrasion and alkali resistant gloves. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.
Other skin and body protection	Use barrier creams to prevent skin contact. Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	<p>This product contains silica sands.</p> <p>The grain size distribution of silica sand present means that it is not classified as hazardous. However, any respirable crystalline dust generated by secondary processing may cause health effects.</p> <p>Prolonged and /or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness.</p> <p>Occupational exposure to respirable crystalline silica dust should be monitored and controlled</p>
Respiratory protection	Wear a respirator fitted with the following cartridge: Particulate filter, type P2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Granules.
Colour	Grey.
Odour	Odourless.
Odour threshold	Not relevant.
pH	pH (concentrated solution): >12
Melting point	>1250°C
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	The product is not flammable.
Other flammability	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	1.2 @ 20°C
Bulk density	Not determined.
Solubility(ies)	Insoluble in water.

RENDEROC TG

Partition coefficient	Not available.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not applicable.
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information	Not available.
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	When mixed with water, hardens to form a stable mass that is not reactive in normal conditions.
-------------------	---

10.2. Chemical stability

Stability	When stored under humid conditions, the chromate neutralization will decrease. Stable under the prescribed storage conditions. This product contains a chromate reducing agent to reduce the risk of allergic dermatitis caused by chromium (VI). This product has a shelf life. If not stored in accordance with packaging instructions (sealed and dry), there is an increased risk of the presence of hexavalent chromate leading to an increased risk of an allergic reaction.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not known. Will not polymerise.
---	---------------------------------

10.4. Conditions to avoid

Conditions to avoid	Water, moisture.
----------------------------	------------------

10.5. Incompatible materials

Materials to avoid	Acids Chemically-active metals.
---------------------------	---------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	No known hazardous decomposition products.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin sensitisation

Skin sensitisation	Some individuals may exhibit eczema upon exposure to wet cement caused either by the high pH which induces irritant contact dermatitis, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis. The cement contains a soluble Cr (VI) reducing agent and as long as the mentioned period of effectiveness is not exceeded, a sensitising effect is not expected.
---------------------------	--

RENDEROC TG

Inhalation	Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to cement dust.
Ingestion	May cause irritation of mouth, throat and digestive tract.
Skin contact	This product is strongly irritating. Prolonged contact may cause burns. May cause sensitisation by skin contact.
Eye contact	Irritating and may injure eye tissue if not removed promptly.
Acute and chronic health hazards	Repeated and/or prolonged contact may lead to dermatitis

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Acute toxicity - fish Not determined.
The product is not expected to be hazardous to the environment. The addition of cements to water will, however, cause the pH to rise and may therefore be toxic to aquatic life in some circumstances.

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility The product hardens to a solid, immobile substance. The product is not volatile but may be spread by dust-raising handling.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not empty into drains, sewers or water courses. Cement that has exceeded its shelf life: when demonstrated that it contains more than 0.0002% Cr (VI), the product shall not be used other than in controlled closed and totally automated processes. It may be recycled and/or treated again with a reducing agent.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Note that fully cured material is not considered as hazardous waste.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

RENDEROC TG

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	19/05/2015
Revision	4

RENDEROC TG

Hazard statements in full

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.