

## **Product Advantages:**

- Heavy Duty design, apply to AC380V50HZ.
- Imported high quality pump station, lifting is stable.
- Patended satey system on platform, ensure the table decline in the course of an obstacles stop falling.
- To using scissors desiggn, with overload protecting your safety.
- With safety wedge to facilitate maintenance.
- The products are widely used in manufacturing, maintenance industries.







HW4001

Model	Rated Lifting Capacity(kg)	Min Height/Max Height(mm)	Platform size(mm)	Base size(mm)	Elevating time(S)	Power parameters	N .W.(kg)
HW1001	1000	205/990	1300x820	1240x640	20-25	380V/50HZ	160
HW1002	1000	205/990	1600x1000	1240x640	20-25	380V/50HZ	186
HW1003	1000	240/1300	1700x850	1580x640	30-35	380V/50HZ	200
HW1004	1000	240/1300	1700×1000	1580x640	30-35	380V/50HZ	210
HW1005	1000	240/1300	2000x850	1580x640	30-35	380V/50HZ	212
HW1006	1000	240/1300	2000x1000	1580x640	30-35	380V/50HZ	223
HW1007	1000	240/1300	1700x1500	1580x1320	30-40	380V/50HZ	365
HW1008	1000	240/1300	2000×1700	1580x1320	30-40	380V/50HZ	430
HW2001	2000	230/1000	1300x850	1220x785	20-25	380V/50HZ	235
HW2002	2000	230/1000	1600×1000	1220x785	20-25	380V/50HZ	268
HW2003	2000	250/1300	1700x850	1600x785	25-35	380V/50HZ	289
HW2004	2000	250/1300	1700×1000	1600x785	25-35	380V/50HZ	300
HW2005	2000	250/1300	2000x850	1600x785	25-35	380V/50HZ	300
HW2006	2000	250/1300	2000x1000	1600x785	25-35	380V/50HZ	315
HW2007	2000	250/1400	1700x1500	1600x1435	25-35	380V/50HZ	415
HW2008	2000	250/1400	2000x1800	1600x1435	25-35	380V/50HZ	500
HW4001	4000	240/1050	1700x1200	1600x900	30-40	380V/50HZ	375
HW4002	4000	240/1050	2000x1200	1600x900	30-40	380V/50HZ	405
HW4003	4000	300/1400	2000x1000	1980x900	30-40	380V/50HZ	470
HW4004	4000	300/1400	2000x1200	1980x900	35-40	380V/50HZ	490
HW4005	4000	300/1400	2200x1000	1980x900	35-40	380V/50HZ	480
HW4006	4000	300/1400	2200x1200	1980x900	35-40	380V/50HZ	505
HW4007	4000	350/1300	1700x1500	1620x1400	35-45	380V/50HZ	570
HW4008	4000	350/1300	2200x1800	1620x1400	35-45	380V/50HZ	655