



## Standard equipment

- Proportional controls
- Automatic Pothole Protection
- 2WD
- Emergency lowering system
- Emergency stop button
- Onboard diagnostic system
- Tilt sensor with alarm
- Low volt age alarm
- Horn
- Hour Meter
- Forklift pockets
- Charger protection
- Charge indicator
- Flashing beacon
- Can Bus Technology
- Controller languages choose

Model	GTWZ6-200	GTWZ7.5-200	GTWZ7.5-200B	GTWZ9-200
Max. Platform Height (m)	6	7.5	7.5	9
Working Height (m)	8	9.5	9.5	11
Platform Size (m)	0.78x0.7	0.78x0.7	1.0x0.7	1.0x0.7
Capacity (kg)	125	125	200	150
Min Turning Radius (mm)	1.15	1.15	1.28	1.28
Drive wheel size (mm)	230x80		250x80	
Gradeability (%)	25			
Lifting Motor (V/KW)	24V/2kw			
Max. working slope	1.5/3%			
Ground Clearance (mm)	50			
Battery (V/Ah)	2x12/115			
Charger (V/Ah)	24v/12A			
Drive Motor	2x24V/0.4KW		2x24V/0.5KW	
Overall Length (m)	1.4		1.5	
Overall Width (m)	0.8		1	
Overall Height (m)	1.98		2.08	
Weight (kg)	850	880	1100	1250