



Model	NRS15/25	NRS15/30	NRS15/35	NRS15/40	NRS15/45
Drive Unit	Electric				
Load Capacity(kg)	1500				
Load Center(mm)	500				
Tyre type(mm)	Polyurethane				
Front tyre dimensions(mm)	180x55				
Rear tyre dimensions(mm)	130x55				
Traction wheel(mm)	230x75				
Wheels quantity front/rear(x=traction)	1x+2/2				
Wheels base(mm)	1480				
wheel-base(Load wheel/Balance wheel)(mm)	946/718				
Ground clearance(mm)	45				
Reach distance(mm)	590				
Travel Position tiller height(mm)	1300				
Lift Height(mm)	2500	3000	3500	4000	4500
Closed Height(m)	1720				
Overall Length(without standing board)(mm)	2230				
Forks clearance from the ground(mm)	35				
Aisle Width for pallets 1000x1200 lenthways(m)	2570				
Aisle Width for pallets 800x1200 lenthways(m)	2520				
Forks dimensions(mm)	920x100x35				
Total width(mm)	1050/850(Body Width)				
Forks, adjustable(mm)	200-620				
Forks, tilt forward/back	4-Feb				
Minimum turning radius(mm)	1785/2160(open pedal)				
Lifting speed(lade/unlade)(mm/s)	150/100				
Lowering speed(lade/unlade)(mm/s)	500				
Traction speed(lade/unlade)(km/h)	06/05				
Maximum grade ability(lade/unlade)	10/5				
Traction Motor(Kw)	1.5				
Lift Motor(Kw)	3				
Battery volt/ampere(V/Ah)	2Vx12/270				
Battery Weight(kg)	240				
Breaking System	Electromagnetic/Regenerative				