

used IP communication method and USB flash disk, TA500 is the most powerful simple attendance system for your small and medium offices.

*Made to order



Plug and Play

TA500 is easy to operate, connect it to the power source and it's ready to roll! Comes with in-built battery, you can make it portable for your convenience.



Intuitive Navigation

Equipped with colored screen LCD and intuitive icons, navigation in TA500 is made simple.











Easy Data Management

IP communication and USB Flash disk are available for your choice of connectivity



Sturdy Exterior

Made from robust materials, TA500 can stand the wear and tear for years to come and it comes with 3 years limited warranty.



Versatile and Secured Verification

TA500 gives you a variety of verification options such fingerprint, password or card, or combination of options, providing you security and versatility you



Small in Size, Large in Storage

The compact TA500 can contain up to 2,000 fingerprints and 80,000 transaction logs, more than for sufficient your office requirements.



Get Your Money's Worth

This model was designed to offer biometrics solution economically, efficiency you and performance without putting a hole in your pocket.



Manage Data Easily

TCMS V3 is loaded with useful features complete with various reports for your business. Its data integration to 3rd party software is made available through the readily available SDK.

http://info.fingertec.com/ta500-1



Quick Start Guide http://info.fingertec.com/ta500c-2



Installation Guide http://info.fingertec.com/ta500c-3



User Guide http://info.fingertec.com/ta500c-4



Video Guide http://info.fingertec.com/ta500c-5



Technical Tips http://info.fingertec.com/ta500c-6




TCMS V3 Software http://info.fingertec.com/tcmsv3



PackagingDimension (mm): 245 (L) x 90 (W) x 225 (H)
Weight: 1kg



for illustration only



	SPECIFICATIONS
MODEL	TA500
SURFACE FINISHING	Acrylonitrile butadiene styrene (ABS) & polycarbonate (PC)
TYPE OF SCANNER	Non coated optical scanner
MICROPROCESSOR	360 MHz
MEMORY	128 MB flash memory & 16 MB SDRAM
ALGORITHM	BioBridge VX10.0
DIMENSION (L X W X H), mm	184 x 38 x 134
STORAGE	
Fingerprint templates	2000
• Cards	Made to order
• Transactions	80000
ENROLLMENT & VERIFICATION	-
• Methods	Fingerprint (1:1, 1:N) & password (Optional RFID card)
Recommended fingerprint per user ID	2
Fingerprint placement	Any angle
Verification time (sec)	<1
• FAR (%)	< 0.0001
• FRR (%)	<1
CARD TECHNOLOGY	
• RFID: 64-bit, 125kHz	Made to order
• MIFARE: MFIS50/S70, 13.56MHz	Made to order
COMMUNICATIONS	
• Method	TCP/IP, USB disk
OPERATING ENVIRONMENT	
• Temperature (°C)	0 ~ 45
• Humidity (%)	20 ~ 80
Power input	DC12V1.5A
TIME ATTENDANCE	
• Siren	Yes
• Work codes	Yes
MULTIMEDIA	
• Voice	Yes
• Display	2.8" 3k color TFT screen
Short messaging	Yes
Internal backup battery	Yes (2-hours working, 4-hours standby)
VOICE / DISPLAY LANGUAGE (TERMINAL)	English (Standard), Arabic, Indonesian, Vietnamese, Spanish, Portuguese (Portugal), Russion, Thai, Turkish, French, Persian. Other languages are available upon request.
SOFTWARE LANGUAGE	Arabic, Bulgarian, Chinese (Simplified), Chinese (Traditional), English, German, Hindi, Indonesian, Kurdish, Malay, Portuguese, Russian, Spanish, Thai, Vietnamese

NOTE: Specifications are subject to change. Check http://product.fingertec.com for latest product information.





