




MUS / MUS-F series



2/2 WAY N.C. PISTON TYPE SOLENOID VALVE

2-WAY normally closed solenoid valve.
Available fluid: Water, air, steam, light oil & heavy oil.



Specification

- MUS/MUS-F series is multiplex-drive, piston guide, connected normal close.
- Acceptable for customization Viton (130°C), Silicone (130°C) and EPDM (130°C) for seal plug.
- Flange: JIS 10K (Option: ANSI 150LB or PN-16)
- AC voltage tolerance: $\pm 10\%$
DC voltage tolerance: $\pm 1\%$

Material

Model	MUS	MUS-F
Parts name		
Body	Cast bronze	Cast Iron (FC-20)
Coil	Special copper wire (H class)	
Tube	Stainless steel	
Spring	Stainless steel	
Core	Stainless steel	
Plug	PTFE+15%GF	PTFE (Teflon)
Piston	Brass	
Piston plug	PTFE (Teflon)	

Caution

- Min pressure to open 0.05 MPa (over 1 1/4" is 0.1 MPa)
- Before pipelining, the pipe line must be very clean without any contaminants or impurity.
- To extend the lifetime, Y-line filter should be installed in the front end of solenoid valve.
- It should be installed horizontally; vertical installation is not advisable.

Order example

MUS - 35 F - □ - □ - AC110 - G

MODEL: MUS
PORT SIZE: 35 (1 1/4")
COIL: F (Flange)
FLUID: AC (Light oil)
PORT THREAD: G (G thread)

Blank: Standard coil
D: Waterproof DIN (under 130°C) (*1)
T: Steam
LO: Light oil (*2)
HO: Heavy oil (*3)
W: Water, air

Blank: Rc thread
G: G thread
NPT: NPT thread (Only for standard type)

VOLTAGE: AC220V(50/60)Hz, AC110V(50/60)Hz, DC24V

*1. Please order according to the specification sheet.
*2. Note, if diesel fuel or gasoline.
*3. Please indicate the kind.

Not for fluid of

- Liquid when heat, solid when cool.
- Corrosive fluid.
- Viscosity over 20 cst.
- Temperature over 185°C.

Model	DIN	Port size	CV	Orifice (mm)	Fluid temp. °C	Operating pressuer range (MPa)				Dimensions (mm)			Weight (kg)
						Steam	Water, air	Heavy oil	Light oil	L	H	D	
MUS-15		Rc1/2"	4.0	17	-5~+185	0.05~1	—	0.05~1	0.05~1	82	125	58	1.60
MUS-20		Rc3/4"	6.0	17	-5~+185	0.05~1	—	0.05~1	0.05~1	82	125	58	1.67
MUS-25		Rc1"	12.0	22	-5~+185	0.05~1	—	0.05~1	0.05~1	91	133	58	2.02
MUS-35		Rc1 1/4"	18.0	30	-5~+185	0.1~1	—	0.1~1	0.1~1	111	141	58	3.08
MUS-40		Rc1 1/2"	22.0	30	-5~+185	0.1~1	—	0.1~1	0.1~1	111	144	58	3.10
MUS-50		Rc2"	48.0	50	-5~+185	0.1~1	—	0.1~1	0.1~1	163	175	58	6.82
MUS-35F	•	1 1/4"	22	35	-5~+185	0.1~1	0.1~1	—	0.1~1	200	189	48	10.7
MUS-40F	•	1 1/2"	30	40	-5~+185	0.1~1	0.1~1	—	0.1~1	200	189	48	11.9
MUS-50F	•	2"	40	50	-5~+185	0.1~1	0.1~1	—	0.1~1	210	202	48	13.2
MUS-65F	•	2 1/2"	68	65	-5~+185	0.1~1	0.1~1	—	0.1~1	240	209	48	19.2
MUS-80F	•	3"	100	80	-5~+185	0.1~1	0.1~1	—	0.1~1	300	228	48	27.0
MUS-100F	•	4"	175	100	-5~+185	0.1~1	0.1~1	—	0.1~1	340	244	48	38.7

* The pressure ratings indicated above are based on AC110V/220V. The maximum pressure may vary in case on DC/AC24V.