


GPWT

Male Y



MODEL[ØD-T] Tube(Metric)-Thread(R)

MODEL	ØD	R	ØP	A	B	C	Ød	J	F	H	X	Y	Orifice (Ømm)	W.G(g)	Qty/Inbox
GPWT 04M5	4	M5	9	4	37.4	14.5	3.2	9.3	13.2	9	8.6	10.8	2	8.9	50
GPWT 04M6	4	M6	9	5	38.4	14.5	3.2	9.3	13.2	9	8.6	10.8	2.1	9.4	50
GPWT 0401	4	R1/8	9	8	40.6	14.5	3.2	9.3	13.2	10	8.6	10.8	2.1	11.6	50
GPWT 0402	4	R1/4	9	11	43.6	14.5	3.2	9.3	13.2	14	8.6	10.8	2.1	20.5	50
GPWT 0403	4	R3/8	9	12	44.6	14.5	3.2	9.3	13.2	17	8.6	10.8	2.1	28.8	50
GPWT 06M5	6	M5	11.2	4	40.5	15.5	3.2	11.4	14.1	11	11	13	2	12.9	50
GPWT 06M6	6	M6	11.2	5	41.5	15.5	3.2	11.4	14.1	11	11	13	3	13.3	50
GPWT 0601	6	R1/8	11.2	8	43.7	15.5	3.2	11.4	14.1	11	11	13	3.6	15.2	50
GPWT 0602	6	R1/4	11.2	11	46.7	15.5	3.2	11.4	14.1	14	11	13	3.6	23.1	50
GPWT 0603	6	R3/8	11.2	12	47.7	15.5	3.2	11.4	14.1	17	11	13	3.6	35.2	25
GPWT 0604	6	R1/2	11.3	15	51.7	15.5	3.2	11.4	14.1	21	11	13	3.6	52.6	25
GPWT 0801	8	R1/8	13.6	8	52.6	17.8	3.2	14.2	18.6	13	13	15	5.4	23.3	50
GPWT 0802	8	R1/4	13.6	11	55.1	17.8	3.2	14.2	18.6	14	13	15	5.4	27.9	50
GPWT 0803	8	R3/8	13.6	12	56.1	17.8	3.2	14.2	18.6	17	13	15	5.4	36.2	25
GPWT 0804	8	R1/2	13.6	15	60.1	17.8	3.2	14.2	18.6	21	13	15	5.4	57.2	25
GPWT 1001	10	R1/8	16.3	8	53	19.4	4.2	17	18	17	16	18.5	6	30.6	25
GPWT 1002	10	R1/4	16.3	11	56	19.4	4.2	17	18	17	16	18.5	6.4	35.2	25
GPWT 1003	10	R3/8	16.3	12	58	19.4	4.2	17	18	17	16	18.5	6.4	40.8	25
GPWT 1004	10	R1/2	16.3	15	61	19.4	4.2	17	18	21	16	18.5	6.4	59.8	25
GPWT 1201	12	R1/8	19.7	8	62.9	22.4	4.2	20	23.9	19	19.5	22.5	6	49.0	25
GPWT 1202	12	R1/4	19.7	11	65.9	22.4	4.2	20	23.9	19	19.5	22.5	7.3	53.7	20
GPWT 1203	12	R3/8	19.7	12	67.9	22.4	4.2	20	23.9	19	19.5	22.5	7.3	59.5	20
GPWT 1204	12	R1/2	19.7	15	70.9	22.4	4.2	20	23.9	21	19.5	22.5	7.3	74.9	20

*Rotating body construction after a proper installation.