



SAFETY DATA SHEET	Page :1
	Revised edition no : 02
P-713 HD 30 MOTOR OIL	Effective Date: 19.6.2020

1 Identification of the Product and the company

Chemical Name : HD 30 MOTOR OIL
Type of product chemical family : Motor Oil
Producer : TLC-KOYA CHEMICALS MANUFACTURING SDN BHD
No.22 & 23, Jalan Maju 1,
Cemerlang Industrial Estate,
81800 Ulu Tiram, Johor, Malaysia.
Tel: 607-8675798 Fax: 607-8675799
Website: www.koyachemicals.com Email:admin@koyachemicals.com
Emergency phone nr : See producer

2 Hazards Identification

Classification of the mixture: Not Classified

GHS label element
Signal Word : No signal word
Hazard Statement: No known significant effects or critical hazards.

Precautionary statements :
Prevention Not applicable
Response Not applicable
Storage Store in well-ventilated place
Disposal Dispose of contents and container in accordance with all local, regional, national and international regulations

3 Composition / Information on Ingredients

Mineral Oil (C15 ~ C50) : Mixture
93% ~ 99%

Ashless anti wear lubricant oil additives : Blend
1% ~ 7%

4 First Aid Measures

Inhalation : Using proper respiratory protection, immediately remove the affected victim from exposure.
Administer artificial respiration if breathing is stopped. Keep at rest.
Call for prompt medical attention.

Skin Contact : Flush with large amounts of water and use soap if available.
Remove grossly contaminated clothing including shoes and launder before reuse.

Eye Contact : Immediately flush eyes with large amounts of water for at least 15 minutes.
Get prompt medical attention.

Ingestion : If swallowed, DO NOT induces vomiting. Keep at rest. Get prompt medical attention.



SAFETY DATA SHEET	Page : 2
	Revised edition no : 02
P-713 HD 30 MOTOR OIL	Effective Date: 19.6.2020

5 Fire Fighting Measures

- Fire Fighting Procedures : Use water spray cool fire exposed surfaces and to protect personnel. Shut off "fuel" to fire.
Use dry chemical powder, foam, carbon dioxide (CO₂) or water fog to extinguish fire.
- Special Fire Precautions : Respiratory and eye protection required for fire fighting personnel.
See also Section 4 "FIRST AID MEASURES" as well as Section 10 "STABILITY AND REACTIVITY".
- Hazardous Combustion Products : Fumes, smoke, carbon dioxide (CO₂), carbon monoxide (CO), oxides of phosphorus (Toxic), oxides of sulfur (Toxic).

6 Accidental Release Measures

- Land Spill : Contain spilled liquid with sand or earth.
Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent. If liquid is too viscous for pumping, scrape up with shovels or pails and place in suitable containers for recycle or disposal.
Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
See Section 4 "FIRST AID MEASURES" as well as Section 10 "STABILITY AND REACTIVITY".
- Water Spill : Warn other shipping. Notify port or relevant authority and keep public away.
Shut off source if possible to do so without hazard. Confine if possible.
Remove from surface by skimming or with suitable absorbents. If swallowed by local authorities and environment agencies sinking and or suitable dispersants may be used in non-confined waters.
Consult an expert on disposal of any recovered material and ensure conformity to local disposal regulations.
See also Section 4 "FIRST AID MEASURES" as well as Section 10 "STABILITY AND REACTIVITY".

7 Handling And Storage

- Electrostatic Accumulation Hazard : No, but use proper grounding procedure.
- Loading / Unloading Temperature : 30°C ~ 60°C recommended range
- Transportation Temperature : 30°C ~ 60°C recommended range
- Usual Shipping Container : Tank cars, tank trucks, drum, pails, carboys.
- Transport / Storage Pressure : Atmospheric
- Storage Temperature : 45°C maximum
- Materials and Coatings Suitable : Mild steel, stainless steel
- Materials and Coatings unsuitable : Natural rubber, butyl rubber, PVC

Compatibility with plastic materials can vary, we therefore recommend the compatibility is tested prior to use.

- Handling / Storage, General Notes : Keep container closed. Handle containers with care, Open slowly in order to control possible pressure release. Store in a cool, well ventilated place away from incompatible materials.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



SAFETY DATA SHEET	Page : 3
	Revised edition no : 02
P-713 HD 30 MOTOR OIL	Effective Date: 19.6.2020

Extreme caution must be used in tank gauging or similar operations because overheating could cause lethal concentrations of hydrogen sulfide to accumulate in the head space of containers.

DO NOT handle, store or open near flame, sources of heat or sources of ignition. Protect material from direct sunlight.

This material is not a static accumulator but use proper bonding and or grounding procedures.

DO NOT pressurize, cut, heat or weld containers. Empty product containers may contain product residue. DO NOT reuse empty containers without commercial cleaning or reconditioning.

Additional Warnings : Product liberates very toxic gas when overheated. Keep at temperature below 60°C.
Container remains hazardous when empty. Continue to observe all precautions.

8 Exposure Controls and Personal Protections

Occupational Exposure Limits : This product contains mineral oil and heat sensitive material. Under certain conditions (open heating and or mechanical shear), the following component(s) with a recognized or recommended OEL value may be released.
- Hydrogen sulfide (Eight-hour time-weighted average, airborne concentration):
OSHA FEB 2007 SCHEDULE 1: 10 ppm, 14 mh/m³
- Mineral oil mist (Eight-hour time-weighted average, airborne concentration):
OSHA FEB 2007 SCHEDULE 1: 5 mg/m³, vapour excluded

Engineering Controls : The use local exhaust ventilation is recommended to control process emissions near the source.
Laboratory samples should be handled in a lab hood.
Provide mechanical ventilation of confined spaces.

Personal Protection General Advice : The use and choice of Personnel Protection equipment is related to the hazard of the product, the workplace and the way the product is handled.
In general, we recommend as a minimum safety precaution that safety glasses with side-shields and work-clothes that protecting arms, legs and body be used. In addition, any person visiting an area where this product is handled.

Personal Protection Special Advice : Based on and limited to TLC-KOYA CHEMICALS MFG SDN BHD experience of this product as such, the following special advice is believed to provide satisfactory protection for the industrial user or handler.

Respiratory Protection : Where concentrations in air may exceed the limits given in this section, it is recommended to use a half face filter mask to protect from over exposure by inhalation. Suitable filter material depends on the amount and type of chemicals being handled. In the workplace, but filter material of type "B-P" or similar may be considered for used.

Hand Protection : When handling this product, it is recommended to wear chemicals resistant gloves. The choice of suitable protective gloves depends on work conditions and what chemicals are handled. But we have positive experience with gloves made of PVC or Nitrile. Gloves should be replaced immediately if sign of degradation is observed.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



SAFETY DATA SHEET	Page : 4
	Revised edition no : 02
P-713 HD 30 MOTOR OIL	Effective Date: 19.6.2020

Eye Protection : When handling this product, it is recommended to wear splash resistant goggles.

Skin / Body Protection : When handling this product, it is recommended to wear a chemical resistant apron, jacket and rubber boots.

9 Physical and Chemical Properties

Specific Gravity : 0.855-0.865 @ 28.9°C
Appearance : Liquid
Colour : Pale Brown
Kinematic Viscosity : 125-170 mm²/s @ 40°C

10 Stability and Reactivity

Stability : Stable
Conditions to avoid instability : Avoid overheating
Contact with acids
Materials and conditions to avoid (Incompatibility : Strong oxidizing agents
Hazardous Polymerization? : No
Hazardous Decomposition Products : When heated above 60°C (140°F), Hydrogen Sulphide (H₂S)(Toxic) may be released.

11 Toxicological Information

Inhalation : Negligible hazard at ambient (10°C ~ 38°C) temperature.
WARNING. If overheating especially in the presence of water, hydrogen sulphide maybe released. This can cause respiratory collapse, coma and even death without necessarily any odour being sensed.
Avoid breathing vapour or mists.
Repeated and prolonged overexposure to oil mists may result in droplet deposition, oil granuloma formation, inflammation and increased of infection.

Skin Contact : Low order of toxicity.
Frequent prolonged contact may cause mild skin discomfort.

Eye Contact : Severely irritating. If not removed promptly, will injure eye tissue, which may result in permanent damage.

Ingestion : Minimal toxicity

12 Ecological Information

Ecotoxicity and Bioaccumulation : Expected to be harmful to aquatic organisms.
Long term adverse effects to aquatic organism are possible if continuous exposure is maintained.

Environmental Degradability : This Product is not expected to be "readily" biodegradable.
A component(s) of this product is expected to be "inherently" biodegradable to OECD guideline.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



SAFETY DATA SHEET	Page : 5
	Revised edition no : 02
P-713 HD 30 MOTOR OIL	Effective Date: 19.6.2020

Environmental Mobility : This is a preparation and environmental assessment based on component data and that of similar products.
A mineral oil component of this product floats and can migrate from water to land.

13 Disposal Information

- The following advice only applies to the product as supplied.
- Combination with other materials may well indicate another route of disposal. If in doubt, contact TLC-KOYA CHEMICALS MFG SDN BHD or local authorities.
- Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor.
- Care should in any case be taken to ensure compliance with national and local authorities.
- This product is NOT suitable for disposal by either landfill or via municipal sewers, drains, natural streams and rivers.
- This product will generate an ash if burned. It can be burned directly in appropriate equipment.

14 Transport Information

LAND : This product is not regulated for road and rail transport.
SEA - IMDG : This is not regulated for sea transport.
AIR (ICAO/IATA) : This product is not regulated for air transport.

15 Regulatory Information

Governing Directive : Occupational Safety and Health (Classification, packaging and Labelling of Hazardous Chemicals) Regulations 2007 Act 514
ACCESSIBILITY on this CSDS according to the above ACT on Regulation 10. (1)(a), must be available and easily accessible by any person who uses or handles this product.

Label name : Ashless Anti Wear Hydraulic Oil (Group 1)

Indication of Special Risks : R36/37/38 Irritating to eyes, respiratory system and skin.

Indication of safety Precautions : S2 Keep out of reach of children.
S9 Keep in a well ventilated place.
S14 Keep away from strong oxidizing agents - acids, alkaline
S16 Keep away sources of ignition - "No Smoking"
S 23 Do not breathe spray, vapour, fumes or gas
S43 In case of fire, use dry chemical powder, foam, carbon dioxide (CO²)
S56 Do not discharge into drains or the environmental, dispose of an authorized waste collection point

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



SAFETY DATA SHEET	Page : 6
	Revised edition no : 02
P-713 HD 30 MOTOR OIL	Effective Date: 19.6.2020

16 Other information

Further information : None
Print date : 19.6.2020

N/A - Not Applicable N/D - Not Determined

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from data or test results obtained by us, are based on the current state of our knowledge at the time such recommendations are made. When additional information is obtained, these recommendations may be updated. They may also be influenced by circumstances outside our control. Notwithstanding such recommendations, the user is responsible to determine that the product as supplied by us, is suitable for the process or purpose he intends to use it. The user of the product is solely for compliance with all laws and regulation applying to the use of the product. Since we cannot control the application, use or processing of the products, we do not accept responsibility therefore. The user shall ensure that the intended use of the products will not infringe in any party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com