

## **Description:**

Premium, high quality TCW III 2 cycle Engine Oil (2T) specially designed for use in outboard motors, chainsaws, garden equipment and all others 2 stroke motor.

It is formulated with high grade synthetic base oils and detergent inhibitor additive package to minimize spark fouling, pre-ignition, ring sticking carbon build up on pistons and get your engine running smoothly.

## **Specification**

			Method
<u>Test</u>	<u>Unit</u>	<u>Result</u>	<u>ASTM</u>
Appearance	-	Red	VISUAL
Colour	-	3	1500
Specific Gravity 28.9 DEG	KG/L	0.85-0.855	D-4052
Kinematic Viscosity @ 40 DEG c	CST	80-1000mm2/s	-

## **Benefits**

- \* With stand higher load and temperature
- \* Cleaner combustion
- \* Low smoke decrease air pollution
- \* Good detergency and lubricity to avoid ring sticking and piston seizure

# Storage

Keep container sealed when not in use Keep away from direct sunlight.

## **Packing**

0.5 Ltr, 1 Ltr, 4 Ltr, 18 Ltr

## <u>Note</u>

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.