

PRODUCT SPECIFICATION Page :1 P-626 GALVANIZED Revised edition no : 01 PROTECTIVE COATING Effective Date: 14-7-2014

Description:

P-626 Galvanized Protective Coating is a compound designed to provide a protective coating anti white rust on the galvanized products. It is blind by wax and mineral oil & solvent, the tinned wax film imparts lubricity resulting in compact wire bundles and aids in subsequent forming operations.

Recommed Use

P-626 recommend use on galvanized wire, tinned, cadmium and alloy coated wires. The solvent based liquid excellent stability.

The evaporate of the liquid and dry before the wire goes on the take-up block. A bath temperature of 50% of above gives the best results.

Physical Properties

Appearance : Clear liquid
Colour : Brown
Specific gravity : 0.90
Stability : 2 years
PH : 5 +/- 0.5

Odour : Hydrocarbon odour

Analysis

100% active organic liquid - No water added

Safety precaution

Avoid inhaling and keep away from eyes. If contact with eyes flush with plenty of water and obtain medical advice.

Avoid prolonged and repeated skin contact.

Keep out of reach of children.

Storage

Stored in cool place, avoid direct ultra sunlight.

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com