

Page :1

Revised edition no: 04

P-615 45B MP SOLVENT

Effective Date: 8.5.2024

Identification of the Product and the company

Chemical Name : Lacquer Thinner

Type of product chemical family : N/A

Producer : TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia. Tel: 607-8675798 Fax: 607-8675799

Emergency phone nr : See producer UN NUMBER : UN 1263 / IMO 3

2 Hazard Identification







SIGNAL WORD: WARNING / AMARAN

Flammable liquids

Skin irritation

Category 2

Eye irritation

Category 2

Reproductive toxicity

Specific Target organ Toxicity - single exposure Narcotic effects

Specific Target organ Toxicity - repeated esposure

Category 2

Category 3

Category 2

Category 3

Category 2

Category 2

HAZARD STATEMENT / PENYATAAN HAZARD

H226 Flammable liquid and vapour

Cecair dan wap mudah bakar

H315 Causes skin irritation

H319

Menyebabkan kerengsaan kulit Causes serious eye irritation

Menyebabkan kerengsaan mata yang serius

H336 May cause drowsiness and dizziness (narcotic effects)

Boleh menyebabkan rasa mengantuk dan pening (kesan narkotik)

H361 Suspected of damaging fertility or the unborn child.

Disyaki merosakkan kesuburan atau anak yang belum lahir.

H373 May cause damage to organs through prolonged or repeated exposure.

Boleh menyebabkan kerosakan kepada organ melalui pendedahan berpanjangan atau berulang.

PRECAUTIONARY STATEMENT PREVENTION

P201 Obtain special instructions before use.

Dapatkan arahan khas sebelum digunakan.

P202 Do not handle until all safety precautions have been read and understood.

Jangan mengendalikan sehingga semua langkah keselamatan telah dibaca dan difahami.

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking.

Jauhkan daripada haba/percikan api,nyalaan terbuka,permukaan panas-dilarang merokok.

P233 Keep container tightly closed.

Simpan berkas yang tertutup

P240 Ground/bond container and receiving equipment.

Ikat berkas dan peralatan yang diterima.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

Menggunakan elektrikkalis letupan/pengalih udara/peralatan pencahayaan.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

ebaita www.koyachemicals.com EMAIL: admin@koyachemicals.com



P261

SAFETY DATA SHEET Page :2 Revised edition no : 04 P-615 45B MP SOLVENT Effective Date: 8.5.2024

P242 Use only non-sparking tools.

Hanya menggunakan peralatan yang bukan percikan.

P243 Take precautionary measures against static discharge.

Sila ambil langkah-langkah keselamatan terhadap pelepasan statik.

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

Jangan menghirup debu / asap / gas / kabus / wap / semburan.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Elakkan menyedut habuk/asap/gas/kabus/wap/semburan.

P264 Wash thoroughly after handling.

Basuh tangan bersih-bersih selepas mengendalikan bahan.

P271 Use only outdoors or in a wellventilated area.

Digunakan hanya di luar rumah atau di kawasan yang menpunyai pengudaran.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Memakai peralatan perlindungan seperti sarung tangan/pakaian pelindung/mata dan pelindung muka.

P281 Use personal protective equipment as required.

Gunakan peralatan pelindung diri seperti yang diperlukan.

PRECAUTIONARY STATEMENT RESPONSE

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

Hubungi PUSAT RACUN atau doktor / pakar perubatan jika anda rasa tidak sihat.

P321 Specific treatment reference to supplemental first aid instruction.

Rujukan rawatan khusus untuk tambahan arahan pertolongan cemas.

P314 Get medical advice / attention if you feel unwell.

Dapatkan nasihat perubatan / perhatian jika anda merasa tidak sihat.

P362 Take off contaminated clothing and wash before reuse.

Tanggalkan pakaian yang tercemar dan basuh sebelum digunakan semula.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

JIKA KULIT: Basuh dengan sabun dan air.

P303 + P361 + P353 IF ON SKIN (or hair):Remove/take off immediately all contaminated clothing. Rinse skin with

water/shower.

JIKA TERKENA KULIT (atau rambut): Buang / mengambil dengan segera semua pakaian

yang tercemar. Bilas kulit dengan air / mandi.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

JIKA TERSEDUT: Pindahkan mangsa ke udara bersih dan biarkan berehat dalam kedudukan

yang selesa untuk bernafas.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

JIKA DALAM MATA: Bilas dengan berhati-hati dengan air selama beberapa minit. Keluarkan kanta

lekap, jika ada dan mudah dilakukan. Teruskan mencuci.

P308 + P313 IF exposed or concerned : Get medical advice / attention.

JIKA terdedah atau bimbang: Dapatkan nasihat / perhatian perubatan.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

Jika berlaku kerengsaan kulit: Dapatkan nasihat / rawatan perubatan.

P337 + P313 If eye irritation persists: Get medical advice / attention.

Jika kerengsaan mata berterusan: Dapatkan nasihat / perhatian perubatan.

In case of fire: Use Foam and dry chemical powder, carbon dioxide extinguisher for extinction.

Jika berlaku kebakaran: Gunakan busa dan serbuk kimia kering, karbon dioksida untuk

pemadam kepupusan.

PRECAUTIONARY STATEMENT STORAGE

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Simpan di tempat yang mempunyai pengudaraan yang baik. Simpan bekas dengan ketat ditutup.

P403 + P235 Store in a well-ventilated place. Keep cool.

Simpan di tempat yang mempunyai pengudaraan yang baik. Tetap tenang.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

P370 + P378



Page:3

Revised edition no: 04

P-615 45B MP SOLVENT

Effective Date: 8.5.2024

P405 Store locked up

Simpan dalam keadaan berkunci

PRECAUTIONARY STATEMENT DISPOSAL

P501

Dispose of contents/container in accordance with local/regional/national/international regulation Menguruskan bahan / bekal menurut tempatan / kawasan / negara / antarabangsa peraturan

Composition / Information on Ingredients

Hazardous ingredients : Methylbenzene >60%

> Propan-2-ol 10 to <30% Butan-2-one 5 to <10% 4-Methylpentan-2-one 5 to <10% 2-Butoxyethanol 3 to <5%

First Aid Measures

Eye Contact : Flush with cool running water, lifting the upper and lower eyelids occasionally

until discomfort is relieved.

Skin Contact : Not expected to present a significant skin hazard under anticipated condition

of normal use.

: Not expected to present a significant ingestion hazard under anticipated Ingestion

conditions of normal use.

Inhalation : Treatment base on judgment of physician in response to reaction of

patient.

Fire-Fighting Measures

Flash Point (Tag Closed Tester) : Below 30°C

Extinguishing Media : Foam and dry chemical powder, carbon dioxide, sand or earth may be used

for small fire only.

Special Fire Fighting Produres

: Self-contained breathing apparatus are recommended for fire fighters. Unusual Fire and Explosion Hazards : None.

Accidental Release measures

Personal protection - Wear PVC-gloves and goggles to contain spillage.

Avoid repeated skin contact.

- Prevent the product contaminating soil and groundwater. Prevent the **Environment precautions**

product enetring sewers and waterways.

Cfr.Section 12.

- Large spillages : contain and pump into containers Cleaning / recovery

> - Small spillages : absorb on sand, earth...and collect into containers for disposal. Disposal should always comply with local, national or EEC

regulations. Cfr.Section 13.

Handling and Storage

Handling : Good industrial and personal hygiene practice should be followed. No eating

and drinking in the workplace. Ensure adequate ventilation.

Storage : Storage temperature : between +5 and +40°C.

Protect from frost and direct sunlight.

Drums and bottles: material is plastic or steel.

Bulk tanks: stainless steel, plastic coated materials... Clean bulk tanks

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



Page:4

Revised edition no: 04

P-615 45B MP SOLVENT

Effective Date: 8.5.2024

periodically to prevent accumulation of bacteria.

Specific use : Use the best available methods of handling our Products whereby the

employees enjoy maximum safety and whereby the environment is

minimally affected.

Exposure controls / personal protection

Exposure limit values : No danger in normal ambient conditions.

There are no specific limiting values for professional exposure.

There are no biological limiting values.

User should determine the conditions for safe use of the product. Cfr.

Section 7 "Handling and Storage".

Exposure controls:

: Respiratory protection : not applicable - Occupational exposure controls

> Hand protection: waterproof PVC-gloves (CE) Eye protection: goggles or safety glasses (CE)

Skin protection: N/A

Avoid repeated skin contact.

- Environmental exposure controls : The product must not be discharge directly into drains or waterways without

treatment.

Physical and chemical properties

Boiling Point (°C) : Below 30°C

Vapor Pressure (mm Hg) : N/A Vapor Density (Air=1) : >1

Cu corrosion : No Decoloration

Appearance : Clear liquid and chemical odor

Solubility in water : immiscible with and lighter than water.

Specific Gravity (H₂O=1) : 0.84 Percent Volatile by weight : 100 Evaporation Rate (Water=1) : 100

10 Stabiity and reactivity

Conditions to avoid : Stable under the recommended storage conditions. Cfr. Section 7 "Storage".

Bacterial degradation can occur if the Product is stored for an unuasually

long period or is stored under unsuitable conditions.

Keep away from spark, do not empty into drain. Incompatibility (materials to avoid) : None known

Hazardous Polymerization : Nil : N/D Materials to avoid Hazardous decomposition products : N/D

11 Toxicological information

On product : Low toxicity is indicated by available data.

Under normal industrial conditions, there is no indication that the Product

can be considered as a health risk.

Skin contact should be avoided to prevent possible long-term or short-term

sensitation.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799



Page :5

Revised edition no: 04

P-615 45B MP SOLVENT

Effective Date: 8.5.2024

12 Ecological information

Ecotoxicity : The Product is soluble with water to certain extent and as such could cover

considerable distances if spilled into waterways. Even a small spillage will whiten the appearance of water. Water for sewage treatment, that has been contaminated.

With small quantities of the Product, will not affect the biomass. High

concentrations may be harmful to fish and micro organisms.

Mobility : Not established.

Persistence and degradability : There is only a slow environmental degradation of the Product.

Bioaccumulative potential : There is seemingly no tendency for bioaccumulation.

Other adverse effects : Unknown

13 Disposal Considerations

- The following advice only applies to the product as supplied

- Combination with other materials may well indicate another route of disposal. If in doubt, contact local TLC-KOYA CHEMICALS MANUFACTURING SDN BHD or local authorities.
- Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor.
- Care should in any case be taken to ensure compliance with national and local regulations.
- This product is not suitable for disposal by either landfill or via municipal sewers, drains, and natural streams, rivers or seas, they will effect the relationaship between livings things, plants and their environment.

14 Transport information

IMO PROPER SHIPPING NAME : NORMAL THINNER

IMO U.N. CLASS : 3

IMO U.N. NUMBER : UN 1263

IMO LABEL : Flammable Liquid



15 Regulatory Information

Classification and labeling : Classification /symbol - not regulated

Governing directive : Occupational Safety and Health (Classification, Packaging and Labeling of

Hazardous Chemicals) Regulations 1997

Safety advice : (May contain information in excess of requirements under applicable laws.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a wellventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P314 Get medical advice / attention if you feel unwell.

P321 Specific treatment reference to supplemental first aid instruction.

P362 Take off contaminated clothing and wash before reuse.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799



Page: 6

Revised edition no: 04

P-615 45B MP SOLVENT

Effective Date: 8.5.2024

P303 + P361 + P353 IF ON SKIN (or hair):Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned : Get medical advice / attention.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice / attention.

P370 + P378 In case of fire: Use Foam and dry chemical powder, carbon dioxide extinguisher for extinction.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up

P501 Dispose of contents/container in accordance with local/regional/national/

international regulation.

16 Other information

Further information : None
Print date : 8.5.2024

N/A - Not Applicable N/D - Not Determined

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from data or test results obtained by us, are based on the current state of our knowledge at the time such recommendations are made. When additional information is obtained, these recommendations may be updated. They may also be influenced by circumstances outside our control. Notwithstanding such recommendations, the user is responsible to determine that the product as supplied by us, is suitable for the process or purpose he intends to use it. The user of the product is solely for compliance with all laws and regulation applying to the use of the product. Since we cannot control the application, use or processing of the products, we do not accept responsibility therefore. The user shall ensure that the intended use of the products will not infringe in any party's intellectual property rights.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com