



# SAFETY DATA SHEET

Page :1

Revised edition no : 03

## P-613 CUTTING OIL

Effective Date: 10.4.2021

### 1 Identification of the Product and the company

Chemical Name : Cutting Oil  
Type of product chemical family : N/A  
Use : honing  
Producer : TLC-KOYA CHEMICALS MANUFACTURING SDN BHD  
No.22 & 23, Jalan Maju 1,  
Cemerlang Industrial Estate,  
81800 Ulu Tiram, Johor, Malaysia.  
Tel: 607-8675798 Fax: 607-8675799  
Website: www.koyachemicals.com Email: admin@koyachemicals.com

Emergency phone nr : See producer

### 2 Hazard Identification

Pictogram :  
SIGNAL WORD: WARNING



Specific target organ toxicity-single exposure  
Hazardous to the aquatic environment-chronic hazard

Category 3  
Category 2

#### HAZARD STATEMENT

H336: May cause drowsiness and dizziness (narcotic effects)

H411: Toxic to aquatic life with long lasting effects

#### PRECAUTIONARY STATEMENT

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312 Call a POISON CENTER or doctor / physician if you feel unwell.  
P391 Collect spillage  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up  
P501 Dispose of contents/container in accordance with local/regional/national/international regulation

### 3 Composition / Information on Ingredients

Hazardous ingredients : Base Oil 85%  
Additive 15%

Active Ingredients : 100%

#### TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



# SAFETY DATA SHEET

Page :2

Revised edition no : 03

## P-613 CUTTING OIL

Effective Date: 10.4.2021

### 4 First Aid Measures

- Inhalation : Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.
- Skin Contact : Flush with large amounts of water and use soap if available. Remove grossly contaminated clothing including shoes and launder before reuse.
- Eye Contact : Immediately flush eyes with large amounts of water at least 15 minutes. Get prompt medical attention.
- Ingestion : If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

### 5 Fire-Fighting Measures

- Fire Fighting Procedures - Use water spray cool fire exposed surfaces and to protect personnel. Shut off "fuel" to fire. Use dry chemical powder, foam, carbon dioxide (CO<sub>2</sub>) or water fog to extinguish fire.
- Special Fire Precautions - Respiratory and eye protection required for fire fighting personnel. See also Section 4 "FIRST AID MEASURES" as well as Section 10 "STABILITY AND REACTIVITY".
- Hazardous Combustion Products - Fumes, smoke, carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of phosphorus (Toxic), oxides of sulfur (Toxic).

### 6 Accidental Release measures

- LAND SPILL - Contain spilled liquid with sand or earth.  
- Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent. If liquid is too viscous for pumping, scrape up with shovels or pails and place in suitable containers for recycle or disposal.  
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.  
- See Section 4 "FIRST AID MEASURES" as well as Section 10 "STABILITY AND REACTIVITY".
- WATER SPILL - Warn other shipping. Notify port or relevant authority and keep public away. Shut off source if possible to do so without hazard. Confine if possible.  
- Remove from surface by skimming or with suitable absorbents. If swallowed by local authorities and environment agencies sinking and or suitable dispersants may be used in non-confined waters.  
- Consult an expert on disposal of any recovered material and ensure conformity to local disposal regulations.  
- See Section 4 "FIRST AID MEASURES" as well as Section 10 "STABILITY AND REACTIVITY".

#### TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



# SAFETY DATA SHEET

Page :3

Revised edition no : 03

## P-613 CUTTING OIL

Effective Date: 10.4.2021

### 7 Handling and Storage

7.1 ELECTROSTATIC ACCUMULATION HAZARD? No, but use proper grounding procedure  
LOADING/ UNLOADING TEMPERATURE: 30°C ~ 60°C recommended range  
TRANSPORTATION TEMPERATURE: 30°C ~ 60°C recommended range  
USUAL SHIPPING CONTAINER: Tank cars, tank trucks, drums, pails, carboys  
TRANSPORT / STORAGE PRESSURE: Atmospheric

7.2 STORAGE TEMPERATURE: 45°C maximum  
MATERIALS AND COATING SUITABLE: Mild steel, stainless steel  
MATERIALS AND COATINGS UNSUITABLE: Natural rubber, butyl rubber, PVC  
Compatibility with plastic materials can vary, we therefore recommend the compatibility is tested prior to use.

#### 7.3 HANDLING / STORAGE, GENERAL NOTES:

- Keep container closed. Handle containers with care, open slowly in order to control possible pressure release. Store in a cool, well ventilated place away from incompatible materials.
- Extreme caution must be used in tank gauging or similar operations because overheating could cause lethal concentrations of hydrogen sulfide to accumulate in the head space of containers.
- DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight.
- This material is not a static accumulator but use proper bonding and or grounding procedures.
- DO NOT pressurize, cut, heat or weld containers. Empty product containers may contain product residue. DO NOT reuse empty containers without commercial cleaning or reconditioning.

#### 7.4 ADDITIONAL WARNINGS:

- Product liberates very toxic gas when overheated. Keep at temperature below 60°C.
- Container remains hazardous when empty. Continue to observe all precautions.

### 8 Exposure controls / personal protection

#### 8.1 OCCUPATIONAL EXPOSURE LIMITS:

This product contains mineral oil and heat sensitive material. Under certain conditions (open heating and or mechanical shear), the following component(s) with a recognized or recommended OEL value may be released.

- Hydrogen sulfide (Eight hour time-weighted average, airborne concentration):  
OSHA FEB 2007 SCHEDULE 1:10 ppm, 14 mg/m<sup>3</sup>
- Mineral oil mist (Eight hour time-weighted average, airborne concentration):  
OSHA FEB 2007 SCHEDULE 1:5 MG/M<sup>3</sup>, vapour excluded

#### 8.2 ENGINEERING CONTROLS:

- The use of local exhaust ventilation is recommended to control process emissions near the source.
- Laboratory samples should be handled in a lab hood.
- Provide mechanical ventilation of confined spaces.

#### 8.3 PERSONAL PROTECTION GENERAL ADVICE:

- The use and choice of Personnel Protection equipment is related to the hazard of the product, the workplace and the way the product is handled. In general, we recommend as a minimum safety precaution that safety glasses with side-shields and work-clothes that protecting arms, legs and body be used. In addition, any person visiting an area where this product is handled. In addition, any person visiting an area where this product is handled or processed should at least wear safety glasses with side-shield.

#### TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



# SAFETY DATA SHEET

Page :4

Revised edition no : 03

## P-613 CUTTING OIL

Effective Date: 10.4.2021

### 8.4 PERSONAL PROTECTION SPECIAL ADVICE:

Based on and limited to TLC-KOYA CHEMICALS MFG SDN BHD experience of this product as such, the following special advice is believed to provide satisfactory for the industrial user or handler.

### 8.5 RESPIRATORY PROTECTION

Where concentrations in air may exceed the limits given in this section, it is recommended to use a half face filter mask to protect from over exposure by inhalation. Suitable filter material depends on the amount and type of chemicals being handled. In the workplace, but filter material of type "B-P" or similar may be considered for used.

### 8.6 HAND PROTECTION

When handling this product, it is recommended to wear chemicals resistant gloves. The choice of suitable protective gloves depends on work conditions and what chemicals are handled, but we have positive experience with gloves made of PVC or Nitrile. Gloves should be replaces immediately if sign of degradation is observed.

### 8.7 EYE PROTECTION

When handling this product, it is recommended to wear splash resistant goggles.

### 8.8 SKIN / BODY PROTECTION

When handling this product, it is recommended to wear a chemical resistant apron, jacket and rubber boots.

## 9 Physical and chemical properties

Appearance	:liquid
Colour	:brown
Specific gravity	:0.85-0.87 @ 28.9°C
pH value	:8.0-10.0 @ 24.0-26.5°C
Viscosity	:58-90mm <sup>2</sup> /s @30°C

## 10 Stabiity and reactivity

STABILITY	: STABLE
CONDITIONS TO AVOID INSTABILITY	: Avoid overheating and contact with acids
MATERIALS AND CONDITIONS TO AVOID (INCOMPATIBILITY)	: Strong oxidizing agents
HAZARDOUS POLYMERIZATION	: No
HAZARDOUS DECOMPOSITION PRODUCTS	: When heated above 60°C (140°F), Hydrogen Sulfide (H <sub>2</sub> S) (Toxic) may be released.

## 11 Toxicological information

INHALATION	- Negligible hazard at ambient (10°C ~ 38°C) Temperature - WARNING. If overheating especialy in the presence of water, hydrogen sulphide maybe released. This can cause respiratory collapse, coma and even death without necessarily any odour being sensed. - Avoid breathing vapour or mists. - Repeated and prolonged overexposure to oil mists may result in droplet deposition, oil granuloma formation, inflammation and increased of infection.
------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



# SAFETY DATA SHEET

Page :5

Revised edition no : 03

## P-613 CUTTING OIL

Effective Date: 10.4.2021

SKIN CONTACT	- Low order of toxicity - Frequent prolonged contact may cause mild skin discomfort.
EYE CONTACT	- Severely irritating. If not removed promptly, will injure eye tissue, which may result in permanent damage.
INGESTION	- Minimal toxicity

### 12 Ecological information

#### ECOTOXICITY AND BIOACCUMULATION

- Expected to be harmful to aquatic organisms.
- Long term adverse effects to aquatic organism are possible if continuous exposure is maintained.

#### ENVIRONMENTAL DEGRADABILITY

- This product is not expected to be "readily" biodegradable.
- A component(s) of this product is expected to be "inherently" biodegradable according to OECD guideline.

#### ENVIRONMENTAL MOBILITY

- This is a preparation and environmental assessment based on component data and that of similar products.
- A mineral oil component of this product floats and can migrate from water to land.

### 13 Disposal Considerations

- The following advice only applies to the product as supplied
- Combination with other materials may well indicate another route of disposal. If in doubt, contact local TLC-KOYA CHEMICALS MANUFACTURING SDN BHD or local authorities.
- Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor.
- Care should in any case be taken to ensure compliance with national and local regulations.
- This product is not suitable for disposal by either landfill or via municipal sewers, drains, and natural streams, rivers or seas, they will effect the relationship between living things, plants and their environment.

### 14 Transport information

LAND	: This product is not regulated for road and rail transport.
SEA-IMDG	: This product is not regulated for sea transport.
AIR (ICAO/IATA)	: This product is not regulated for air transport.

### 15 Regulatory Information

Classification and labeling	: Classification /symbol - not regulated
Governing directive	: Occupational Safety and Health (Classification, Packaging and Labeling of Hazardous Chemicals) Regulations 1997
Safety advice	: (May contain information in excess of requirements under applicable laws. S23 Do not breathe gas/fumes/vapor/spray S24 Avoid contact with skin S33 Take precautionary measures against static discharges S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

#### TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



SAFETY DATA SHEET	Page : 6
	Revised edition no : 03
P-613 CUTTING OIL	Effective Date: 10.4.2021

16 Other information

Further information : None  
Print date : 10-4-2021

N/A - Not Applicable      N/D - Not Determined

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from data or test results obtained by us, are based on the current state of our knowledge at the time such recommendations are made. When additional information is obtained, these recommendations may be updated. They may also be influenced by circumstances outside our control. Notwithstanding such recommendations, the user is responsible to determine that the product as supplied by us, is suitable for the process or purpose he intends to use it. The user of the product is solely for compliance with all laws and regulation applying to the use of the product. Since we cannot control the application, use or processing of the products, we do not accept responsibility therefore. The user shall ensure that the intended use of the products will not infringe in any party's intellectual property rights.

**TLC-KOYA CHEMICALS MANUFACTURING SDN BHD**

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: [www.koyachemicals.com](http://www.koyachemicals.com) EMAIL: [admin@koyachemicals.com](mailto:admin@koyachemicals.com)