

SAFETY DATA SHEET

P-569

HEAVY DUTY FLOOR WAX STRIPPER

Page:1

Revised edition no: 03

Effective Date: 23.4.2023

1 Identification of the Product and the company

Chemical Name : Heavy Duty Floor Wax Stripper

Type of product chemical family : Alkaline Cleaner

Use : remove of old stubborn floor wax

Producer : TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia. Tel: 607-8675798 Fax: 607-8675799

Emergency phone no : See producer

2 Hazard Identification





Pictogram:

SIGNAL WORD: Danger

Skin CorrosionCategory 1Serious eye damageCategory 1Acute Toxicity (Oral)Category 4CarcinogenicityCategory 1B

HAZARD STATEMENT

H314: Causes severe skin burns and eye damage

H318: Causes serious eye damage

H302: Harmful if swallowed

H350: May cause cancer (Ingestion, Inhalation, dermal absorption)

Precautionary statement

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this products.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor.physician if you feel unwell.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove /take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799



SAFETY DATA SHEET

A SHEET Page :2

P-569

HEAVY DUTY FLOOR WAX STRIPPER

Revised edition no : 03

Effective Date: 23.4.2023

P308+P313 IF exposed or concerned: Get medical advice/attention.
P310 Immediately call a POISON CENTER or doctor/physician.
P321 Specific treatment reference to supplemental first aid instruction.

P330 Rinse Mouth

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation

3 Composition / Information on Ingredients

Hazardous ingredients : Potassium Hydroxide 10 to <30%

CAS No.: 1310-58-3

Active Ingredients : 30%

4 First Aid Measures

Inhalation : Treatment base on judgement of physician in response to reaction of

patient.

Skin Contact : Not expected to present a significant skin hazard under anticipated

condition of normal use.

Eye Contact : Flush with cool running water, lifting the upper and lower eyelids

occasionally until discomfort is relieved.

Ingestion : Not expected to present a significant ingestion hazard under anticipated

conditions of normal use.

5 Fire-Fighting Measures

Fire Hazard - Product is water based and in wet form, its fire hazard is low. The dried

product is combustible, decomposition products can be toxic.

Extinguishing media - Water, powder, CO2, sand...all extinguishing media are suitable.

Protective clothing and seld-contained breathing equipment should be

available for firemen.

- To prevent environmental damage, if possible collect water used to

extinguish the fire in containers.

6 Accidental Release measures

Personal protection - Wear PVC-gloves and goggles to contain spillage.

Avoid repeated skin contact.

Environment precautions - Prevent the product contaminating soil and groundwater. Prevent the

product enetring sewers and waterways.

Cfr.Section 12.

Cleaning / recovery - Large spillages : contain and pump into containers

 Small spillages: absorb on sand, earth...and collect into containers for disposal. Disposal should always comply with local, national or EEC

regulations. Cfr.Section 13.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799



SAFETY DATA SHEET

P-569

HEAVY DUTY FLOOR WAX STRIPPER

Page:3

Revised edition no: 03

Effective Date: 23.4.2023

7 Handling and Storage

Handling : Good industrial and personal hygiene practice should be followed. No

eating and drinking in the workplace. Ensure adequate ventilation.

Storage : Storage temperature : between +5 and +40°C.

Protect from frost and direct sunlight.

Drums and bottles: material is plastic or steel.

Bulk tanks: stainless steel, plastic coated materials... Clean bulk tanks

periodically to prevent accumulation of bacteria.

Specific use : Use the best available methods of handling our Products whereby the

employees enjoy maximum safety and whereby the environment is

minimally affected.

8 Exposure controls / personal protection

Exposure limit values : No danger in normal ambient conditions.

There are no specific limiting values for professional exposure.

There are no biological limiting values.

User should determine the conditions for safe use of the product. Cfr.

Section 7 "Handling and Storage".

Exposure controls:

- Occupational exposure controls : Respiratory protection : not applicable

Hand protection: waterproof PVC-gloves (CE) Eye protection: goggles or safety glasses (CE)

Skin protection: N/A

Avoid repeated skin contact.

- Environmental exposure controls : The product must not be discharge directly into drains or waterways

without treatment.

9 Physical and chemical properties

PH of concentrate : 14.5-15.5 @24-26.5°C

Appearance : clear liquid
Colour : colourless
Specific Gravity (H²0=1) : 1.2-1.25@28.9°C

10 Stabiity and reactivity

Conditions to avoid : Stable under the recommended storage conditions. Cfr. Section 7 "Storage".

Bacterial degradation can occur if the Product is stored for an unuasually

long period or is stored under unsuitable conditions.

Materials to avoid : N/D Hazardous decomposition products : N/D

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799



SAFETY DATA SHEET P-569

HEAVY DUTY FLOOR WAX STRIPPER

Page :4

Revised edition no: 03

Effective Date: 23.4.2023

11 Toxicological information

On product : Low toxicity is indicated by available data.

Under normal industrial conditions, there is no indication that the Product

can be considered as a health risk.

Skin contact should be avoided to prevent possible long-term or short-term

sensitation.

12 Ecological information

Ecotoxicity : The Product is soluble with water and as such could cover considerable

distances if spilled into waterways. Even a small spillage will whiten the

appearance of water. Water for sewage treatment, that has been contaminated.

with small quantities of the Product, will not affect the biomass. High

concentrations may be harmful to fish and micro organisms.

Mobility : Not established.

Persistence and degradability : There is only a slow environmental degradation of the Product.

Bioaccumulative potential : There is seemingly no tendency for bioaccumulation.

Other adverse effects : Unknown

13 Disposal Considerations

- The following advice only applies to the product as supplied

- Combination with other materials may well indicate another route of disposal. If in doubt, contact local TLC-KOYA CHEMICALS MANUFACTURING SDN BHD or local authorities.
- Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor.
- Care should in any case be taken to ensure compliance with national and local regulations.
- This product is not suitable for disposal by either landfill or via municipal sewers, drains, and natural streams, rivers or seas, they will effect the relationship between livings things, plants and their environment.

14 Transport information

General information : This Product is not regulated for road/rail & sea transport.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799



SAFETY DATA SHEET P-569

HEAVY DUTY FLOOR WAX STRIPPER

Page :5

Revised edition no: 03

Effective Date: 23.4.2023

15 Regulatory Information

Classification and labeling : Classification /symbol - not regulated

Governing directive : Occupational Safety and Health (Classification, Packaging and Labeling of

Hazardous Chemicals) Regulations 1997

Safety advice : (May contain information in excess of requirements under applicable laws.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this products.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

16 Other information

Further information : None Print date : 23.4.2023

N/A - Not Applicable N/D - Not Determined

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from data or test results obtained by us, are based on the current state of our knowledge at the time such recommendations are made. When additional information is obtained, these recommendations may be updated. They may also be influenced by circumstances outside our control. Notwithstanding such recommendations, the user is responsible to determine that the product as supplied by us, is suitable for the process or purpose he intends to use it. The user of the product is solely for compliance with all laws and regulation applying to the use of the product. Since we cannot control the application, use or processing of the products, we do not accept responsibility therefore. The user shall ensure that the intended use of the products will not infringe in any party's intellectual property rights.

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799