

Page :1

Revised edition no: 02

P-633 MOLYBDENUM GREASE

Effective Date: 29.3.2023

Identification of the Product and the company

Chemical name : Molybdenum Grease Type of product chemical family : Petroluem Grease

Distributor : TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No. 22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800. Ulu Tiram, Johor. Malaysia. Tel: 607-8675798 Fax: 607-8675799

Emergency phone no : See distributor

2 Hazard Identification

HAZARD PICTOGRAM



SIGNAL WORD: WARNING

CLASSIFICATION

Skin irritation category 2

Hazard Statement

H315 Causes skin irritation

Precautionary statement-Prevention

P264 Wash thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statement-response

P302 + P352 IF ON SKIN: wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.

3 Composition / Information on Ingredients

Common name	Proportion
Base Oils	> 85%
Molybdenum Disulfide	< 5%
Graphite	< 5%
Proprietary Additives	< 5%

4 First Aid Measures

Acute Swallowed : This is not expected to be a means of entry during routine operation.

Ingestion of small quantities should not cause irritation.

Eye : May cause slight irritation to the eyes.

Skin : May be mildly irritating to the skin, High pressure injection through the skin,

when using appatus such as grease guns, can be highly irritating and may cause

localized damage.

Inhaled : No data to indicate a toxic inhalation azard. Inhalation of vapours or mist

(generated at elevated temperatures) may cause irritation to the nose and throat. May be harmful if exposed to vapour, mists or fumes resulting from

thermal decomposition products.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799



Page:2

Revised edition no: 02

Effective Date: 29.3.2023

P-633 MOLYBDENUM GREASE

: Prolonged or repeated skin contact may lead to drying of the skin,

Swallowed First Aid

: If a large quantity is ingested seek medical attention. It may be necessary to induce vomiting, taking extreme care that the person dows not aspirate

into the lungs. If aspiration occurs, urgent medical attention should be sought.

Eve : Wash with copious amounts of water for 15 minutes and seek medical

advice if irritation develops or persists.

Skin : Remove contaminated clothing and wash skin thoroughly with plenty of

soap and water. High pressure injection through the skin requires urgent medical attention for possible incision, irrigation and/or debridement. Contact with molten material will require treatment by a physician for burns

(Do not remove material)

Inhaled : Remove person to fresh air and seek medical advice. If not breathing, apply

artificial respiration and seek urgent medical aid.

First Aid Facilities : Eye wash fountains and safety showers are recommended.

Advice to doctor : Treat symptomatically.

5 Fire-Fighting Measures

Hazards of use / storage

List of dangerous decomposition or combustion

Fire-fighting recommendations

: This product is combustible if preheated

: Combustion products oxided of carbon, nitrogen phosporus and zinc.

: Keep storage tanks, pipelines, containers, fire exposed surfaces, etc.

cool with water spray.

Type of extiguisher / Fire-fighting agents

Precaution

Protective Clothing

Reativity

: Use foam, carbon dioxide or dry chemical. Do not use water jets.

: Water may cause splattering or boil-over.

: Self-contained breathing appratus is recommended during a fire.

: May react with strong oxidising agents.

Accidental Release Measures

Personal protection

Cleaning / recovery

Environment precautions

- Wear PVC-gloves and goggles to contain spillage. Avoid repeated skin contact.

- Prevent the product contaminating soil and groundwater. Prevent the product

entering sewers and waterways. Cfr. Section 12. - Large spillages : contain and pump into containers

- Small spillages : absorb on sand, earth... and collect into containers for disposal.

Disposal should always comply with local, national or EEC regulations.

Cfr. Section 13.

Handling and Storage

Storage and Transport

: Classified as a combustible solid. Store in a well ventilated area away from ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Do not store in plastic containers unless appreved for this application.

Exposure controls / personal protection

Exposure standards : If the material is subject to high temperature operations and mists or

> vapours are generated the Manufacturer recommends: Time Weighted Average (TWA): 5 mg/m³ (oil mist). Short Term Exposure Limit (STEL): 10mg/m³ (oil mist).

Time Weighted Average (TWA): 5 mg/m³ Short Term Exposure Limit (STEL): 10mg/m3

Engineering Controls : Special ventilation is not normally required. However, in the operation of certain

equipment or at elevated temperatures mistsor vapour may be generated and localised exhaust ventilation should be provided to maintain airborne concentration

levels below the manufacturer recommended exposure standard.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



Page:3

Revised edition no: 02

Effective Date: 29.3.2023

P-633 MOLYBDENUM GREASE

Personal Protection

Respirator Type (AS 1716) : During routine operation a repirator is not required. However, if mists or vapours

are generated, an approved organic vapour/particulate respirator is required.

: PVC. Neoprene or Nitrile gloves are recommended. Glove Type

Eve Protection : Safety glasses or goggles are recommended to avoid eye contact.

If the material is used at elevated temperatures or under pressure a full face

shield should be worn.

: During normal operating procedured, long sleeved clothing is recommended Clothing

to provide skin protection. Soiled clothing should be washed with detergent

prior to re-use.

Physical and Chemical Properties

Colour : Black **Appearance** : Grease Vapour Pressure (mmgHg at 20°C) : Typically < 0.1 Density @ 15°C (g/mL) : Typically 0.9

Flashpoint (°C) : >200°C (ASTM D-93)

Flammability Limits (%) : Not available

Solubility in Water (g/L) : Not miscible with water

Other Properties

Work Penetration @ 25°C : 260-295 Dropping Point (°C) : Typically 260°C Viscosity @ 40°C (cSt) : Typically 150

10 Stability and Reactivity

Conditions to avoid : Stable under the recommended storage conditions. Cfr. Section 7 "Storage".

Bacterial degradation can occur if the Product is stored for an unuasually

long period or is stored under unsuitable conditions.

Materials to avoid : N/D Hazardous decomposition products : N/D

11 Toxicological Information

: Low toxicity is indicated by available data. On product

Under normal industrual conditions, there is no indication that the Product

can be considered as a health risk.

Skin contact should be avoided to prevent possible long-term or short-term

sensitation.

12 Ecological Information

Ecotoxicity : The Product is soluble with water and as such could cover considerable

distances if spilled into waterways. Even a small spillage will whiten the

appearance of water. Water for sewege treatment, that has been contaminated.

with small quantities of the Product, will not affect the biomass. High

concentrations may be harmful to fish and micro organisms.

Mobility : Not established.

Persistence and degradability : There is only a slow environmental degradation of the Product.

Bioaccumulative potential : There is seemingly no tendency for bioaccumulation.

Other adverse effects : Unknown.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



Page :4

Revised edition no: 02

P-633 MOLYBDENUM GREASE

Effective Date: 29.3.2023

13 Disposal Considerations

Spills are easily contained due to the nature of the product. Caution: The product may be slippery. The product should be shovelled into a metal drum and treated as a solid waste. Follow state or local regulations for the disposal of the waste. Clean area with soap and water. Do not allow product to enter drains, sewers or water courses-inform local authorities if this occurs.

14 Transport Information

General information : This Product is not regulated for road/rail & sea transport.

15 Regulatory Information

Classification and labeling : Classification / symbol - not regulated

Governing directive : Occupational Safety and Health (Classification, packaging and Labeling of

Hazardous Chemicals) Regulations 1997.

Safety advice : May contain information in excess of requirements under applicable laws.

P264 Wash thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P302 + P352 IF ON SKIN: wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.

16 Other information

NFPA hazard rating

Health : Irritation, minor residual injury (1) Flammability : Burns only if pre-heated (1)

Reactivity : N/A (0) Special Hazard : N/A

NPCA HMIS Health : 2 Moderate hazard

PERS. Protect Index : Burns only if pre-heated (1)

Print date : 29.3.2023

N/A - Not Applicable N/D - Not Determined

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from data or test results obtained by us, are based on the current state of our knowledge at the time such reommendations are made. When additional information is obtained, these recommendations may be updated. They may also be influenced by circumstances outside our control. Notwithstanding such recommendations, the user is responsible to determine that the product as supplied by us, is suitable for the process or purpose he intends to use it. The user of the product is solely for compliance with all laws and regulation applying to the use of the product. Since we cannot control the application, use or processing of the products, we do not accept responsibility therefore. The user shall ensure that the intended use of the products will not infringe in any party's intellectual property rights.

Tel: 607-8675798 Fax: 607-8675799