



PRODUCT SPECIFICATION	Page :1
	Revised edition no : 01
P-505 HEAVY DUTY GREASE	Effective Date: 30-6-2014

Description:

P-505 Heavy Duty Grease is high quality grease providing maximum lubrication and performance for a broad range of application. It has steady working temperature range up to approx. 80°C.

Precaution

If resists water wash out, provides good mechanical stability and reduced friction and wear. Avoid contact with skin. Do not ingest of this should occur, drink large volumes of water and seek medical attention.

Keep out of reach of children.

Specification

Physical state : Semi solid at ambient temperature
Colour : Red
Odour : Characteristic mineral oil
Density at 15°C (Kg/M3) : 900
Solubility in water : Negligible

Storage

Keep container sealed when not in use. Keep away from direct sunlight.

Packing

1/2Kg, 4Kgs, 15Kgs, and 180Kgs

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com