

Page:1

Revised edition no: 02

P-520 HI-TEMPERATURE SPRAY GREASE

Effective Date: 12.5.2019

Identification of the Product and the company

Chemical Name : HI Temperature Spray Grease

Type of product chemical family : N/A Use : Grease

Distributor : TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia. Tel: 607-8675798 Fax: 607-8675799

Emergency phone nr : See distributor

UN NUMBER : DG UN1950 / IMO 2.1 / JPA 3

2 Hazard Identification

Flammable Aerosol Category 1

Hazard Statement

H222 Extremely flammable aerosol

Precautionary Statement

P210 Keep away from heat/sparks/open flames/hor surfaces - No smoking

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

3 Composition / Information on Ingredients

Hazardous ingredients : Perchloroethylene 31% TLV: 100ppm

Petroleum Grease 21% TLV: 100ppm LPG 30% TLV: 1000ppm

4 First Aid Measures

Inhalation : Move to fresh air. Seek medical attention.

Skin Contact : Flush with copious amount of water for 15 minutes.

Eye Contact : Wash with copious quantities of water for 15 minutes. Seek medical

attention where necessary.

Ingestion : Do not induce vomiting. Contact physician immediately.

5 Fire-Fighting Measures

Flash Point (Material Used) : 192c (coc) ASTM D92

Extinguishing Media : Carbon dioxide, foam, dry chemical powder and water fog .

Special Fire Fighting Procedures : Use water to keep container cool, fire exposed.

Unusual Fire and Explosion Hazards : Flammable, Vapor accumulation could flash and / or explode if ignited.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799



Page :1

Revised edition no : 02

P-520 HI-TEMPERATURE SPRAY GREASE

Effective Date: 12.5.2019

6 Accidental Release measures

Personal protection - Wear PVC-gloves and goggles to contain spillage.

Avoid repeated skin contact.

Environment precautions - Prevent the product contaminating soil and groundwater. Prevent the

product enetring sewers and waterways.

Cfr.Section 12.

Cleaning / recovery - Large spillages : contain and pump into containers

- Small spillages: absorb on sand, earth...and collect into containers for disposal. Disposal should always comply with local, national or EEC

regulations. Cfr.Section 13.

7 Handling and Storage

Handling : Good industrial and personal hygiene practice should be followed. No eating

and drinking in the workplace. Ensure adequate ventilation.

Storage : Storage temperature : between +5 and +40°C.

Protect from frost and direct sunlight.

Drums and bottles: material is plastic or steel.

Bulk tanks: stainless steel, plastic coated materials... Clean bulk tanks

periodically to prevent accumulation of bacteria.

Specific use : Use the best available methods of handling our Products whereby the

employees enjoy maximum safety and whereby the environment is

minimally affected.

Precautionary labeling : Container is pressurized

Other handling and storage requirement : Avoid heat & open flames. Do not puncture or throw into fire. Do not expose

to temperature above 65°C (150F). Avoid contact with skin.

8 Exposure controls / personal protection

Exposure limit values : No danger in normal ambient conditions.

There are no specific limiting values for professional exposure.

There are no biological limiting values.

User should determine the conditions for safe use of the product. Cfr.

Section 7 "Handling and Storage".

Exposure controls:

- Occupational exposure controls : Respiratory protection : not applicable

Hand protection : waterproof PVC-gloves (CE) Eye protection : goggles or safety glasses (CE)

Skin protection: N/A

Avoid repeated skin contact.

- Environmental exposure controls : The product must not be discharge directly into drains or waterways without

treatment.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



Page:1

Revised edition no: 02

P-520 HI-TEMPERATURE SPRAY GREASE

Effective Date: 12.5.2019

Physical and chemical properties

Boiling Point (°F) : N/A Vapor Pressure (mm hg) : 700 Vapor Density (Air=1) : 2.00 PH of concentrate : N/A

Appearance : Light, yellowish liquid

Solubility in water : Insoluble Specific Gravity (H20=1) : 0.9 - 1.1 Volatile : >77 Evaporation Rate (Water=1) : N/A Melting Point : N/A

10 Stabiity and reactivity

Stability

Condition to avoid : Keep away from heat source, open flames and other Source of ignition. Imcompatibility (materials to avoid)

: Avoid contact with strong oxidants such as liquid chlorine and concentrated

oxygen.

Hazardous Decomposition Products : HC1, CO, CO2

11 Toxicological information

On product : Low toxicity is indicated by available data.

Under normal industrial conditions, there is no indication that the Product

can be considered as a health risk.

Skin contact should be avoided to prevent possible long-term or short-term

sensitation.

12 Ecological information

Ecotoxicity : The Product is soluble with water and as such could cover considerable

> distances if spilled into waterways. Even a small spillage will whiten the appearance of water. Water for sewage treatment, that has been

contaminated.

with small quantities of the Product, will not affect the biomass. High

concentrations may be harmful to fish and micro organisms.

Mobility : Not established.

Persistence and degradability : There is only a slow environmental degradation of the Product.

Bioaccumulative potential : There is seemingly no tendency for bioaccumulation.

Other adverse effects : Unknown

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



Page :1

Revised edition no: 02

P-520 HI-TEMPERATURE SPRAY GREASE

Effective Date: 12.5.2019

13 Disposal Considerations

- The following advice only applies to the product as supplied

- Combination with other materials may well indicate another route of disposal. If in doubt, contact local TLC-KOYA CHEMICALS MANUFACTURING SDN BHD or local authorities.
- Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor.
- Care should in any case be taken to ensure compliance with national and local regulations.
- This product is not suitable for disposal by either landfill or via municipal sewers, drains, and natural streams, rivers or seas, they will effect the relationaship between livings things, plants and their environment.

14 Transport information

IMO PROPER SHIPPING NAME : Spray Grease

IMO U.N. CLASS : 2.1 IMO U.N. NUMBER : UN 1950

IMO LABEL : Flammable Gases



15 Regulatory Information

Classification and labeling : Classification /symbol - not regulated

Governing directive : Occupational Safety and Health (Classification, Packaging and Labeling of

Hazardous Chemicals) Regulations 1997

Safety advice : (May contain information in excess of requirements under applicable laws.

S23 Do not breathe gas/fumes/vapor/spray

S24 Avoid contact with skin

S33 Take precautionary measures against static discharges
S62 If swallowed, do not induce vomiting: seek medical advice

immediately and show this container or label.

16 Other information

Further information : None
Print date : 12.5.2019

N/A - Not Applicable N/D - Not Determined

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from data or test results obtained by us, are based on the current state of our knowledge at the time such recommendations are made. When additional information is obtained, these recommendations may be updated. They may also be influenced by circumstances outside our control. Notwithstanding such recommendations, the user is responsible to determine that the product as supplied by us, is suitable for the process or purpose he intends to use it. The user of the product is solely for compliance with all laws and regulation applying to the use of the product. Since we cannot control the application, use or processing of the products, we do not accept responsibility therefore. The user shall ensure that the intended use of the products will not infringe in any party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com