



SAFETY DATA SHEET

Page :1

Revised edition no : 00

P-576 AUTO PAINT THINNER

Effective Date: 4.10.2023

1 Identification of the Product and the company

Chemical Name : AUTO PAINT THINNER
Type of product chemical family : N/A
Producer : TLC-KOYA CHEMICALS MANUFACTURING SDN BHD
No.22 & 23, Jalan Maju 1,
Cemerlang Industrial Estate,
81800 Ulu Tiram, Johor, Malaysia.
Tel: 607-8675798 Fax: 607-8675799
Website: www.koyachemicals.com Email: admin@koyachemicals.com

Emergency phone no : See producer
UN NUMBER : UN 1263 / IMO 3

2 Hazard Identification



SIGNAL WORD: DANGER/BAHAYA

Flammable liquids	Category 3
Skin irritation	Category 2
Eye irritation	Category 2
Reproductive toxicity	Category 2
Specific Target Organ Toxicity-Single Exposure	Category 3
Specific Target Organ Toxicity-Repeated Exposure	Category 2

HAZARD STATEMENT

H226: Flammable liquid and vapour
H315: Causes skin irritation
H319: Causes serious eye irritation
H336: May cause drowsiness or dizziness
H361: Suspected of damaging the unborn child
H373: May cause damage to organs through prolonged or repeated exposure

PRECAUTIONARY STATEMENT

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a wellventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P314 Get medical advice/attention if you feel unwell
P321 Specific treatment reference to supplemental first aid instruction.
P362 Take off contaminated clothing and wash before reuse.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.
Tel: 607-8675798 Fax: 607-8675799
Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



SAFETY DATA SHEET

Page :2

Revised edition no : 00

P-576 AUTO PAINT THINNER

Effective Date: 4.10.2023

P303 + P361 + P353	IF ON SKIN (or hair):Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use Foam and dry chemical powder, carbon dioxide extinguisher for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation

3 Composition / Information on Ingredients

Hazardous ingredients	: Methyl Benzene 40 - 60%
	ACGIH TLV : TWA
	ACGIH STEL : 150ppm
	Isopropanol 10 - 25%
	ACGIH TLV : 100ppm
	2-Butanone 10 - 15%
	4 Methyl 2 Pentanone 10 - 15%
	Ethylene Glycol Monobuthyl Ether 2 - 5%

4 First Aid Measures

Eye Contact	: Flush with cool running water, lifting the upper and lower eyelids occasionally until discomfort is relieved.
Skin Contact	: Not expected to present a significant skin hazard under anticipated condition of normal use.
Ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
Inhalation	: Treatment base on judgment of physician in response to reaction of patient.

5 Fire-Fighting Measures

Flash Point (Tag Closed Tester)	: Below 30°C
Extinguishing Media	: Foam and dry chemical powder, carbon dioxide, sand or earth may be used for small fire only.
Special Fire Fighting Produres	: Self-contained breathing apparatus are recommended for fire fighters.
Unusual Fire and Explosion Hazards	: None.

6 Accidental Release measures

Personal protection	- Wear PVC-gloves and goggles to contain spillage. Avoid repeated skin contact.
Environment precautions	- Prevent the product contaminating soil and groundwater. Prevent the product enetring sewers and waterways. Cfr.Section 12.
Cleaning / recovery	- Large spillages : contain and pump into containers - Small spillages : absorb on sand, earth...and collect into containers for disposal. Disposal should always comply with local, national or EEC regulations. Cfr.Section 13.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



SAFETY DATA SHEET

Page :3

Revised edition no : 00

P-576 AUTO PAINT THINNER

Effective Date: 4.10.2023

7 Handling and Storage

Handling	: Good industrial and personal hygiene practice should be followed. No eating and drinking in the workplace. Ensure adequate ventilation.
Storage	: Storage temperature : between +5 and +40°C. Protect from frost and direct sunlight. Drums and bottles : material is plastic or steel. Bulk tanks : stainless steel, plastic coated materials... Clean bulk tanks periodically to prevent accumulation of bacteria.
Specific use	: Use the best available methods of handling our Products whereby the employees enjoy maximum safety and whereby the environment is minimally affected.

8 Exposure controls / personal protection

Exposure limit values	: No danger in normal ambient conditions. There are no specific limiting values for professional exposure. There are no biological limiting values. User should determine the conditions for safe use of the product. Cfr. Section 7 "Handling and Storage".
Exposure controls:	
- Occupational exposure controls	: Respiratory protection : not applicable Hand protection : waterproof PVC-gloves (CE) Eye protection : goggles or safety glasses (CE) Skin protection : N/A Avoid repeated skin contact.
- Environmental exposure controls	: The product must not be discharge directly into drains or waterways without treatment.

9 Physical and chemical properties

Boiling Point (°F)	: Below 30°C
Appearance	: Clear liquid and chemical odor
Colour	: Colourless
Solubility in water	: immiscible with and lighter than water.
Specific Gravity (H ₂ O=1)	: 0.84 - 0.85 @15.6°C

10 Stability and reactivity

Conditions to avoid	: Stable under the recommended storage conditions. Cfr. Section 7 "Storage". Bacterial degradation can occur if the Product is stored for an unusually long period or is stored under unsuitable conditions. Keep away from spark, do not empty into drain.
Incompatibility (materials to avoid)	: None known
Hazardous Polymerization	: Nil
Materials to avoid	: N/D
Hazardous decomposition products	: N/D

11 Toxicological information

On product	: Low toxicity is indicated by available data. Under normal industrial conditions, there is no indication that the Product can be considered as a health risk. Skin contact should be avoided to prevent possible long-term or short-term sensitisation.
------------	--

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



SAFETY DATA SHEET

Page :4

Revised edition no : 00

P-576 AUTO PAINT THINNER

Effective Date: 4.10.2023

12 Ecological information

Ecotoxicity	: The Product is soluble with water and as such could cover considerable distances if spilled into waterways. Even a small spillage will whiten the appearance of water. Water for sewage treatment, that has been contaminated. with small quantities of the Product, will not affect the biomass. High concentrations may be harmful to fish and micro organisms.
Mobility	: Not established.
Persistence and degradability	: There is only a slow environmental degradation of the Product.
Bioaccumulative potential	: There is seemingly no tendency for bioaccumulation.
Other adverse effects	: Unknown

13 Disposal Considerations

- The following advice only applies to the product as supplied
- Combination with other materials may well indicate another route of disposal. If in doubt, contact local TLC-KOYA CHEMICALS MANUFACTURING SDN BHD or local authorities.
- Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor.
- Care should in any case be taken to ensure compliance with national and local regulations.
- This product is not suitable for disposal by either landfill or via municipal sewers, drains, and natural streams, rivers or seas, they will effect the relationship between living things, plants and their environment.

14 Transport information

IMO PROPER SHIPPING NAME	: NORMAL THINNER
IMO U.N. CLASS	: 3
IMO U.N. NUMBER	: UN 1263
IMO LABEL	: Flammable Liquid



15 Regulatory Information

Classification and labeling	: Classification /symbol - not regulated
Governing directive	: Occupational Safety and Health (Classification, Packaging and Labeling of Hazardous Chemicals) Regulations 1997
Safety advice	: (May contain information in excess of requirements under applicable laws.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a wellventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell
P321	Specific treatment reference to supplemental first aid instruction.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



SAFETY DATA SHEET	Page : 5
	Revised edition no : 00
P-576 AUTO PAINT THINNER	Effective Date: 4.10.2023

P362	Take off contaminated clothing and wash before reuse.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair):Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use Foam and dry chemical powder, carbon dioxide extinguisher for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation

16 Other information

Further information : None
Print date : 4.10.2023

N/A - Not Applicable N/D - Not Determined

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from data or test results obtained by us, are based on the current state of our knowledge at the time such recommendations are made. When additional information is obtained, these recommendations may be updated. They may also be influenced by circumstances outside our control. Notwithstanding such recommendations, the user is responsible to determine that the product as supplied by us, is suitable for the process or purpose he intends to use it. The user of the product is solely for compliance with all laws and regulation applying to the use of the product. Since we cannot control the application, use or processing of the products, we do not accept responsibility therefore. The user shall ensure that the intended use of the products will not infringe in any party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com