

# PRODUCT SPECIFICATION

Page :1

Revised edition no: 00

P-730 SAE 40 CF/SD

Effective Date: 3-1-2024

# PRODUCT DESCRIPTION

SAE 40 CF/SD is a high performance engine oil formulated with premium base oil enhanced with selective additive package designed to meet the requirements of both gasoline and diesel engines where CF/SD is recommended.

# **FEATURES AND BENEFITS**

- Excellence between gasoline and diesel engines requirements.
- Good protection against high temperature deposits in gasoline and diesel engines.
- Efficient control on rust under low temperature operating conditions in gasoline and diesel engines.

# **APPLICATION**

- On- and off-highway heavy duty applications that require up to CF service level.
- Suitable for older passenger cars with gasoline engines in which SD or lower performance level oils are specified.

### **PHYSICAL PROPERTIES**

Property	
SAE Grade	40
Specific Gravity @ 28.9°C	0.875
Viscosity @ 40°C, cst. ASTM D445	165
Viscosity @ 100°C, cst. ASTM D445	15.6
Viscosity Index, ASTM D2270	96

These data are given as an indication of typical values and not as exact specifications.

# **STORAGE**

- Store in a dry and cool area (below 40°C).
- · Keep away from direct sunlight.
- Keep away from food and children.

#### **AVAILABLE PACKAGES**

1Ltr, 5Ltr, 18Ltr, 200Ltr

#### Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property right.

Tel: 607-8675798 Fax: 607-8675799

 $Website: www.koyachemicals.com \\ EMAIL: admin@koyachemicals.com$