



PRODUCT SPECIFICATION	Page :1
	Revised edition no : 00
P-732 HYDRAULIC OIL AW 46	Effective Date: 1-11-2017

Description:

P-732 Hydraulic Oil AW46 is a superior quality multi-purpose and sulphur phosphorous lubricant oil. It is produced with Group II base oil and special additive distinguished by its high oxidation resistant, anti-stick slip properties, excellent rust prevention and corrosion protection meet AW46.

Applications and Benefits:

- Provide Anti-wear, Anti-stick and Anti-slip protection
- Excellent rust and corrosive protection
- Provide good water separation

PRODUCT SPECIFICATIONS: AW 46

<u>TEST</u>	<u>UNIT</u>	<u>TYPICAL RESULTS</u>
Specific Gravity	-	0.85 - 0.86
Viscosity @ 40 Deg C	cst	58 - 71
Flash Point	°C	224
Pour Point	°C	-24
Demulsibility		Pass

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot assume responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com