



PRODUCT SPECIFICATION	Page :1
P-745 5W-40 SN	Revised edition no : 00
FULLY SYNTHETIC ENGINE OIL	Effective Date: 17/7/2024

PRODUCT DESCRIPTION

5W-40 is a high performance engine oil formulated with premium base oil enhanced with additives possess pour point depression ,fulfill requirement for shear stability, control oxidation and catalytic convertor fouling and protect against sludge deposits & valve train wear designed to meet the requirements of gasoline engines.

FEATURES AND BENEFITS

- Saves on maintenance costs.
- Excellent oxidation resistance provide protection against in-service oil degradation that contributes to sludge deposits and valve train wear.
- Inherent stay-in-grade shear stability.

APPLICATION

- Specially designed for high performance gasoline engines in passenger cars.
- Light truck gasoline engines where API SN or earlier API 'S' performance categories are specified.

PHYSICAL PROPERTIES

Property	
SAE Grade	SAE 5W-40
Specific Gravity @ 28.9°C	0.845
Viscosity @ 40°C, cst. ASTM D445	100
Viscosity @ 100°C, cst. ASTM D445	14.4
Viscosity Index, ASTM D2270	148

These data are given as an indication of typical values and not as exact specifications.

STORAGE

- Store in a dry and cool area (below 40°C).
- Keep away from direct sunlight.
- Keep away from food and children.

AVAILABLE PACKAGES

4Ltr, 18Ltr, 200Ltr

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property right.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com