



PRODUCT SPECIFICATION	Page :1
P-655 PU GREASE	Revised edition no : 01
	Effective Date: 13.6.2023

Product Information

P-655 PU Grease is a state of the art polyurea based lubricating grease based on mineral oil. The grease has excellent mechanical stability over a wide temperature range

P-655 PU Grease is applicable to long term lubrication of all kind of medium and heavy load ball bearings and sliding bearings in steel works, for example, fan bearings, motor bearings, conticaster, sintering machine, casthouse roller etc.

Key Properties

Operating Temperature	-30 to 230°C.
Appearance	Refined
Color	brown
Vapor pressure	negligible at ambient
Solubility in water wt%	negligible
Freezing/melting point	less than ambient
Evaporation rate	negligible
Boiling point (°C)	N/A
Flash point (open cup, °C)	N/A

Packing

½ Kg, 15 Kg & 180 Kg

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com