



Prolife 5W-30

Fully Synthetic

Official Approvals:

Approved under VW standard 504 00 and VW standard 507 00

Recommended by Comma for applications requiring:

MB 229.51; BMW LL-04; PORSCHE C30
ACEA C3

Product Features:

- Fully synthetic, high performance 5W-30 low SAPS oil for modern VW-Audi group petrol and diesel vehicles including those operating under long life service regimes. Also protects exhaust after-treatment units.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 10-04-2019

Typical Inspection Data:

Density @ 20°C	0.845 g/cm ³
Viscosity @ 100°C	11.7 cSt
Viscosity @ 40°C	65 cSt
Viscosity Index	177
Viscosity CCS @ -30°C	5700 cP
T.B.N.	8.6 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.17%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C