


IC650 Specifications



Above: The IC650 comes with a universal mounting plate for use with Skyjack or Genie Scissor lifts.

Charger / Lift Model Cross-Reference		
Replaces Genie charger model number	105739	
Compatible Genie machines	GS-1530/32	GS-1930/32
	GS-2032	GS-2046
	GS-2632	GS-2646
	GS-3232	GS-3246
	QS-12	QS-15
	QS-20	TZ-30
	TZ-50	
Replaces Skyjack charger model numbers	161827 / 161828	
Compatible Skyjack machines	SJ3215	SJ3219
	SJ3220	SJIII3226
	SJIII4620	SJIII4626
	SJIII4632	SJIII4832
	SJIII6826	SJIII6832

Key Specifications	IC650 Charger for Aerial Work Platforms	
Warranty	2-year limited warranty	
Dimensions	9.9" x 7.3" x 3.1" (25.2 x 18.6 x 8 cm)	
Weight	< 6.5 lbs. (< 3 kg.)	
Charger voltage / current	24 V / 27 A	
Maximum DC output power	650 W	
AC input voltage range	85-270 VAC	
Deep discharge recovery	Can recharge packs discharged as low as 1.2 V / cell	
Durability	Sealing rated to IP66 against high pressure spray and dirt Designed for long service life on-board: tolerates high levels of vibration and shock	
Battery type	Preloaded charging profiles for Trojan, U.S. Battery, Interstate and Discover (flooded and AGM types), plus generic flooded and AGM batteries	
Interlock	Functional interlock to prevent use while charging	
Operating temperature	-40°F to 149°F (-40°C to +65°C)	Derated at >104°F (40°C)

Regulatory / Safety	
Efficiency	93.5% peak, California Energy Commission compliant
Safety	UL1564, CSA 107.2, EN 60335-2-29
Emissions	FCC Part 15 / ICES 003 Class A, EN55011
Immunity	EN61000-3-2, EN61000-3-3, EN 61000-4-2/-3/-4/-5/-6/-11
Reverse polarity	Electronic protection with auto-reset
Short circuit	Electronic current limit

In the box:

- + IC650 Charger
- + Mounting plate for installation in Skyjack / Genie lifts
- + Sealed, locking AC cable
- + DC cable with ring terminals and temperature sensor
- + Interlock cable
- + Installation / use instructions

Additional Benefits

- + AC cable seals against dirt / moisture and locks to charger (won't vibrate loose)
- + AC/DC cables are replaceable
- + Recharge from very deep discharge—as low as 1.2 V/cell



Contact Delta-Q for pricing and availability information, including wholesale quantities.

Web: delta-q.com/rental
 Phone: +1.604.327.8244
 E-mail: sales@delta-q.com

Delta-Q Technologies
 3755 Willingdon Avenue
 Burnaby, BC V5G 3H3
 Canada



NEW!
CONTACT US
FOR PRICING &
AVAILABILITY

Delta-Q IC650

Battery Charger for Genie & Skyjack Aerial Work Platforms

Key Features

Fits in existing mounting holes and connects to existing cables in Skyjack and Genie scissor lifts

Sealed charger (IP66) with die cast design:
Tolerates high-pressure spray, dirt and vibration

Proven charging profiles for battery brands such as Trojan, U.S. Battery, Interstate, and Discover.

Wide AC input voltage range (100-240V) and high efficiency (93.5% peak)

Benefits

+ Easy to install—a drop-in replacement for the existing battery charger

+ Extremely durable: increased machine uptime
+ 8+ year service life: will last into lift's second life

+ Keep lifts running for longer at top performance
+ Reduce charge times / protect battery investment
+ Simple to use: change profiles by pressing a button

+ Meets CEC energy efficiency standards
+ Reduce electricity costs
+ Provides reliable DC power even when used with on-site AC generators