AM SERIES

PUSH-AROUND VERTICAL LIFT



Performance

Platform Height - Elevated		
20AM	6.15 m	
25AM	7.60 m	
30AM	9.02 m	
36AM	11.00 m	
41AM	12.34 m	
Platform Capacity		
20AM	160 kg	
25AM	160 kg	
30AM	135 kg	
36AM	135 kg	
41AM	135 kg	
Stowed Height		
20AM	1.97 m	
25AM	1.97 m	
30AM	1.97 m	
36AM		
Standard Position	2.64m	
Tilt Back Position	1.94 m	
41AM	3.64	
Standard Position	2.64 m	
Tilt Back Position	2.00 m	
Base Length – Stowed	110	
20AM	1.19 m	
25AM	1.24 m	
30AM	1.32 m	
36AM	1.38 m	
41AM	1.46 m	
Overall Width – Stowed	0.74	
20AM	0.74 m	
25AM	0.74 m	
30AM	0.74 m	
36AM 41AM	0.74 m 0.74 m	
	0.74 111	
Outrigger Footprint (LxW)	1.57 1.20	
20AM	1.57 m x 1.38 m	
25AM	1.57 m x 1.38 m	
30AM	1.89 m x 1.81 m	
36AM	2.02 m x 2.02 m 2.14 m x 2.18 m	
41AM	2.14 III X 2.18 III	
Weight	AC 226 los	DC 200 l
20AM	AC 336 kg	DC 390 kg
25AM	AC 374 kg	DC 410 kg
30AM	AC 404 kg	DC 427 kg
36AM	AC 481 kg	DC 526 kg



Standard Features

- Low Maintenance Anodized Aluminum Non-Marking Solid Tyres Mast
- Dual Chain Vertical Mast
- 4 Easy Fit Outriggers with Interlock Switch and Telltale Light Indicator
- 0.66 m x 0.66 m Platform with Drop Bar Entry Gate
- 1 x 12V DC Deep Cycle Battery
- Removable SCR Battery Charger
- Battery Discharge Indicator at Base
- Transportation Tie Downs
- Built-In Fork Truck Pockets
- AS/ NZS 1418.10 Compliant

Accessories & Options

- 109 cm -Straddle Kit including Interlock Adapter (Factory Order)
- 140 cm -Straddle Kit including Interlock Adapter (Factory Order)
- Fluorescent Light Tube Caddy
- Tool Tray (20 x 45 x 12.5 cm)
- · AC Outlet to Platform



The JLG "1 & 5" Warranty

41AM

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications.

AC 499 kg

DC 558 kg

JLG Industries (Australia)

358 Park Road Regents Park, NSW 2143 Telephone 02 8718 6300 Fax 02 8718 6377

www.jlg.com.au

An Oshkosh Corporation Company