



# Aerial Work Platforms

## IWP<sup>®</sup> Super Series<sup>™</sup>

### Specifications

Measurements	IWP-200		IWP-250		IWP-300	
	US	Metric	US	Metric	US	Metric
Working height*	20 0.2 m	6.10 m	25 0.0 m	6.60 m	29 0.0 m	11 m
Platform height	10 0.2 m	4.10 m	17 0.0 m	7.61 m	20 0.0 m	9 m
▲ Hydraulic outreach**	7 0.2 m	2.04 m	—	—	—	—
▲ Height - chassis						
Fully extended	6 0.4 m	1.80 m	6 0.4 m	1.80 m	6 0.4 m	1.80 m
Fully retracted	6 0.4 m	1.80 m	6 0.4 m	1.80 m	6 0.4 m	1.80 m
▲ Length	5 0	1.52 m	5 0	1.52 m	5 0	1.52 m
▲ Width - standard beam with base	2 0.0 m	0.50 m	2 0.0 m	0.50 m	—	—
with base	—	—	—	—	2 0.4 m	1.52 m
Drive wheel***	6 m	0.19 m	6 m	0.19 m	7 m	0.23 m

### Productivity

LB capacity (400/20/20A)	200 lbs	100 kg	200 lbs	100 kg	200 lbs	100 kg
400/20 with outreach option	200 lbs	100 kg	—	—	—	—
Platform Dimensions (inch)						
Standard	2120/44.75 in	66/60/114 cm	2120/44.75 in	66/60/114 cm	2120/44.75 in	66/60/114 cm
Rated standard	2120/44.75 in	66/60/114 cm	2120/44.75 in	66/60/114 cm	2120/44.75 in	66/60/114 cm
Rated outreach	2020/40.75 in	60/51/114 cm	2020/40.75 in	60/51/114 cm	2020/40.75 in	60/51/114 cm
Standard height**	2020/40.75 in	140/111/0 cm	2020/40.75 in	140/111/0 cm	2020/40.75 in	140/111/0 cm

### Power

AC models	115 V / 30-40 hp or 220 V / 30-40 hp
DC models	12V / 110 V / 40 hp or 110/220 for worldwide model

### Weight\*\*\*\*

Standard beam						
400 (40/20)	1,200 lbs	500 kg	1,200 lbs	500 kg	—	—
400 (20/20A)	1,370 lbs	610 kg	1,300 lbs	590 kg	—	—
(2-20)	1,200 lbs	500 kg	1,200 lbs	500 kg	—	—
(2-20)	1,300 lbs	600 kg	1,300 lbs	600 kg	—	—
Standard beam with outreach option						
400 (20)	1,350 lbs	610 kg	—	—	—	—
400 (20)	1,450 lbs	650 kg	—	—	—	—
(2-20)	1,200 lbs	610 kg	—	—	—	—
(2-20)	1,450 lbs	650 kg	—	—	—	—
Wide beam						
400 (40/20A)	—	—	—	—	1,400 lbs	640 kg
400 (20/20A)	—	—	—	—	1,300 lbs	600 kg
(2-20)	—	—	—	—	1,400 lbs	640 kg
(2-20)	—	—	—	—	1,300 lbs	600 kg

### Standards Compliance

ANSI A92.5, CSA B354.1, EN 280, AS 1418.1-1

\* The stated maximum of working height adds 2' to the platform height, or 6' added to the extension height.

\*\* Working height platform lift not available with the standard option.

\*\*\* Capacity of platform may vary according to load with safety or weight limiting unit installed.

\*\*\*\* Weight will vary depending on options and/or specific standards.



