



Self-Propelled Articulating Booms

Z™-30/20N & Z™-30/20N RJ

Specifications

Results	Z-30/20N		Z-30/20N RJ	
Measurements	US	Metric	US	Metric
Working height maximum*	36 ft	11.0 m	26 ft 9 in	8.10 m
Pattern height maximum	36 ft	11.0 m	29 ft 8 in	8.60 m
Horizontal reach maximum	21 ft 9 in	6.6 m	20 ft 6 in	6.25 m
Up and over clearance maximum	13 ft 6 in	4.1 m	13 ft 9 in	4.16 m
▲ Pattern length	23 ft 6 in	7.2 m	23 ft 6 in	7.2 m
▲ Pattern width	19 ft 11 in	6.10 m	21 ft 10 in	6.60 m
Height - stowed	8 ft 2 in	2.50 m	8 ft 6 1/2 in	2.60 m
Length - stowed	10 ft 0 in	3.10 m	17 ft 5 in	5.25 m
Storage length	8 ft 10 1/2 in	3.28 m	7 ft 4 in	2.24 m
Storage height	11 ft 8 1/2 in	3.60 m	12 ft	3.60 m
Width	3 ft 7 1/2 in	1.10 m	2 ft 7 1/2 in	1.00 m
Heights	9 ft 2 1/2 in	3.00 m	9 ft 3 in	3.00 m
Ground clearance - obstacle	23 in	0.58 m	23 in	0.58 m

Productivity

Lift capacity	100 lb	227 kg	100 lb	227 kg
Pattern radius	100'		100'	
Vertical lift radius	130'		130'	
Horizontal lift radius	—		105'	
Turntable rotation	25° side-to-side		25° side-to-side	
Turning radius	10 ft		10 ft	
Drive speed - stowed	1.5 mph	0.8 km/h	2.5 mph	4.0 km/h
Drive speed - raised**	2.0 mph	1.1 km/h	3.0 mph	1.7 km/h
Ground slope - stowed***	30%		30%	
Turning radius - stowed	1 ft 8 1/2 in	0.52 m	1 ft 8 1/2 in	0.52 m
Turning radius - extended	10 ft 7 in	3.23 m	10 ft 7 in	3.23 m
Controls	24 VDC proportional		24 VDC proportional	
Time - cold start-up/arming	25 sec/17.5 in	58 sec/45.75 in	23 sec/17.5 in	58 sec/45.75 in

Power


Power source	48 VDC (regulated V battery)	48 VDC (regulated V battery)
Fuel source	980 Ah (capacity)	500 Ah (capacity)
Auxiliary power out	24 VDC	24 VDC
Hydraulic tank capacity	4 gal	15.1 L

Weights****

	14,250 lb	6,457 kg	14,250 lb	6,457 kg
--	-----------	----------	-----------	----------

Standards Compliance

ANSI/ASSE Z355.1, CSA B335.1, EN 320, AS/NZS 1418.10



*The radius measured from working height saddle to the center of rear axles. **10 sec. 444 lb ft in constant torque.
***The track's wheel load capacity. **The machine's total weight includes the boom, outriggers, rear tracks, fuel, auxiliaries, tools, and controls.



****Weight will vary depending on options, add-ons, country, and country.

www.genielift.com

Range Of Motion Z™-30/20N



Range Of Motion Z™-30/20N RJ





Self-Propelled Articulating Booms

Z-30/20N & Z-30/20N RJ

Features

Standard Features	Easy Configured To Meet Your Needs	Options & Accessories
Measurements	Platform	Productivity
Z-30/20N	Steel 3 ft. 10 in (1.17 m)	<ul style="list-style-type: none"> Platform swing gate
<ul style="list-style-type: none"> 35 ft. 0 in (11.14 m) working height 21 ft. 0 in (6.32 m) horizontal reach 12 ft. 0 in (3.66 m) up and over clearance Up to 1000 lbs (227 kg) lift capacity 	Job Options <ul style="list-style-type: none"> 4 ft. (1.22 m) job boom 4 ft. (1.22 m) horizontal rotating job boom 	<ul style="list-style-type: none"> Half-mast platform inserts with swing gate Platform top auxiliary rail Air line to platform Access protection package (Not available on RJ model)* Hostile environment package Fire-resistant hydraulic oil Biodegradable hydraulic oil Toot tray Flame retardant tube safety Tool cradle (part) Roofing basket Platform work lights Lockable platform control box cover
Z-30/20N RJ	Power	Power
<ul style="list-style-type: none"> 35 ft. 0 in (10.68 m) working height 20 ft. 0 in (6.25 m) horizontal reach 12 ft. 0 in (3.66 m) up and over clearance Up to 1000 lbs (227 kg) lift capacity 	<ul style="list-style-type: none"> 48 V DC power source 	<ul style="list-style-type: none"> AGM batteries EE ML363 Pro Protection rating Battery charge indicator (BCI) Low voltage interrupt with BCI 800 watt 120VAC power inverter
Productivity	Drive	
<ul style="list-style-type: none"> 4 ft (1.22 m) job boom with 13° working range Self-leveling platform Hydraulic platform rotation Fully proportional controls Thrust-locked steer Drive enable AC power cord to platform Horn Haul motor Tilt alarm Decelerate travel alarms 330° min-continuous turntable rotation Zero tailswing and limit arm swing 	<ul style="list-style-type: none"> 2WD Tire Solid rubber non-marking 	
Power	Platform	
<ul style="list-style-type: none"> 48 V DC keep cycle battery pack 24 V DC auxiliary power Universal 30A battery smart charger 		

* Maximum platform weight capacity is 441 lbs.

Genie United States:

10340 NE 19th Street
PO Box 970381
Redmond, Washington 98073-9708
Telephone +1 425) 279-1800
Toll Free in Canada +1 800-548-1800
Fax +1 425) 279-1808

Genie Europe:

Via Antignano
Strada Rossa
Giovanni XXIII, 88H
131
Telephone +44 20 470 04620
Fax +44 0115 852260
Email: info@EuropeGenie.com

Distributed By:

Genie, Inc., 2008. All rights reserved. Genie and Z are registered trademarks or trademarks of Genie, Inc. in the United States and/or other countries. All other trademarks and trade names are the property of their respective owners. *Maximum platform weight capacity is 441 lbs. Not all configurations available in all markets. All trademarks and trade names are the property of their respective owners. GENIE is a registered trademark of Genie, Inc. in the United States and other countries. GENIE is a registered trademark of Genie, Inc. in the United States and other countries.