

### Specifications

Model	GS-12		GS-16		GS-26	
Measurements	US	Metric	US	Metric	US	Metric
Working height*	17 ft 6 in	5.38 m	20 ft 12 in	6.35 m	26 ft 6 in	7.98 m
Platform height	11 ft 4 in	3.48 m	14 ft 12 in	4.52 m	19 ft 6 in	5.92 m
<b>▲▲</b> Platform dimensions (length x width)						
Working area	36 x 36.75 in	91 x 73 cm	36 x 36.75 in	91 x 73 cm	36 x 36.75 in	91 x 73 cm
Working top	36 x 36.75 in	1.1 x 73 cm	36 x 36.75 in	1.1 x 73 cm	36 x 36.75 in	1.1 x 73 cm
<b>▲</b> Height - stored	5 ft 2 in	1.57 m	6 ft 3 in	1.91 m	6 ft 6 in	1.98 m
<b>▲</b> Length - stored	4 ft 5 in	1.35 m	4 ft 5 in	1.35 m	4 ft 5 in	1.35 m
<b>▲</b> Width	2 ft 5.5 in	.75 m	2 ft 5.5 in	.75 m	2 ft 7.5 in	.81 m
<b>▲</b> Stored distance - center	2.5 in	.06 m	2.5 in	.06 m	2.5 in	.06 m

### Productivity

Lift capacity	500 lbs	227 kg	500 lbs	227 kg	500 lbs	227 kg
Drive speed - stored	2.2 mph	4.2 km/h	2.2 mph	4.2 km/h	2.2 mph	4.2 km/h
Drive speed - raised	2.2 mph	3.8 km/h	2.2 mph	3.8 km/h	2.2 mph	3.8 km/h
Stability**	30%		30%		30%	
Turning radius - inside	0 in		0 in		0 in	
Turning radius - outside	4 ft 7 in	1.42 m	4 ft 7 in	1.42 m	4 ft 7 in	1.42 m
Raise / lower speed	20 / 18 in/s	20 / 18 cm/s	21 / 18 in/s	21 / 18 cm/s	21 / 21 in/s	21 / 21 cm/s
Controls	24V DC proportional		24V DC proportional		24V DC proportional	
Tires - self-sealing	10 x 7 in	26 x 20 cm	10 x 7 in	26 x 20 cm	10 x 7 in	26 x 20 cm

### Power

Power source	24V (two 12V 20 Ah maintenance-free batteries)	
Hydraulic system capacity	2.2 gal	8.35 l

### Weight\*\*\*

Rated lift configuration	1,000 lbs	450 kg	1,200 lbs	540 kg	1,400 lbs	630 kg
Workload (W) configuration	1,200 lbs	540 kg	1,100 lbs	500 kg	1,400 lbs	630 kg

### Standards Compliance

ANSI A92.4, CSA B34.2, EN 280



\*The rated capacity of working height with 2 m platform height. U.S. with 6 ft in platform height.

\*\*Productivity applies to lifting air inside. See operator's manual for details regarding drive settings.

\*\*\*Weight includes handling in vehicle and/or storage conditions.

