

Specifications

Model	09-12		09-19		09-21	
Measurements	US	Metric	US	Metric	US	Metric
Working height ¹	11 ft 4 in	3.39 m	20 ft 8 in	6.33 m	25 ft 9 in	7.89 m
Platform height	11 ft 4 in	3.43 m	14 ft 8 in	4.52 m	19 ft 9 in	6.03 m
▲▲ Platform dimensions (length x width)						
Standard	75 x 29.5 in	39 x 25 in	75 x 29.5 in	39 x 25 in	75 x 29.5 in	39 x 25 in
Standard with catwalk	90 x 29.5 in	44 x 25 in	90 x 29.5 in	44 x 25 in	90 x 29.5 in	44 x 25 in
Standard AWP ²	21 x 20 in	39 x 38 in	21 x 20 in	39 x 38 in	21 x 20 in	39 x 38 in
Narrow AWP ³	25 x 22 in	36 x 31 in	25 x 22 in	36 x 31 in	25 x 22 in	36 x 31 in
▲ Height - stored	3 ft 2 in	1.37 m	3 ft 2 in	1.31 m	4 ft 4 in	1.90 m
▲ Length - stored	1 ft 5 in	1.31 m	4 ft 9 in	1.90 m	3 ft 5 in	1.31 m
▲ Width	3 ft 3 in	75 in	2 ft 5 in	75 in	3 ft 3 in	80 in
▲ Ground clearance - center	3.5 in	38 in	3.5 in	38 in	3.5 in	38 in

Productivity

Lift capacity	300 lbs	327 kg	300 lbs	327 kg	300 lbs	327 kg
Lift capacity - obstacle deck	250 lbs	113 kg	250 lbs	113 kg	250 lbs	113 kg
Drive speed - stored	2.5 mph	4.0 km/h	2.5 mph	4.0 km/h	2.5 mph	4.0 km/h
Drive speed - raised	0.5 mph	0.8 km/h	0.5 mph	0.8 km/h	0.5 mph	0.8 km/h
Stability ⁴	30%		30%		30%	
Tearing velocity - inside	200		200		200	
Tearing velocity - outside	4.8 / 7 in	1.22 m	4.8 / 7 in	1.22 m	4.8 / 7 in	1.22 m
Raise / lower speed	20 / 18 sec	20 / 18 sec	21 / 19 sec	21 / 19 sec	24 / 21 sec	24 / 21 sec
Controls	24V DC proportional		24V DC proportional		24V DC proportional	
Turn - with non-working	10 x 7 x 9 in	25 x 8 x 23 cm	10 x 3 x 9 in	25 x 8 x 23 cm	10 x 3 x 9 in	25 x 8 x 23 cm

Power

Power source	24V (See BT 220-48 battery)		24V (See BT 220-48 battery)		24V (See BT 220-48 battery)	
Hydraulic system capacity	2.2 gal	8.3 L	2.2 gal	8.3 L	2.2 gal	8.3 L

Weight⁵

	1,591 lbs	717 kg	2,180 lbs	984 kg	2,491 lbs	1,122 kg
--	-----------	--------	-----------	--------	-----------	----------

Standards Compliance

ANSI 50.1, CSA B364.2, CE Compliance, ISO 1418-10



¹ *Maximum dependent on extension height, 6ft 2 in on standard height, 2.5 mph at 6 ft on platform height.

² *Stability limited to 30% on level, 30% capacity limited for slopes regarding drive speed.

³ *Weight and size depending on option and/or country standards.

⁴ *See example for 2.2.

Features

Standard Features

Measurements

GR-12

- 17 ft 4 in (5.26 m) working height
- 11 ft 4 in (3.46 m) platform height
- Up to 500 lbs (227 kg) lift capacity

GR-15

- 20 ft 6 in (6.26 m) working height
- 14 ft 6 in (4.52 m) platform height
- Up to 500 lbs (227 kg) lift capacity

GR-20

- 25 ft 9 in (7.86 m) working height
- 19 ft 9 in (6.03 m) platform height
- Up to 350 lbs (159 kg) lift capacity

Productivity

- Work station tray (DR™ 12, DR™ 15 only)
- Standard platform with wiring rack
- Auxiliary platform (optional)
- Low 15.0 in (3.81 m) platform entry height
- Patented foot rest system
- Compact base 29.5 x 53 in (75.3 x 1.36 m) (DR™ 12, DR™ 15 only)
- Ground clearance 2.5 inches (64 mm)
- SmartLink control system
- Battery charge indicator
- On-board diagnostic system
- AC power to platform
- Dequat and lift alarm
- Zero-radius turning radius
- Dual wheel brakes
- Hydraulic brake release
- Pedal protection
- Hinged rear ABS covers for easy access to all major electrical and hydraulic components
- Tie-down attachment points
- Overhead cover attachment point
- Large front pockets access
- Non-marking cast tires

Power

- Automatic 25-amp battery charger

Options & Accessories

Productivity

- 20-in (5.1 m) extension platforms with sliding railing
- 20-in (5.1 m) extension platforms with gate
- Narrow AWP platform with gate*
- Dual latching cushions
- Motor alarm
- Flotation tube (entry)
- Automatic horn
- EEC Certification
- Biodegradable hydraulic oil
- Drive lockout while charging
- 10 ft retractable charging cord

Power

- 24V (four 6V 225 Ah) batteries
- 600 watt inverter (320-330V AC/50-60 Hz)
- AOM maintenance-free batteries

Tires

- Non-marking, solid tires



Genie United States:

13540 NE 15th Street
PO Box 97021
Redmond, Washington 98073-8750
Telephone: +1 (425) 861-1800
Toll Free: 1-800-4-A-GENIE or 1-800-531-1800
Fax: +1 (425) 863-5475

Genie Europe:

The Maltings
Silver Street
Quorn Leicestershire LE14
UK
Telephone: +44 (0) 1753 694222
Fax: +44 (0) 1753 694234
Email: genie@genie-europe.com

Distributed By:

Genie® and Runabout™ are trademarks of Genie Industries, Inc. All other trademarks are the property of their respective owners. Genie Industries, Inc. is not responsible for the accuracy of the information provided in this document. Genie Industries, Inc. reserves the right to change specifications without notice. © 2010 Genie Industries, Inc.