



Material Lifts

Genie® Lift™

Features

Standard Features

Measurements

GL™-4

- 5 ft. 11 in. (1.80 m) maximum lifting height
- Up to 330 lbs (150 kg) load capacity

GL-8

- 10 ft., 5 in. (3.05 m) maximum lifting height
- Up to 430 lbs (195 kg) load capacity

GL-10

- 11 ft. 5 in. (3.50 m) maximum lifting height
- Up to 380 lbs (170 kg) load capacity

GL-12

- 13 ft. 9.5 in. (4.20 m) maximum lifting height
- Up to 350 lbs (159 kg) load capacity

Productivity

- Portable and compact design
- Rolls easily through a single door
- Durable standard steel forks
- 8 in. (20 cm) non-marking rear wheels and 3 in. (8 cm) dual wheels front (standard casters (standard and straddle base only))
- 5 in. (12 cm) rear swivel casters with wide bases and 4 in. (10 cm) load front wheels (counterweight base only)
- Loads easily into a pickup truck for transporting
- Fold-down mechanism reduces damage during transport

Power

- Standard winch
- Reversible winch handle for easy storage

Options & Accessories

Productivity & Fork Options

- Boom
- Load platform
- Aluminum ladder (standard and straddle base only)
- Foot-rotate boom (standard and straddle base only)

Power

- Heavy duty winch
- Winch operates while ladder is in use or stored

Base Options

- Standard base (GL-5, -6 only)
- Straddle base (all units)
- Counterweight base (GL-4, -6, -10 only)

Wheel/Caster Options

Straddle and standard base

- 10 in. (25 cm) pneumatic rear wheels, 2.5 in. (6.3 cm) front swivel casters

Straddle base

- 4 point caster option A: 4 in. (10 cm) rear swivel casters, 2 in. (5 cm) front swivel casters
- 4 point caster option B: 5 in. (12 cm) rear swivel casters, 2.5 in. (6.3 cm) front swivel casters



Genie United States:

10540 NE 18th Street
PO Box 97023
Redmond, Washington 98074-9702
Telephone: +1 (425) 866-1933
Toll Free in US/Canada: +1 (800) 436-1933
Fax: +1 (425) 866-3475

Genie Europe:

The Maltings
Silver Street
Oxford OX1 2JE
UK
Telephone: +44 (0) 1865 564000
Fax: +44 (0) 1865 564204
Email: genie@genielift.com

Distributed By:

©2010 Genie Lift Corporation. All rights reserved. Genie Lift Corporation is not responsible for changes without previous notification. This document may contain drawings or other information that is not necessarily intended to be used in the design or construction of any product or system. Genie Lift Corporation is not responsible for any damage or injury that may occur as a result of the use of this document. Genie Lift Corporation is not responsible for any damage or injury that may occur as a result of the use of this document.

Specifications

Model	GS-4	GS-4	GS-4	GS-18	GS-12				
Measurements	US	Metric	US	Metric	US	Metric			
▲ Height - closed ¹	5'8.25 in	1.72 m	5'8.25 in	1.72 m	4'8.62 in	2.00 m	3'8.7 in	2.31 m	
	maximum fork down	4'8.25 in	1.26 m	4'8.25 in	1.26 m	4'8.10 in	3.01 m	12'8	3.66 m
	maximum fork up	5'8.11 in	1.60 m	11'8.2 in	3.59 m	11'8.8 in	3.66 m	15'8.8 in	4.20 m
Standard Base									
▲ Length - closed	1'8	30 in	1'8	30 in	-----	-----	-----	-----	
	springing	2'8.125 in	80 in	2'8.125 in	80 in	-----	-----	-----	
▲ Width - standard	2'8.18 in	80 in	2'8.18 in	80 in	-----	-----	-----	-----	
Weight - standard control options									
standard control options	117 lbs	51 kg	132 lbs	60 kg	-----	-----	-----	-----	
power-assist control options	117 lbs	51 kg	136 lbs	62 kg	-----	-----	-----	-----	
Double Base									
Length - closed	1'8.25 in	30 in	1'8.25 in	30 in	1'8.25 in	30 in	1'8.25 in	30 in	
	springing	3'8.7 in	1.00 m	3'8.7 in	1.00 m	3'8.7 in	1.00 m	3'8.7 in	1.00 m
Width - standard ²	2'8.25 in	73 in	2'8.25 in	73 in	2'8.25 in	73 in	2'8.25 in	73 in	
	maximum ³	3'8.25 in	1.12 m	3'8.25 in	1.12 m	3'8.25 in	1.12 m	3'8.25 in	1.12 m
maximum loads	3'8	81 in	3'8	81 in	3'8	81 in	3'8	81 in	
Weight - standard control options									
standard control options	128 lbs	57 kg	139 lbs	63 kg	149 lbs	68 kg	160 lbs	73 kg	
power-assist control options	132 lbs	59 kg	143 lbs	65 kg	163 lbs	74 kg	174 lbs	79 kg	
4-post control options A	131 lbs	60 kg	142 lbs	65 kg	162 lbs	74 kg	173 lbs	78 kg	
4-post control options B	135 lbs	61 kg	146 lbs	67 kg	166 lbs	75 kg	177 lbs	80 kg	
Swivelweight Base									
Length - springing	2'8.43 in	72 in	2'8.43 in	72 in	2'8.43 in	72 in	-----	-----	
Width - standard ²	2'8.25 in	73 in	2'8.25 in	73 in	2'8.25 in	73 in	-----	-----	
maximum ³	3'8.25 in	1.12 m	3'8.25 in	1.12 m	3'8.25 in	1.12 m	-----	-----	
maximum loads	3'8	81 in	3'8	81 in	3'8	81 in	-----	-----	
Weight - standard control options									
standard control options	302 lbs	138 kg	311 lbs	140 kg	321 lbs	146 kg	-----	-----	
Productivity									
Load height - minimum (fork down)	5.5 in	20 in	5.5 in	20 in	5.5 in	20 in	5.5 in	20 in	
Load clearance - center ^{1,1}	75 in	22 m	75 in	22 m	75 in	22 m	75 in	22 m	
Average stacks - standard wheel	11.25	30 in	11.50	30 in	11.25	30 in	11.25	30 in	
Fork length	1'8.125 in	31 in	1'8.125 in	31 in	1'8.125 in	31 in	1'8.125 in	31 in	
Fork width	1'8.83 in	32 in	1'8.83 in	32 in	1'8.83 in	32 in	1'8.83 in	32 in	
Load platform length	1'8.11 in	30 in	1'8.11 in	30 in	1'8.11 in	30 in	1'8.11 in	30 in	
Load platform width	1'8.12 in	30 in	1'8.12 in	30 in	1'8.12 in	30 in	1'8.12 in	30 in	
Load capacity at 12 in (30 cm) load center	602 lbs	271 kg	602 lbs	271 kg	602 lbs	271 kg	602 lbs	271 kg	
Riser length	25.19 in	51 cm	25.19 in	51 cm	25.19 in	51 cm	25.19 in	51 cm	
Riser attachment points	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	

Power

Power source: rechargeable standard battery

¹ The 12 in. protrusion from wheel center will add 1 in (25 mm) to these specifications.

² The maximum height will add 1 in (25 mm) to these specifications.

³ The 4-post control options B will add 1 in (25 mm) to these specifications.

⁴ Double base only.

