

Specifications

| Measurements | SLA™-8 | | SLA™-10 | | SLA™-15 | | SLA™-20 | | SLA™-25 | | |
|---------------------------------|--------------|---------|--------------|---------|--------------|---------|--------------|---------|-------------|---------|--|
| | US | Metric | US | Metric | US | Metric | US | Metric | US | Metric | |
| Working height | | | | | | | | | | | |
| standard folds - down | 4 ft 10.5 in | 1.49 m | 8 ft 9 in | 2.67 m | 14 ft 7.5 in | 4.50 m | 18 ft 8 in | 5.69 m | 24 ft 9 in | 7.42 m | |
| standard folds - up | 4 ft 7 in | 1.2 m | 11 ft 5.5 in | 3.49 m | 14 ft 11 in | 4.50 m | 21 ft 2.5 in | 6.46 m | 28 ft 3 in | 7.94 m | |
| adjustable folds - down | 4 ft 10.5 in | 1.49 m | 8 ft 9 in | 2.67 m | 14 ft 7.5 in | 4.50 m | 18 ft 8 in | 5.69 m | 24 ft 9 in | 7.42 m | |
| adjustable folds - up | 4 ft 7 in | 1.2 m | 11 ft 5.5 in | 3.49 m | 14 ft 11 in | 4.50 m | 21 ft 2.5 in | 6.46 m | 28 ft 3 in | 7.94 m | |
| flat folds | 4 ft 10.5 in | 1.49 m | 8 ft 9 in | 2.67 m | 14 ft 7.5 in | 4.50 m | 18 ft 8 in | 5.69 m | 24 ft 9 in | 7.42 m | |
| boom** | 4 ft 10.5 in | 1.49 m | 8 ft 9 in | 2.67 m | 14 ft 7.5 in | 4.50 m | 18 ft 8 in | 5.69 m | 24 ft 9 in | 7.42 m | |
| load platform** - folds down | 4 ft 10.5 in | 1.49 m | 8 ft 9 in | 2.67 m | 14 ft 7.5 in | 4.50 m | 18 ft 8 in | 5.69 m | 24 ft 9 in | 7.42 m | |
| load platform** - folds up | 4 ft 7 in | 1.2 m | 11 ft 5.5 in | 3.49 m | 14 ft 11 in | 4.50 m | 21 ft 2.5 in | 6.46 m | 28 ft 3 in | 7.94 m | |
| ▲ height - stored | 8 ft 6.5 in | 2.59 m | 8 ft 6.5 in | 2.59 m | 8 ft 6.5 in | 2.59 m | 8 ft 6.5 in | 2.59 m | 8 ft 6.5 in | 2.59 m | |
| ▲ length - stored | 29.9 in | 7.6 m | 29.9 in | 7.6 m | 29.9 in | 7.6 m | 29.9 in | 7.6 m | 29.9 in | 7.6 m | |
| ▲ length - stowed | 29.9 in | 7.6 m | 29.9 in | 7.6 m | 29.9 in | 7.6 m | 29.9 in | 7.6 m | 29.9 in | 7.6 m | |
| ▲ width - stored | 29.9 in | 7.6 m | 29.9 in | 7.6 m | 29.9 in | 7.6 m | 29.9 in | 7.6 m | 29.9 in | 7.6 m | |
| with stabilizer spread | 4 ft 11 in | 1.46 m | 4 ft 11 in | 1.46 m | 4 ft 11 in | 1.46 m | 4 ft 11 in | 1.46 m | 4 ft 11 in | 1.46 m | |
| Width - stabilizer base* | | | | | | | | | | | |
| extension | 2 ft 7.5 in | .80 m | 2 ft 7.5 in | .80 m | 2 ft 7.5 in | .80 m | — | — | — | — | |
| extension | 4 ft 10 in | 1.20 m | 4 ft 10 in | 1.20 m | 4 ft 10 in | 1.20 m | — | — | — | — | |
| extension folds | 4 ft 2 in | 1.20 m | 4 ft 2 in | 1.20 m | 4 ft 2 in | 1.20 m | — | — | — | — | |
| ▲ ground clearance - center | 2 in | 5.1 cm | 2 in | 5.1 cm | 2 in | 5.1 cm | 2 in | 5.1 cm | 2 in | 5.1 cm | |
| ▲ load height - extension | 6 in | 15.2 cm | 6 in | 15.2 cm | 6 in | 15.2 cm | 6 in | 15.2 cm | 6 in | 15.2 cm | |

Productivity

| Load capacity | 10 ft (3.0 m) load center | | 10 ft (3.0 m) load center | | 10 ft (3.0 m) load center | | 10 ft (3.0 m) load center | | 10 ft (3.0 m) load center | |
|----------------------------|---------------------------|--------|---------------------------|--------|---------------------------|--------|---------------------------|--------|---------------------------|--------|
| 10 ft (3.0 m) load center | 1,000 lbs | 444 kg | 1,000 lbs | 444 kg | 800 lbs | 360 kg | 800 lbs | 360 kg | 600 lbs | 269 kg |
| 20 ft (6.1 m) load center | 1,000 lbs | 444 kg | 1,000 lbs | 444 kg | 800 lbs | 360 kg | 800 lbs | 360 kg | 600 lbs | 269 kg |
| 40 ft (12.2 m) load center | 500 lbs | 222 kg | 400 lbs | 179 kg | 300 lbs | 133 kg | 300 lbs | 133 kg | 200 lbs | 89 kg |

Power

| Average cycle | 6.5 cycle/20 ft cycle | | 6.5 cycle/20 ft cycle | | 6.5 cycle/20 ft cycle | | 6.5 cycle/20 ft cycle | | 6.5 cycle/20 ft cycle | |
|----------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| standard cycle | 6.5 cycle/20 ft cycle | 6.5 cycle/20 ft cycle | 6.5 cycle/20 ft cycle | 6.5 cycle/20 ft cycle | 6.5 cycle/20 ft cycle | 6.5 cycle/20 ft cycle | 6.5 cycle/20 ft cycle | 6.5 cycle/20 ft cycle | 6.5 cycle/20 ft cycle | 6.5 cycle/20 ft cycle |

Weight

| | | | | | | | | | | |
|---------------|---------|--------|---------|--------|---------|--------|---------|--------|---------|--------|
| Standard | 310 lbs | 139 kg | 280 lbs | 124 kg | 320 lbs | 141 kg | 400 lbs | 181 kg | 460 lbs | 204 kg |
| Standard base | 200 lbs | 89 kg | 200 lbs | 89 kg | 200 lbs | 89 kg | — | — | — | — |

Load Handling Comments

| Measurements | US | Metric | Weight - US | Weight - Metric |
|---|-------------------|-----------------|-------------|-----------------|
| Standard folds (fold)** | 21'23.2 in | 6468.0 cm | 39.9 lbs | 18 kg |
| Adjustable folds (fold)** | 21'17.3-22'2.4 in | 6453-680.0 cm | 53.9 lbs | 24 kg |
| Flat extension attached (fold) (fold)** | 30'2.0 in | 9200.0 cm | 4.5 lbs | 2 kg |
| Flat extension attached (fold) (fold)** | 30'2.0 in | 9200.0 cm | 4.5 lbs | 2 kg |
| Flat folds (fold)** | 32'16.5-31.5 in | 9844-803.0 cm | 81.9 lbs | 36 kg |
| Boom (fold)** | 18'41.5-18.5 in | 5612.0-468.0 cm | 30.9 lbs | 14 kg |
| Load platform (fold)** | 21'52.2-21.0 in | 6567.0 cm | 31.9 lbs | 14 kg |



* Excludes dimensions.
 ** For use with standard fixed adjustable folds only.
 *** Measurements based on position of stabilizer.
 **** Capacity with 140 lbs.

Features

Standard Features

Measurements

SLA™-5

- 5 ft 7 in (2.0 m) maximum lifting height
- Up to 3,000 lbs (136 kg) load capacity

SLA-10

- 11 ft 5.5 in (3.49 m) maximum lifting height
- Up to 3,000 lbs (136 kg) load capacity

SLA-15

- 15 ft 4 in (4.68 m) maximum lifting height
- Up to 300 lbs (133 kg) load capacity

SLA-20

- 21 ft 2.5 in (6.46 m) maximum lifting height
- Up to 300 lbs (133 kg) load capacity

SLA-25

- 26 ft 5 in (7.94 m) maximum lifting height
- Up to 650 lbs (295 kg) load capacity

Productivity

- Heavy-duty design
- Patented telescoping mast system
- Captive stabilizer set (standard on SLA-20, -25)
- Rolls easily through single door in upright position
- Quick set up requires no tools
- Interchangeable load handling attachments
- Manueverable 4 in (10 cm) front casters and 5 in (13 cm) rear casters, with 4-way swivel locks and auto-brakes
- Compact design, legs fold up for easy storage
- Easy to load and unload on or off a vehicle for transport
- Fold-down bar secures mast assembly during transport
- Winch locks load in place

Power

- One speed manual winch

Options & Accessories

Productivity & Fork Options

- Adjustable forks
- Fork extensions
- Flat tires (SLA-5, -10, -15 only)
- Boom
- Pipe cradle (available aftermarket only)
- Level platform
- Captive stabilizer set (option on SLA-5, -10, -15)
- Mast locks

Power Options

- Two-speed manual winch (available aftermarket only)

Base Options

- Stable base (SLA-5, -10, -15 only)
- Stabilizer set (standard on SLA-20, -25, not available on truck-like base)

Caster & Brake Options

- Four transport wheel assembly



Genie United States:

10540 NE 18th Street
 P.O. Box 97023
 Redmond, Washington 98074-0723
 Telephone +1 (425) 866-1900
 Toll Free +1 (800) 474-6244 ext. 6000-6300-6500
 Fax +1 (425) 866-3475

Genie Europe:

The Maltings
 Silver Street
 Overhampton SO3 6BA
 UK
 Telephone +44 (0) 1703 594225
 Fax +44 (0) 1703 594234
 Email: info@genieeurope.com

Distributed By: