

Material Lifts

Superlift Contractor™

Specifications



Models	SJC-12™		SJC-18		SJC-24	
Measurements	US	Metric	US	Metric	US	Metric
Working height						
extended forks - forks down	13 8.2 ft	3.40 m	16 8.9 ft	5.12 m	22 9.3 ft	6.78 m
extended forks - forks up	12 9.11 ft	3.94 m	16 8.9 ft	5.61 m	24 8	7.32 m
adjustable forks - forks down	11 8.2 ft	3.40 m	14 8.9 ft	4.55 m	22 9.3 ft	6.78 m
adjustable forks - forks up	12 9.11 ft	3.94 m	16 8.9 ft	5.61 m	24 8	7.32 m
lower**	12 9.2 ft	3.70 m	11 8.9 ft	4.43 m	20 8.2 ft	7.03 m
▲ Height - stored	7 8.2 ft	2.38 m	7 8.2 ft	2.38 m	7 8.2 ft	2.38 m
▲ Length - stored	2 8.11 ft	.86 m	2 8.11 ft	.86 m	2 8.11 ft	.86 m
▲ - spreading	3 8.2 ft	1.60 m	4 8.1 ft	1.25 m	6 8.9 ft	2.04 m
▲ Width - stored*	2 8.13 ft	.81 m	2 8.2 ft	.80 m	2 8.2 ft	.81 m
- with dual wheels lowered	3 8.9 ft	1.09 m	3 8.9 ft	1.09 m	3 8.9 ft	1.09 m

Productivity

Load capacity						
14 ft (30 cm) load center	600 lbs	269 kg	600 lbs	269 kg	600 lbs	269 kg
24 ft (31 cm) load center	425 lbs	193 kg	425 lbs	193 kg	425 lbs	193 kg
42 ft (102 cm) load center	180 lbs	82 kg	180 lbs	73 kg	180 lbs	73 kg
▲ Ground clearance	2 ft	.61 m	2 ft	.58 m	2 ft	.58 m
Load height maximum	6 ft	1.8 m	6 ft	1.8 m	6 ft	1.8 m

Power

Average cycle						
standard wheel	8.0 cycle/hr	27.8 cycle/hr	8.0 cycle/hr	27.8 cycle/hr	8.0 cycle/hr	27.8 cycle/hr

Weight

220 lbs	102 kg	227 lbs	103 kg	347 lbs	157 kg
---------	--------	---------	--------	---------	--------

Load Handling Attachments

Measurements	US	Metric	Weight - US	Weight - Metric
Standard fork assembly (SJC)™	38/25/2.9 ft	11/800 cm	36.5 lbs	13 kg
Adjustable fork assembly (SJC)™	27.6/12-332.8 ft	10/30-100 cm	12.8 lbs	34 kg
Fork extension (standard loads) (SJC)™	30/27 ft	10/8 cm	4.5 lbs	2 kg
Beam (SJC)™	18-42/1.58 ft	48-127/15 cm	38.9 lbs	18 kg
Load platform (SJC)™†	38.3/202.5 ft	6/1500 cm	24.3 lbs	11 kg
Adjustable Fork Spacing	2 x 1.5 ft	2 x 4 cm	4.5 lbs	2 kg

* Overall dimensions
 ** Measured from ground to bottom of platform
 † Length/diameter/height

