

Features

Standard Features

Measurements

GS-2669 RT

- 32 ft (9.75 m) working height
- Up to 3,000 lbs (680 kg) lift capacity

GS-3369 RT

- 39 ft (11.90 m) working height
- Up to 3,000 lbs (680 kg) lift capacity

GS-4069 RT

- 45 ft (14.02 m) working height
- Up to 3,000 lbs (680 kg) lift capacity

Productivity

- 130 x 63 in (2.73 x 1.6m) steel frame platform with recessed aluminum deck
- 50 in (1.27 m) extension deck (ANSI)
- Folding guardrails
- Proportional lift and drive
- AC power to platform
- Full-height swing gate
- 4WD
- Front rotating axle
- Positive traction control
- Four-wheel braking
- Swing-out engine tray
- Foam-filled rough-terrain tires (12 x 26)
- 12" tire center with audible alarm
- Deceleration alarm
- Horn
- Hour meter

Options & Accessories

Productivity

- Automatic leveling hydraulic outdrives
- Air-ride to platform
- Foam-filled non-marking rough-terrain tires 12 x 26 in (30 x 65 cm)
- Dual-latching deck gate
- Motor alarm
- Bi-directional hydraulic lift

Power Options

- Kubota gas/LPG 28 hp (21.7 kW)
- Kubota diesel 24.5 hp (18.5 kW)
- Perkins diesel 28 hp (19.5 kW)
- AC, 3000-Watt generator (110 V/50 Hz) or 240 V/50 Hz
- Diesel Scrubber (Perkins)
- Cold weather package
- Hydraulic oil cooler



Genie United States:

11540 NE 18th Street
 P.O. Box 97021
 Redmond, Washington 98074-9701
 Telephone: +1 (425) 861-1932
 Toll Free in the US/Canada: +1 (800) 451-1932
 Fax: +1 (425) 862-9475

Genie Europe:

The Maltings
 Silver Street
 Overhampton, Hants RG10 0BA
 UK
 Telephone: +44 (0)1475 366222
 Fax: +44 (0)1475 366234
 Email: info@genie-europe.com

Distributed By:

Self-Propelled Scissor Lifts

GS[®]-2669 RT, GS-3369 RT, GS-4069 RT

Specifications



Units	GS-2669 RT		GS-3369 RT		GS-4069 RT	
Measurements	US	Metric	US	Metric	US	Metric
Working height - platform ¹	32 ft	9.75 m	39 ft	11.9 m	46 ft	14.02 m
Platform height - maximum	28 ft	7.9 m	32 ft 6 in	9.96 m	40 ft	12.2 m
Drive height	28 ft	7.9 m	32 ft 6 in	9.96 m	40 ft	12.2 m
Platform height - standard	18 ft 10 in	5.71 m	18 ft 10 in	5.71 m	18 ft 9 in	5.65 m
Platform height - standard	18 ft 2 in	5.54 m	18 ft 2 in	5.54 m	18 ft 2 in	5.54 m
	retracted		14 ft 2 in	4.33 m	14 ft 2 in	4.33 m
Retract platform - maximum drive	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m
Platform width - standard	5 ft 3 in	1.6 m	5 ft 3 in	1.6 m	5 ft 3 in	1.6 m
Forward length	6 ft	1.83 m	6 ft	1.83 m	6 ft	1.83 m
Height - standard ²	6 ft 6 in	2.00 m	6 ft 6 in	2.00 m	6 ft	1.83 m
	into forward		6 ft 3 in	1.92 m	6 ft 10 in	2.08 m
Length - standard	12 ft 3 in	3.72 m	10 ft 2 in	3.12 m	10 ft 3 in	3.12 m
	platform extended		11 ft 3 in	3.43 m	11 ft 3 in	3.43 m
	with outriggers		12 ft 4 in	3.76 m	12 ft 4 in	3.76 m
Width	2 ft 9 in	0.79 m	2 ft 9 in	0.79 m	2 ft 9 in	0.79 m
Wheelbase	7 ft 0 in	2.13 m	7 ft 0 in	2.13 m	7 ft 0 in	2.13 m
Ground clearance - main	5 ft 6 in	1.68 m	5 ft 6 in	1.68 m	5 ft 6 in	1.68 m

Productivity

Maximum platform capacity ³	2	4	5			
Lift capacity	1,000 lbs	800 kg	1,000 lbs	450 kg	800 lbs	360 kg
Maximum deck capacity	300 lbs	136 kg	300 lbs	136 kg	300 lbs	136 kg
Drive speed - standard	0.3 mph	0.4 km/h	0.3 mph	0.4 km/h	0.3 mph	0.4 km/h
Drive speed - optional	0.3 mph	0.4 km/h	0.3 mph	0.4 km/h	0.3 mph	0.4 km/h
Stability - standard ⁴	40%		30%		30%	
Maximum outrigger leveling	front/back up/down side to side 11.7°					
Turning radius - width	23 ft	7.01 m	23 ft	7.01 m	23 ft	7.01 m
Turning radius - height	101.2 ft	30.8 m	100.2 ft	30.5 m	101.2 ft	30.8 m
Maximum speed	30 ft/min		420 ft/min		300 ft/min	
Steering	propelled					
Drive	four wheel					
Drive - rough terrain	12x16 in		16x16 in		12x16 in	16x16 in

Power

Power source	battery 2P-817 gal/LPG 20 gal battery 2-005 Diesel 24.2 gal Perkins 400D-11 Diesel 26 gal					
Fuel tank capacity	10 gal	37.9 L	10 gal	37.9 L	10 gal	37.9 L
Automatic refuel capacity	10 gal	40.1 L	10 gal	40.1 L	10 gal	40.1 L

Weight⁵

	1,200 lbs	539 kg	1,800 lbs	816 kg	10,245 lbs	4,647 kg
with outriggers	8,100 lbs	3,684 kg	8,300 lbs	3,762 kg	11,115 lbs	5,040 kg

Standards Compliance

ANSI A92.6, CSA B334.2, CE Compliance, AS 1418.10

¹ The maximum height of working height plus 2 ft to platform height is 6 ft with 4 ft to platform height.
² Based on 10' base, deduct 2' with 4 ft to top and maximum height.
³ OSHA requires 12" (305 mm) and 18" (457 mm) toe boards for scissor lifts.
⁴ OSHA requires 40% on rough terrain, 30% on smooth. The weight fluctuates on the weight of platform-mounted or hydraulic lift-mounted.
⁵ Weight varies depending on option and accessories installed.