



Self-Propelled Scissor Lifts

GS™-2032, GS-2632 & GS-3232

Features

Standard Features

Measurements

- GS-2032: 26 ft (8.0 m) working height
- Up to 200 lbs (90.7 kg) lift capacity
- GS-2632:
- 36 ft (10.9 m) working height
- Up to 300 lbs (136.1 kg) lift capacity
- GS-3232:
- 36 ft (11.7 m) working height
- Up to 300 lbs (136.1 kg) lift capacity

Productivity

- GS + 32 in (0.8 m) lift platform
- 36 in (31 m) extension deck
- Fixed rate with short cycle time (standard on all GS, GS™-2032, GS™-2632)
- Folding rate with full height swing gate (standard on all GS, GS™-2032, GS™-2632)
- Automatic leveling outriggers (GS™-2632 only)
- Dual front-wheel drive
- Universal 20 amp smart charger
- User-replaced charge receptacle
- Proportional 2-speed lift and drive
- Platform control with battery charge indicator and diagnostic display
- On-board diagnostic system
- AC power to platform
- Lanyard attachment points
- Manual platform braking valve
- Emergency stop of both platform and ground controls
- Four-wheel multiple disc brakes
- Front-wheel hydraulic dynamic braking
- Brake release
- Swing-out component tray
- Solid non-marking tires
- Polyurethane guards
- Tilt lever contact with audible alarm
- Diesel start
- Electronic horn
- Four mats

Power

- 24 V DC (use 8 V 250 Ah battery)

Options & Accessories

Productivity Options

- Folding rate with half-height swing gate (GS™-3232)
- Platform swing gate, full-height (GS™-3232)
- Air-line to platform
- Dual leveling indicator
- Motion alarm
- Electronic horn
- Bi-directional hydraulic lift

Power Options

- Power inverter (120 V/60 Hz)
- EE rating
- eCOM maintenance-free batteries



Genie United States:

11540 Hwy 70 West
PO Box 377381
Memphis, Tennessee 38137-0001
Telephone: +1 (800) 888-1800
Fax: +1 (901) 682-1800
Fax: +1 (901) 682-3475

Genie Europe:

7790 Ardingly
Arling Road
Gatwick RH6 0BB
UK
Telephone: +44 20 479 584222
Fax: +44 20 479 584224
Email: Europe@GenieLift.com

Distributed By:

Genie is a registered trademark of Genie Industries Inc. and is used by other companies to denote products or services. The listing under vendor information in this document are for distribution purposes only. Refer to the manufacturer's catalog for detailed information on their products. All trademarks and service marks are the property of their respective owners. The Genie logo is a registered trademark of Genie Industries Inc. and is used by other companies to denote products or services. The listing under vendor information in this document are for distribution purposes only. Refer to the manufacturer's catalog for detailed information on their products.

Self-Propelled Scissor Lifts

GS™-2032, GS-2632 & GS-3232

Specifications

Model	GS-2032	GS-2632	GS-3232			
Measurements	US	Metric	US	Metric	US	Metric
Working height - maximum	39 ft	11.9 m	52 ft	15.8 m	59 ft	18.0 m
▲ Platform height - maximum	20 ft	6.0 m	26 ft	7.9 m	32 ft	9.2 m
▲ Platform height - standard	17 ft 4 1/2 in	5.2 m	22 ft 10 in	7.0 m	28 ft 7 1/2 in	8.7 m
▲ Platform height - options	17 ft 4 1/2 in	5.2 m	22 ft 10 in	7.0 m	28 ft 7 1/2 in	8.7 m
Ground height - standard	10 ft 8 1/2 in	3.25 m	15 ft 7 1/2 in	4.8 m	19 ft 9 1/2 in	6.0 m
Side-set platform extension dock	3 ft	0.9 m	3 ft	0.9 m	3 ft	0.9 m
▲ Platform width - standard	2 ft 8 1/2 in	85 cm	2 ft 8 1/2 in	85 cm	2 ft 8 1/2 in	85 cm
Ground height - fixed only	3 ft 3 1/2 in	1.0 m				
Ground slope rate (G)	3 ft 7 1/2 in	1.12 m	3 ft 7 1/2 in	1.12 m	3 ft 7 1/2 in	1.12 m
Forward height	6 ft	1.8 m	8 ft	2.4 m	8 ft	2.4 m
▲ Height - standard						
Total height	9 ft 8 1/2 in	3.0 m				
Working platform height (G)	20 ft	6.0 m	26 ft	7.9 m	32 ft	9.2 m
Platform height - standard	17 ft 4 1/2 in	5.2 m	22 ft 10 in	7.0 m	28 ft 7 1/2 in	8.7 m
▲ Length - standard	9 ft	2.7 m	9 ft	2.7 m	9 ft	2.7 m
Length - extended	10 ft 7 1/2 in	3.25 m	11 ft 7 1/2 in	3.55 m	12 ft 7 1/2 in	3.85 m
Width	2 ft 8 1/2 in	85 cm	2 ft 8 1/2 in	85 cm	2 ft 8 1/2 in	85 cm
Ground clearance - center	1 ft 10 in	55 cm	2 ft 4 in	70 cm	2 ft 4 in	70 cm
▲ With folded platform deployed, 2 ft 8 1/2 in	22 ft	6.7 m	22 ft	6.7 m	22 ft	6.7 m

Productivity

Working platform capacity**	1	1	1	1	1	1
Lift capacity	600 lbs	272 kg	600 lbs	272 kg	600 lbs	272 kg
Extension dock capacity	250 lbs	113 kg	250 lbs	113 kg	250 lbs	113 kg
Drive height	5 ft height		10 ft height		12 ft	0.11 m
Drive speed - closed	12 mph	19 km/h	22 mph	35 km/h	22 mph	35 km/h
Drive speed - rated	11 mph	17 km/h	21 mph	33 km/h	21 mph	33 km/h
Steerability - closed***	90%	90%	90%	90%	90%	90%
Maximum outrigger leveling						
Front to back	—	—	—	—	—	—
Maximum outrigger leveling:						
width to side	—	—	—	—	—	—
Turning radius - inside	20 ft	6.0 m	20 ft	6.0 m	20 ft	6.0 m
Turning radius - outside	7 ft	2.13 m	7 ft	2.13 m	7 ft	2.13 m
Ride / travel speed	30 / 34 mph	48 / 54 km/h	30 / 40 mph	48 / 64 km/h	30 / 40 mph	48 / 64 km/h
Outriggers/propellers	proportional	proportional	proportional	proportional	proportional	proportional
Drive	front front wheel					
Multiple dock features	fold rear wheel					
Tires - solid non-marking	10x6.50-16	10x6.50-16	10x6.50-16	10x6.50-16	10x6.50-16	10x6.50-16

Power

Power source	30 V DC	24 V DC	24 V DC			
	(four 48 V 12 Ah batteries)	(four 48 V 16 Ah batteries)	(four 48 V 20 Ah batteries)			
Hydraulic system capacity	3.75 gal	14.2 L	3.75 gal	14.2 L	3.75 gal	14.2 L

Weights*

AWL (USA)	1,314 lbs	597 kg	4,013 lbs	1,819 kg	5,180 lbs	2,302 kg
SL (AUS)	4,231 lbs	1,915 kg	4,213 lbs	1,904 kg	5,180 lbs	2,302 kg

Standards Compliance: ANSI/ASSE A.17A-2014/2, OSHA 1910.21, CSA Z333.1-13

*The maximum capacity of working height (G) is 10 ft (3.0 m) above ground level.

**Outriggers - 10 ft (3.0 m) wide and 10 ft (3.0 m) deep. Outriggers must be deployed independently.

***Steerability depends on steering or chassis. See operator's manual for details regarding steerability.

****Weight capacity depending on chassis profile - see operator's manual.