



Self-Propelled Scissor Lifts

GS[®]-2669 DC, GS-3369 DC, GS-4069 DC

Features

Standard Features

Measurements

GS-2669 DC

- 32 ft (9.75 m) working height
- Up to 1,000 lbs (454 kg) lift capacity

GS-3369 DC

- 39 ft (11.90 m) working height
- Up to 1,000 lbs (454 kg) lift capacity

GS-4069 DC

- 45 ft (14.02 m) working height
- Up to 800 lbs (363 kg) lift capacity

Productivity

- AC sealed drive motor
- 48V DC light SV battery
- 110 x 50 in (2.79 x 1.27) m steel frame platform with replaceable aluminum deck
- 60 in (1.52 m) extension deck (4069)
- Forking guards
- 2 speed lift and drive
- AC power to platform
- Full height swing gate
- 2940
- Front oscillating axle
- Positive traction control
- Regenerative braking
- Non-marking rough terrain tires 12 x 26 in (30 x 66 cm)
- Tilt level sensor with audible alarm
- Deceleration alarm
- Horn

Options & Accessories

Productivity

- Automatic leveling hydraulic outdrives
- Airline to platform
- High flotation, foam filled tires
- 3 IS AV battery (standard on GS-4069DC)
- Power inverter (520 V / 50 Hz)
- Dual battery breakers
- Motor alarm



Genie United States:

11540 NE 19th Street
 PO Box 97033
 Redmond, Washington 98074-9750
 Telephone +1 (425) 866-1933
 Toll Free in the US/Canada +1 (800) 451-1933
 Fax +1 (425) 866-3475

Genie Europe:

The Maltings
 Silver Street
 Overhamford, Essex
 UK
 Telephone +44 (0)1473 884225
 Fax +44 (0)1473 884234
 Email: genie@genie-europe.com

Distributed By:

Genie, the Genie logo, GS, and self-propelled are trademarks owned by Genie Lift Corporation. All other trademarks, trade names and product names are the property of their respective owners. Genie Lift Corporation is not responsible for any errors or omissions in this document. Genie Lift Corporation is not responsible for any damage to property or injury to persons or animals resulting from the use of this equipment. Genie Lift Corporation is not responsible for any damage to property or injury to persons or animals resulting from the use of this equipment. Genie Lift Corporation is not responsible for any damage to property or injury to persons or animals resulting from the use of this equipment. Genie Lift Corporation is not responsible for any damage to property or injury to persons or animals resulting from the use of this equipment.



Self-Propelled Scissor Lifts

GS[®]-2669 DC, GS-3369 DC, GS-4069 DC

Specifications



| Units | GS-2669 DC | | GS-3369 DC | | GS-4069 DC | |
|------------------------------|--------------|--------|--------------|--------|--------------|---------|
| Measurements | US | Metric | US | Metric | US | Metric |
| Working height - standard* | 32 ft | 9.75 m | 39 ft | 11.9 m | 46 ft | 14.02 m |
| ▲ Platform height - maximum | 28 ft | 7.9 m | 32 ft 9 in | 9.99 m | 40 ft | 12.2 m |
| Drive height | 28 ft | 7.9 m | 32 ft 8 in | 9.95 m | 40 ft | 12.2 m |
| ▲ Platform height - standard | 8 ft 10 in | 2.7 m | 8 ft 10 in | 2.7 m | 8 ft 9 in | 2.65 m |
| ▲ Platform height - outside | 8 ft 2 in | 2.5 m | 8 ft 2 in | 2.5 m | 8 ft 2 in | 2.5 m |
| | retracted | | | | | |
| ▲ Platform height - outside | 11 ft 2 in | 3.4 m | 11 ft 2 in | 3.4 m | 11 ft 2 in | 3.4 m |
| ▲ Platform height - inside | 8 ft | 2.4 m | 8 ft | 2.4 m | 8 ft | 2.4 m |
| ▲ Platform width - outside | 5 ft 3 in | 1.6 m | 5 ft 3 in | 1.6 m | 5 ft 3 in | 1.6 m |
| ▲ Platform width - inside | 4 ft | 1.2 m | 4 ft | 1.2 m | 4 ft | 1.2 m |
| ▲ Height - standard | 8 ft 6 in | 2.59 m | 8 ft 6 in | 2.59 m | 9 ft | 2.74 m |
| ▲ Height - standard | with ladders | | | | | |
| | 8 ft 3.5 in | 2.52 m | 8 ft 3.5 in | 2.52 m | 8 ft 10 in | 2.68 m |
| ▲ Length - standard | 12 ft 3 in | 3.72 m | 10 ft 2 in | 3.12 m | 10 ft 3 in | 3.12 m |
| | with ladders | | | | | |
| | 11 ft 8.5 in | 3.5 m | 11 ft 8.5 in | 3.5 m | 11 ft 8.5 in | 3.5 m |
| | 12 ft 4 in | 3.75 m | 12 ft 4 in | 3.75 m | 12 ft 4 in | 3.75 m |
| ▲ Width | 2 ft 9 in | 0.75 m | 2 ft 9 in | 0.75 m | 2 ft 9 in | 0.75 m |
| ▲ Wheelbase | 7 ft 6 in | 2.30 m | 7 ft 6 in | 2.30 m | 7 ft 6 in | 2.30 m |
| ▲ Ground clearance - inside | 9.5 in | 0.24 m | 9.5 in | 0.24 m | 9.5 in | 0.24 m |

Productivity

| | 2 | 4 | 5 |
|------------------------------|-------------|-----------|-----------|
| Maximum platform capacity** | | | |
| US capacity | 1,000 lbs | 400 kg | 800 lbs |
| Metric capacity | 450 kg | 180 kg | 360 kg |
| Extension deck capacity | 300 lbs | 136 kg | 300 lbs |
| Metric capacity | 136 kg | 136 kg | 136 kg |
| Drive speed - standard | 4.5 mph | 7.2 km/h | 4.5 mph |
| Metric speed | 7.2 km/h | 7.2 km/h | 7.2 km/h |
| Drive speed - rated | 0.3 mph | 0.5 km/h | 0.3 mph |
| Metric speed | 0.5 km/h | 0.5 km/h | 0.5 km/h |
| Stability - speed standard** | 30% | 30% | 30% |
| - deceleration standard** | 15% | 15% | 15% |
| Maximum outgrip loading | | | |
| back-to-back | 5.7" (4.2") | | |
| side-to-side | 11.7" | | |
| Turning radius - inside | 87 in | 2.11 m | 87 in |
| Metric radius | 2.11 m | 2.11 m | 2.11 m |
| Turning radius - outside | 181.2 in | 4.6 m | 181.2 in |
| Metric radius | 4.6 m | 4.6 m | 4.6 m |
| Acceleration speed | 30/25 sec | 30/25 sec | 31/25 sec |
| Max-mastow time - mast down | 12/26 sec | 35/40 sec | 12/26 sec |
| Metric time | 35/40 sec | 35/40 sec | 35/40 sec |

Power

| | | | |
|---------------------------|---|---|---|
| Power source | 48V DC (single 24 battery, 225 Ah capacity) | 48V DC (single 24 battery, 225 Ah capacity) | 48V DC (single 24 battery, 215 Ah capacity) |
| Hydraulic system capacity | 18 gal | 66.1 L | 18 gal |
| | 66.1 L | 66.1 L | 66.1 L |

Weight****

| | | | | | | |
|--|-----------|----------|-----------|----------|------------|----------|
| | 7,800 lbs | 3,535 kg | 7,940 lbs | 3,575 kg | 10,850 lbs | 4,899 kg |
|--|-----------|----------|-----------|----------|------------|----------|

Standards Compliance: ANSI 462.0, CSA B354-2, CE Compliance, AS 1108.10

* The maximum height of working height with 2 or 4 persons height is 6.5 m (21 ft 6 in) platform height.

** 20 mph requires 10" (254 mm) and 20" (508 mm) wheel for use on a 2 person platform capacity when used on ladders.

*** Deceleration applies to driving or stopping. Stabilities may vary depending on the length of platform extended or retracted. See user's manual for details regarding proper use.

**** Weight varies depending on options and factory standards.