

GENERAL PRESSURE GAUGE



Norex general service pressure gauges are designed for non-corrosive environment. Water, air, oil or gas services are the most common applications which do not have high viscosity and do not crystallize. It's suitable for pneumatic, filters, pressure regulators, hydraulic, compressors and etc.

Standard Specification

Dial Size

2" (50mm) / 2½" (63mm) / 4" (100mm)

Scale Range

2" (50mm)	: 0 ~ 3 bar (45psi)
	: 0 ~ 10 bar (150psi)
	: 0 ~ 20 bar (300psi)
2½" (63mm)	: 0 ~ 7 bar (100psi)
	: 0 ~ 10 bar (150psi)
4" (100mm)	: 0 ~ 4 bar (60psi)
	: 0 ~ 7 bar (100psi)
	: 0 ~ 10 bar (150psi)
	: 0 ~ 16 bar (230psi)
	: 0 ~ 20 bar (300psi)
	: 0 ~ 28 bar (400psi)
	: 0 ~ 40 bar (600psi)
	: 0 ~ 70 bar (1000psi)

Accuracy

± 1.5% of Full Scale

Material

Case & Cover : Black Finished Steel
 Window : Glass
 Movement : Brass
 Element Tube : Brass
 Connection : Brass

Connection

2½" (63mm): 1/4" BSPT Bottom
 4" (100mm) : 3/8" BSPT Bottom

Working Temperature

Ambient : -20 ~ 60°C
 Process : -20 ~ 60°C

Mounting Type

(A) : Bottom connection
 (B) : Back connection