



MILD STEEL ELECTRODE

BLUEARC 6010

AWS A5.1 : E6010
EN ISO 2560-A : E 38 2 C 21

Diameter	Standard Package	Standard Length	Standard Pallet	List Price	Net Price
2.6mm	5kg/20kg	350mm	1000kg		
3.2mm	5kg/20kg	350mm	1000kg		
4.0mm	5kg/20kg	350mm	1000kg		
4.8mm	5kg/20kg	350mm	1000kg		

Applications

High cellulose all-position designed for deep penetration on root and filler layers of butt or fillet welding. It is used for welding mild steel in pipeline, storage tank, pressure vessels and heavy construction work.

BLUEARC 7010

AWS A5.5 : E7010
EN ISO 2560-A : E 42 2 Z C 21

Diameter	Standard Package	Standard Length	Standard Pallet	List Price	Net Price
2.6mm	5kg/20kg	350mm	1000kg		
3.2mm	5kg/20kg	350mm	1000kg		
4.0mm	5kg/20kg	350mm	1000kg		

Applications

High cellulose all-position designed for deep penetration on root and filler layers of butt or fillet welding. It is used for welding mild steel in pipeline, storage tank, pressure vessels and heavy construction work.

Designed for welding long distance pipe lines. Also designed for use on carbon moly piping used in high pressure, high temperature steam service, structure or plates where the molybdenum content it appro 0.50%.