

LYE DUCTILE IRON UNIVERSAL JOINTS



**STRAIGHT
COUPLING**

**FLANGE
ADAPTOR**



LYE MANUFACTURING SDN. BHD. (32836-H)

Brand	LYE
Sizes Available	80mm - 300mm
Material	Ductile Iron (S.G.)
Max. Working Pressure	16 Bars
Setting Gap	20mm - 30mm
Angular Deflection	6 Degrees
Bolts and Nuts	Hot-Dip Galvanised
Coating	Epoxy (Blue)
Rubber Gasket	EPDM Rubber

LYE DUCTILE IRON STRAIGHT COUPLING



NORMAL DIAMETER	NORMAL DIAMETER RANGE (MM)	TYPE OF PIPES
3" / 80mm	89 ~ 99	uPVC, DI, CI, AC, Steel
4" / 100mm	114 ~ 126	uPVC, DI, CI, AC, Steel
6" / 150mm	168 ~ 179	uPVC, DI, CI, AC, Steel
8" / 200mm	219 ~ 234	uPVC, DI, CI, AC, Steel
10" / 250mm	273 ~ 286	uPVC, DI, CI, AC, Steel
12" / 300mm	324 ~ 334	uPVC, DI, CI, AC, Steel

LYE DUCTILE IRON FLANGE ADAPTOR



Brand	LYE
Sizes Available	80mm - 300mm
Material	Ductile Iron (S.G.)
Max. Working Pressure	16 Bars
Setting Gap	10mm - 35mm
Angular Deflection	6 Degrees
Bolts and Nuts	Hot-Dip Galvanised
Coating	Epoxy (Blue)
Rubber Gasket	EPDM Rubber

NORMAL DIAMETER	NORMAL DIAMETER RANGE (MM)	TYPE OF PIPES
3" / 80mm	89 ~ 99	uPVC, DI, CI, AC, Steel
4" / 100mm	114 ~ 126	uPVC, DI, CI, AC, Steel
6" / 150mm	168 ~ 179	uPVC, DI, CI, AC, Steel
8" / 200mm	219 ~ 234	uPVC, DI, CI, AC, Steel
10" / 250mm	273 ~ 286	uPVC, DI, CI, AC, Steel
12" / 300mm	324 ~ 334	uPVC, DI, CI, AC, Steel

Please Note: Technical data provided is indicative only and may be subject to change without notice