Certification No. **ICS 000042** Serial No.: **000040** 

## PLATINUM SHAUFFMANTZ VERITAS

NTERNATIONAL

## Certification

Platinum Shauffmantz Veritas hereby certifies that

## TFC ASIA SDN BHD

Lot 2800, Jalan Sungai Kelkati 32/148, Jalan Sri Gambut Off Jalan Kebun, Seksyen 32, 40460 Shah Alam, Selangor Darul Ehsan, Malaysia.

has complied with the requirements specified in the

BS EN 124-2: 2015

Part 2: Gully Tops and Manhole Tops Made of Cast Iron.

under the Product Certification Scheme Type 5 a license to use the Certification Mark on

**GULLY TOPS FOR VEHICULAR AND PEDESTRIAN AREAS.** 

Reg. No.: MASIBS 101039

Initial Assessment Date : 24<sup>th</sup> November 2022 Certificate Date : 19<sup>th</sup> December 2022

Expiry Date : 18th December 2025



"This certificate issued by PLATINUM SHAUFFMANTZ VERITAS against defined criteria and in cognisance of ISO 17065:2012 'Conformity Assessment – Requirements for bodies certifying products, processes and service'. Notes: (I) Conformity Assessment-Fundamentals of product certification and guideline for Product Certification Scheme Type 5."



**Certification Director** 





VWW, STICOITTICITE.C.

14 45, 7th Floor, Block 1, Jalan Tipiu 13/50, worldwide Bu
1-403/15 Sheh Alam Selangar Darul Ehsan, Malays
1-403/15 Shep 1-403-51 B8793



## **SCHEDULE**

Manufacturer name and location:

DVC MANUFACTURING SDN BHD

No 513 Susur Lencongan Timur Kanan Kawasan Perindustrian Cendana 2, 08000 Sg. Petani, Kedah Darul Aman, Malaysia.

Brand	Model	Description /Type	Series / Rating	Size	Remark
DVC	C250	TYPE: MANHOLE COVERS & FRAMES MATERIAL: DUCTILE IRON; MATERIAL GRADE: 500/7	GROUP: 3	FRAME SIZE (MM): 710 X 710 X 50 CLEAR OPENING DIAMETER (MM): 600 MINIMUM DEPTH INSERTION (MM): 40	-
DVC	C250	TYPE: MANHOLE COVERS & FRAMES MATERIAL: DUCTILE IRON; MATERIAL GRADE: 500/7	GROUP: 3	FRAME SIZE (MM): 840 X 840 X 50 CLEAR OPENING DIAMETER (MM): 600 MINIMUM DEPTH INSERTION (MM): 40	
DVC	D400	TYPE: MANHOLE COVERS & FRAMES MATERIAL: DUCTILE IRON; MATERIAL GRADE: 500/7	GROUP: 4	FRAME SIZE (MM): 840 X 840 X 100 CLEAR OPENING DIAMETER (MM): 600 MINIMUM DEPTH INSERTION (MM): 50	

-----END OF PAGE------