

VOC in Gas Analyzer

MS1800



MS1800

VOC in Gas Analyzer

Monitoring VOCs in industrial processes

The MS1800 is a **VOC and Hydrocarbon Gas Concentration Analyzer**.

It is designed to monitor VOC gases in **industrial processes** and applications as well as in **environmental monitoring** applications.

The instrument senses gases or volatiles providing a measurement system with very **low maintenance requirements**.

Taking a measurement every 2 seconds, the MS1800 is accurate at concentrations from 1 to 500 ppm, dependent upon the target gas, and its **wide dynamic range** allows it to be used in a variety of environments.

A **user-programmable** concentration alarm threshold can be set, connecting to a relay output and an indicator on the front panel. This allows connection to other peripheral equipment such as isolation valves, pumps, samplers or audio-visual alarms.

A 4–20 mA output is available for connection to a PLC or SCADA system and the MS1800 can operate from 90–240 V AC or 12 V DC power supplies.

- ✓ Continuous monitoring
- ✓ Low operating costs
- ✓ Low maintenance costs
- ✓ High reliability
- ✓ Field proven technology




Applications

- Monitoring of Total VOC
- **Process VOC Monitoring**
- Environmental Monitoring
- Detection of VOCs in wastewater systems
- Odor Control
- Land Remediation

Installation

Installation is a **simple process** and consists of connecting the instrument to power and fixing it on a wall or surface. Setup uses a user friendly app running on a laptop PC.



TECHNICAL SPECIFICATION

PARAMETER	OPERATIONAL REQUIREMENTS		NOTES
	<i>Minimum</i>	<i>Maximum</i>	
Supply Voltage	90 V AC	240 V AC	50 Hz or 60 Hz. 12 V DC option available
Power Consumption		9 W	Typical 7 W during operation
Working Temp: Ambient	0 °C / 32 °F	50 °C / 122 °F	Higher temperature available
Sampling Period	Continuous measurement		
Instrument Case	IP65 / NEMA 4X		ABS
Detection Range	1 ppm	500 ppm	Measured against target gas standard. For calibration using specific compounds contact Multisensor Systems
Accuracy	-10%	+10%	15 ppm sample measured at 20 °C
Analog Output	4 mA	20 mA	Scalable to range required, max load 900 Ω
Analog Output Isolation	400 V DC		
Relay Voltage		50 V	Alarm and Fault Relays with NO and NC contacts
Relay Current		5 A	
Data Interface	USB-A to PC		Using Multisensor Software provided
Data Storage	μSD Card		Instrument lifetime data stored
Weight	5 kg / 11 lbs		
Dimensions	300 x 200 x 130 mm 11.8 x 7.8 x 5.1 inches		

Typical Target Compounds

Petroleum Gas	Kerosene	Iso-butylene	Xylene	Methanol
Methane	Ethanol	Toluene	Heptane	Mercaptan
Iso Butane	Diesel	Acetone	Benzene	

Consumables

Every 6 Months:	Dust Filter Elements
Every 12 Months:	Air Pump



Multisensor Systems is a developer and supplier of Water and Gas Analyzers specializing in oil in water, hydrocarbon analyzers, oil in water detectors, THM Analyzers and Ammonia Analyzers based in the United Kingdom.

The contents of this publication are provided to you "as is" without warranty of any kind, and are subject to change without notice. Multisensor systems does not assume any responsibility or liability for any damage, whether direct or indirect, relating to the use of this publication.

Multisensor Systems Ltd., Alexandra Court, Carrs Road, Cheadle, SK8 2JY, United Kingdom

www.multisensorsystems.com
e: info@multisensorsystems.com
p: +44 (0)161 491 5600