

ELECTRIC STRAPPING TOOL FOR POLYPROPYLENE AND POLYESTER STRAP WITH VIBRATION SEALING



TECHNICAL SPECIFICATIONS	
DIMENSIONS	
Length	315 mm • 12.4"
Width	140 mm • 5.5"
Height	183 mm • 7.2"
Weight	3.8 kgs • 8,4lb
FEEDING	
Battery	14.8V - 3 A/h LI-PO
PERFORMANCE	
Max. tension force	5000N
Tensioning speed	12mt/m
Sealing	friction weld seal
Joint strength	80% of plastic strap strength*

\* depends of strap quality

MODEL			
CODE	TYPE	STRAP	THICKNESS
T239997	ITA23 - 16/19mm 5/8"-3/4" with one battery	PET 16mm - 5/8"	1.05 mm - 0.041"
		PET 19mm - 3/4"	0.8 mm 0.031" - 1.27 mm 0.050"
T2399971	ITA23 - 16/19mm 5/8"-3/4" with one battery and charger	PET 16mm - 5/8"	1.05 mm - 0.041"
		PET 19mm - 3/4"	0.8 mm 0.031" - 1.27 mm 0.050"
T2399972	ITA23 - 16/19mm 5/8"-3/4" with two batteries and charger	PET 16mm - 5/8"	1.05 mm - 0.041"
		PET 19mm - 3/4"	0.8 mm 0.031" - 1.27 mm 0.050"

POLYESTER STRAP



POLYESTER STRAP



POLYPROPYLENE STRAP

