C E (150) (150)

Laboratory Refrigerator





BPR-5V68

BPR-5V108

Technical Parameters

Model		BPR-5V68	BPR-5V108	
External Size(W*D*H)mm		495*548*683	495*548*934	
Internal Size(W*D*H)mm		415*405*455	415*405*706	
Capacity		68L	108L	
Temperature Range		2~8℃		
Temperature Accuracy		0.1℃		
Control System		Microprocessor Control		
Alarm		Audible and visual alarm for: High and low temperature, Door Ajar, Thermostat failure		
Refrigeration Type		Forced air refrigeration system		
Refrigerant		R600a		
Climate Type		N, SN		
Glass Door		Toughened with electric heating function,no condensation		
	Constructure	Polyurethane cyclopentane foams		
Construction	Internal material	Spraying steel plate		
	External material	Spraying steel plate		
Consumption		92W	92W	
Power Supply		AC220V±10%, 50/60Hz; AC110V±10%, 50/60Hz		
Shelves		2pcs, cold drawn steel wire impregnated shelf	3 pcs,cold drawn steel wire impregnated shelf	
Door Lock		1 pcs		
Accessory		Standard: USB Port, LED Lamp		
		Optional: temperature recorder, printer(USBport can not be selected at the same time)		
Package Size(W*D*H)mm		560*668*858	560*668*1109	
Gross Weight(kg)		49	61	

Laboratory Refrigerator





260L

Technical Parameters

BPR-5V360	
660*655*1980 360L	
2~8℃ 7 _{0.1℃} base.cc / www.meihuatrade.com	
Microprocessor Control, Large Screen LED Display	
Audible and visual alarm for: High temperature & sensor failure, door ajar, Power failure alarm, Low battery alarm.	
Forced air refrigeration system	
R134a, CFC Free	
Bundy tube condenser	
Frostless design	
Unibody design & mono-assembly foaming (Rigid polyurethane insulation material)	
HIPS engineering plastics, abrasion and acid resistant	
Cold-rolled steel coated with anti-bacteria powder	
Adjustable shelves made of high quality steel wire	
5 pcs	
350W	
AC220V±10%, 50/60Hz	
LED lamp & shelves, USB, probe access port, door keys	
720*750*2150	
124	
t	

10 11