

Wet Film Comb Thickness Gauges

The Wet Film Thickness Gauges are made of a comb-shaped design with precision cut gaps to determine the coating thickness by placing vertically onto a wet coated substrate. It is a corrosion-resistant stainless steel with a hole at the top corner so that a string (not supply) can be attached for hooking.

All Wet Film Thickness Gauges are machined by high precision CNC and with less than 3 micron deviation. They come standard with 10 gaps or more with inscriptions of the thickness at the side of each gap. It is recommended to replace a new gauge if there are chips, crack or uneven at the gap (s) of the gauge.



◆ Ordering Information :

BGD 531/1 : 10 μm–100 μm (Stainless steel , @10 μm)
BGD 531/2 : 20 μm–200 μm (Stainless steel , @20 μm)
BGD 531/3 : 50 μm–750 μm (Stainless steel , @25 μm/@50 μm)
BGD 531/4 : 250 μm–700 μm (Stainless steel , @50 μm)
BGD 531/5 : 50 μm–950 μm (Stainless steel , @100 μm)
BGD 531/6 : 300 μm–2600 μm (Stainless steel , Quadrilateral @25 μm /100 μm)
BGD 531/7 : 25 μm–3,000 μm (Stainless steel , Hexagon)
BGD 531/11 : 0.2mils–6mils (Aluminum , Hexagon , Min.order ≥ 1,000pcs)
BGD 531/12 : 1mils–80mils (Aluminum , Rectangle , Min.order ≥ 1,000pcs)

Note: BGD 531/11 and BGD 531/12 can be marked with customer's Logo if required

