

## -25°C Freezer



## -40°C Freezer



### Technical Parameters

Model	BDF-25H110	BDF-25H210	BDF-25H310
External Size	705*705*885mm	945*785*885mm	1225*790*885mm
Capacity	110L	210L	310L
Temperature Range	-10°C~-25°C		
Temperature Accuracy	0.1°C		
Control System	Microprocessor Control		
Alarm	High or low temperature alarm, Sensor failure, Power failure, Battery switch alarm		
Refrigeration Type	Direct refrigeration		
Refrigerant	R290, 50g	R290, 45g	R290, 65g
Evaporator	Material of copper		
Construction	Structure	Unibody Design, Rigid polyurethane insulation material	
	Internal Material	304 Stainless steel	
	External Material	Powder coated cold rolled steel plate	
Consumption	270w	260w	345w
Power Supply	Standard: 220V 50Hz, optional: 220V 60Hz, 110V 60Hz		
Packing Size	805*800*1015mm	1045*880*1015mm	1325*885*1015mm
Gross Weight	73kg	88kg	101kg

### Technical Parameters

Model	BDF-40H110	BDF-40H210	BDF-40H310
External Size	705*705*885mm	945*785*885mm	1225*790*885mm
Capacity	110L	210L	310L
Temperature Range	-15°C~-40°C		
Temperature Accuracy	0.1°C		
Control System	Microprocessor Control		
Alarm	High or low temperature alarm, Sensor failure, Power failure, Battery switch alarm		
Refrigeration Type	Direct refrigeration		
Refrigerant	R290, 55g	R290, 60g	R290, 65g
Evaporator	Material of copper		
Construction	Structure	Unibody Design, Rigid polyurethane insulation material	
	Internal Material	304 Stainless steel	
	External Material	Powder coated cold rolled steel plate	
Consumption	270w	280w	290w
Power Supply	Standard: 220V 50Hz, optional: 220V 60Hz, 110V 60Hz		
Packing Size	805*800*1015mm	1045*880*1015mm	1325*885*1015mm
Gross Weight	73kg	88kg	101kg