

## Horizontal Cylindrical Pressure Autoclave



### Features:

**\* Brand New Operation Interface**

The LCD touch screen can display temperature, time, operating status, and fault alarm in real time, making the sterilization information more intuitive and clear, and it is convenient for users to observe the operating status of the equipment.

**\* Drying Function**

With auxiliary drying function, it is used to dry sterilized items.

**\* Protection Device**

Equipped with over-temperature and over-pressure automatic protection devices.

**\* Steam Generator**

The equipment has a built-in high-speed steam generator, which saves time and effort without external steam source.

**\* Automatic Operation of The Program**

The equipment is externally connected to the water source, and there is no need for manual water replenishment. After the customer selects the program, the equipment can complete the entire process from water injection to drying without human intervention. After the program is completed, the sound prompts that the sterilization is complete.

**\* Programs: Wrapped, Unwrapped, Dressing, Rubber, Drying, DIY solid**

### Technical Parameters:

Model	BKQ-H150	BKQ-H200	BKQ-H300	BKQ-H400
Volume	150L	200L	300L	400L
Design Pressure	0.28MPa			
Rated Operating Temperature	121°C/134°C			
Rated working pressure	0.12MPa/0.23MPa			
Chamber Material	S30408			
Power Supply	Standard: 380V 50/60Hz three phase; optional: 220V 50/60Hz three phase, 220V 50/60Hz one phase			
Rated Power	16kW			
Ambient Temperature	5-40°C			
Sterilization Time Adjustable Range	0-99min			
Adjustable Drying Time Range	0-99min			
Adjustable Drying Temperature Range	115°C-134°C			
Chamber Size (Φ * L) mm	Φ500*820	Φ500*1050	Φ650*935	Φ650*1235
Packing Size (L*D*H) mm	1370*820*1880	1600*820*1880	1650*950*1980	1950*950*1980
Gross Weight (kg)	320	355	475	535