

Metallurgical Microscope



Technical Parameters:

	Specification	Model			
		XJD-100	XJD-200	XDS-1	4XC
	Monocular Head Inclined at 45°	V			
Viewing Head	Sliding Binocular Head Inclined at 45°		V		
	Sliding Trinocular Head Inclined at 45°			V	
	Compensation Free Trinocular Head30°	plopas	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	√	
Nosepiece	Ball Beating Quadruple Nosepiece	V	√	√	√
4/	WF10X,WF12.5X	V	1	\doldsymbol{\dolds	Ja aar
Eyepiece	WF10X20mm	AA AA AA	. III CIIII	ualial	1
o	100X(S. Oil)	1	√		
Objective	Infinity metallurgical objectives 4X, 10X, 20X(S), 40X				1
0.	Double Layer Mechanical Stage 242*172mm moving range 75*50mm				1
Stage	Double Layer Mechanical Stage 135*140mm moving range 70*50mm	1	1	V	
Focusing	Coaxial coarse&fine focusing adjustment with rack and pinion mechanism fine focusing scale value 0.002mm	1	1	V	√
Illumination	Build-in Illumination, Halogen lamp 6V/20W,	V	√	√	√
Filter	Blue, Green, Yellow	√	√	√	√
Power Supply	AC110/220V±10%, 50/60Hz	√	1	√	√
Package Size	300*400*520mm	√	√	V	√
Gross Weight	12kg	√	1	V	√

Note: 110V/220V for LED lamp , 220V only for Halogen lamp

Optional: 2.0, 3.0 or 5.0 Megapixel, CMOS electronic eyepiece(only for Trinocular microscope)

Metallurgical Microscope



Technical Parameters:

Model		MM-5000
Optical System	Infinite optical system	√
	EW10×/22	
Extra Wide Field Eyepiece	EW10×/20 eyepiece with scale of cross hair	
	EW15×/16	
	EW20×/12	•
	5×/0.12/∞/0(BF/DF) LWD 10mm	√
Infinite LWD Plan	10×/0.25/∞/0(BF/DF) LWD 10mm	√
	20×/0.4/∞/0(BF/DF) LWD 5mm	√
Achromatic Objective	50×/0.75/∞/0(BF/DF) LWD 1.3mm	1
	100×/0.9/∞/0(BF/DF) LWD 0.7mm	1
Viewing Head	Siedentopf binocular viewing head, Inclined at 30°, Interpupillary 48~75mm	√
	12V/50W halogen light, center and brightness adjustable	√
Malata badda aki takk	Polarizer and analyzer	
Kohler Incident Light	DIC	
	Built-in green, blue, yellow, gray and ground glass	
Focusing	Coaxial coarse and fine adjustment, fine division 2µm,	√
Nosepiece	Backward quintuple nosepiece	√
0.	Double layer mechanical stage 226×178mm, Moving range 40mm×40mm	√
Stage	Stage Φ20, Φ30, teardrop	
Accessories	Photo/Video attachment	
Accessories	Micrometer scale 0.01mm	
Power Supply	AC110/220V±10%, 50/60Hz	√
Package Size	730*350*550mm	√
Gross Weight	18kg	√

Note: √ Standard Outfit, • Optional Outfit

25